Safety Data Sheet
according to WHS Regulations

Date of issue: 16.07.2026 Version number 38 Revision: 16.07.2026

Hazardous according to criteria of Australian Safety and Compensation Council.

1 Identification

· **Other means of identification**

· **Trade name:** GRF GASLEAKDETECTOR AE 400ML*12 L313
· **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
· **Application of the substance / the mixture** Metal-working product

· **Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**
Bison International B.V.
Dr.A.F.Philipsstraat 9
NL-4462 EW Goes
PO Box 160
NL-4460 AD Goes
tel. +31 88 3235700
fax. +31 88 3235800
e-mail: sds@boltonadhesives.com

FABER - CASTELL
15 GIBBON RD.
WINSTON HILL
NSW 2153
Toll Free: 1800 677 885
Free Fax: 1800 678 608
EMAIL: enquiries@faber-castell.com.au

· **Further information obtainable from:** PSRA
· **Emergency telephone number:**
POISONS INFORMATION CENTRE (PIC)
TEL: 13 11 26

2 Hazard(s) Identification

· **Classification of the substance or mixture**
Aerosols – Category 3 H229 Pressurized container: may burst if heated.

· **Label elements**
· **Hazard pictograms** Void
· **Signal word** Warning
· **Hazard statements**
H229 Pressurized container: may burst if heated.
· **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P251 Pressurized container: Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

(Contd. on page 2)

Safety Data Sheet
according to WHS Regulations

Date of issue: 16.07.2026 Version number 38 Revision: 16.07.2026

Trade name: GRF GASLEAKDETECTOR AE 400ML*12 L313

(Contd. of page 1)

· **Other hazards**
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable

*
3 Composition and Information on Ingredients

· **Chemical characterisation: Mixtures**
· **Description:** Metal working product

· **Dangerous components:**

10024-97-2	dinitrogen oxide Oxidising gases – Category 1, H270; Gases under pressure – Liquefied gas, H280; Specific target organ toxicity (single exposure) – Category 3, H336	<10%
102-71-6	Triethanolamine Skin corrosion/irritation – Category 2, H315; Eye damage/irritation – Category 2A, H319; Specific target organ toxicity (single exposure) – Category 3, H335	<10%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

· **General information:** No special measures required.
· **After inhalation:**
Supply fresh air; consult doctor in case of complaints.
No special measures required.
· **After skin contact:** Generally the product does not irritate the skin.
· **After eye contact:** Rinse opened eye for several minutes under running water.
· **After swallowing:** If symptoms persist consult doctor.
· **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire Fighting Measures

· **Suitable extinguishing agents:**
Use fire extinguishing methods suitable to surrounding conditions.
· **Special hazards arising from the substance or mixture**
No further relevant information available.
· **Protective equipment:** No special measures required.

AU

(Contd. on page 3)

Safety Data Sheet
according to WHS Regulations

Date of issue: 16.07.2026 Version number 38 Revision: 16.07.2026

Trade name: GRF GASLEAKDETECTOR AE 400ML*12 L313

(Contd. of page 2)

6 Accidental Release Measures

· **Personal precautions, protective equipment and emergency procedures** Not required
· **Environmental precautions:** No special measures required.
· **Methods and material for containment and cleaning up:**
Absorb liquid components with liquid-binding material.
· **Reference to other sections**
No dangerous substances are released.
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and Storage

· **Handling:**
· **Precautions for safe handling** No special precautions are necessary if used correctly.
· **Information about fire - and explosion protection:** No special measures required.
· **Storage:**
· **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
· **Information about storage in one common storage facility:** Not required
· **Further information about storage conditions:** None.
· **Storage class:** 2 B
· **Specific end use(s)** No further relevant information available.

8 Exposure controls and personal protection

· **Appropriate engineering controls** No further data; see section 7.

· **Ingredients with limit values that require monitoring at the workplace:**	
10024-97-2 dinitrogen oxide	
WES	Long-term value: 45 mg/m³, 25 ppm
102-71-6 Triethanolamine	
WES	Long-term value: 5 mg/m³ Sen

· **Additional information:** The lists valid during the making were used as basis.
· **Personal protective equipment:**
· **General protective and hygienic measures:**
The usual precautionary measures are to be adhered to when handling chemicals.
Wash hands before breaks and at the end of work.
· **Respiratory protection:** Not required
· **Protection of hands:**
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 4)

Safety Data Sheet
according to WHS Regulations

Date of issue: 16.07.2026 Version number 38 Revision: 16.07.2026

Trade name: GRF GASLEAKDETECTOR AE 400ML*12 L313

(Contd. of page 3)

· **Material of gloves**
Recommended thickness of the material: > 0,12 mm
Nitrile rubber, NBR
· **Penetration time of glove material**
For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).
· **Eye protection:** Not required

9 Physical and Chemical Properties

· **General Information**	
· **Appearance:**	
· **Form:**	Aerosol
· **Colour:**	According to product specification
· **Odour:**	Characteristic
· **Odour threshold:**	Not determined
· **pH-value:**	Not determined
· **Change in condition**	
· **Melting point/freezing point:**	0 °C
· **Initial boiling point and boiling range:**	100 °C
· **Flash point:**	Not applicable, as aerosol
· **Flammability**	Not applicable
· **Decomposition temperature:**	Not determined
· **Ignition temperature:**	Product is not selfigniting.
· **Explosive properties:**	Not determined
· **Explosion limits:**	
· **Lower:**	2.6 Vol %
· **Upper:**	12.6 Vol %
· **Vapour pressure at 20 °C:**	23 hPa
· **Vapour pressure at 50 °C:**	123 hPa
· **Density at 20 °C:**	1.04 g/cm³
· **Relative density**	Not determined
· **Vapour density**	Not determined
· **Evaporation rate**	Not applicable.
· **Solubility in / Miscibility with**	
· **water:**	Not miscible or difficult to mix.
· **Partition coefficient: n-octanol/water:**	Not determined
· **Viscosity:**	
· **Dynamic at 20 °C:**	0.952 mPas
· **Kinematic:**	Not determined
· **Solvent content:**	
· **Organic solvents:**	0.4 %
· **Water:**	98.6 %
· **VOC (EC)**	0.40 %
· **Solids content:**	0.0 %

(Contd. on page 5)

Safety Data Sheet
according to WHS Regulations

Date of issue: 16.07.2026 Version number 38 Revision: 16.07.2026

Trade name: GRF GASLEAKDETECTOR AE 400ML*12 L313

(Contd. of page 4)

· **Other information**	All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.
· **Particle characteristics**	Not applicable
· **Physical state**	Aerosol

10 Stability and Reactivity

· **Reactivity** No further relevant information available.
· **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
· **Possibility of hazardous reactions** No dangerous reactions known.
· **Conditions to avoid** No further relevant information available.
· **Incompatible materials:** No further relevant information available.
· **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological Information

· **Information on toxicological effects**
· **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**		
10024-97-2 dinitrogen oxide		
Inhalative	LC50/4 h	1.06 mg/l (rat)
102-71-6 Triethanolamine		
Oral	LD50	8000 mg/kg (rat)

· **Primary irritant effect:**
· **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
· **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
· **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
· **Germ cell mutagenicity**
Not applicable
Based on available data, the classification criteria are not met.
· **Carcinogenicity** Based on available data, the classification criteria are not met.
· **Reproductive toxicity** Based on available data, the classification criteria are not met.
· **STOT-single exposure** Based on available data, the classification criteria are not met.
· **STOT-repeated exposure** Based on available data, the classification criteria are not met.
· **Aspiration hazard** Based on available data, the classification criteria are not met.
· **Interactive effects**
· **Acute effects (acute toxicity, irritation and corrosivity)** Not applicable
· **Sensitisation** Not applicable
· **Repeated dose toxicity** Not applicable

AU

(Contd. on page 6)

Safety Data Sheet
according to WHS Regulations

Date of issue: 16.07.2026 Version number 38 Revision: 16.07.2026

Trade name: GRF GASLEAKDETECTOR AE 400ML*12 L313

(Contd. of page 5)

12 Ecological Information

· **Toxicity**
· **Aquatic toxicity:** No further relevant information available.
· **Persistence and degradability** No further relevant information available.
· **Behaviour in environmental systems:**
· **Bioaccumulative potential** No further relevant information available.
· **Mobility in soil** No further relevant information available.
· **Additional ecological information:**
· **General notes:** Not known to be hazardous to water.
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable
· **Other adverse effects** No further relevant information available.


13 Disposal considerations

· **Waste treatment methods**
· **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Disposal must be made according to official regulations.

· **Uncleaned packaging:**
· **Recommendation:**
Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14 Transport information

· **UN-Number**	
· **ADG, IMDG, IATA**	UN1950
· **UN proper shipping name**	
· **ADG**	1950 AEROSOLS
· **IMDG**	AEROSOLS
· **IATA**	AEROSOLS, non-flammable
· **Transport hazard class(es)**	
· **ADG**	



· **Class**	2 5A Gases.

(Contd. on page 7)

AU

Safety Data Sheet
according to WHS Regulations

Date of issue: 16.07.2026 Version number 38 Revision: 16.07.2026

Trade name: GRF GASLEAKDETECTOR AE 400ML*12 L313

(Contd. of page 6)

· **Label**	2.2
· **IMDG, IATA**	
	
· **Class**	2.2 Gases.
· **Label**	2.2
· **Packing group**	
· **ADG, IMDG, IATA**	not regulated
· **Environmental hazards:**	
· **Marine pollutant:**	No
· **Special precautions for user**	Warning: Gases.
· **Hazard identification number (Kemler code):**	-
· **EMS Number:**	F-D,S-U
· **Stowage Code**	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· **Segregation Code**	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· **Transport in bulk according to Annex II of Marpol and the IBC Code**	Not applicable
· **Transport/Additional information:**	
· **Quantity limitations**	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg
· **ADG**	
· **Limited quantities (LQ)**	1L
· **Excepted quantities (EQ)**	Code: E0 Not permitted as Excepted Quantity
· **Transport category**	3
· **Tunnel restriction code**	E
· **IMDG**	
· **Limited quantities (LQ)**	1L

(Contd. on page 8)

AU

Safety Data Sheet
according to WHS Regulations

Date of issue: 16.07.2026 Version number 38 Revision: 16.07.2026

Trade name: GRF GASLEAKDETECTOR AE 400ML*12 L313

(Contd. of page 7)

· **Excepted quantities (EQ)**	Code: E0 Not permitted as Excepted Quantity
· **UN "Model Regulation":**	UN 1950 AEROSOLS, 2.2

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Australian Inventory of Industrial Chemicals**	
7732-18-5	water, distilled, conductivity or of similar purity
102-71-6	Triethanolamine

· **Standard for the Uniform Scheduling of Medicines and Poisons**		
10024-97-2	dinitrogen oxide	S4
102-71-6	Triethanolamine	S4, S5

· **Australia: Priority Existing Chemicals**
None of the ingredients is listed.

· **GHS label elements**
The product is classified and labelled according to the Globally Harmonised System (GHS).
· **Hazard pictograms** Void
· **Signal word** Warning
· **Hazard statements**
H229 Pressurized container: may burst if heated.
· **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P251 Pressurized container: Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

· **Directive 2012/18/EU**
· **Named dangerous substances - ANNEX I** None of the ingredients is listed.
· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**
H270 May cause or intensify fire; oxidizer.
H280 Contains gas under pressure; may explode if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

· **Department issuing SDS:** PSRA

(Contd. on page 9)

Safety Data Sheet
according to WHS Regulations

Date of issue: 16.07.2026 Version number 38 Revision: 16.07.2026

Trade name: GRF GASLEAKDETECTOR AE 400ML*12 L313

(Contd. of page 8)

· **Contact:** PSRA

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Aerosols – Category 3: Aerosols – Category 3
Oxidising gases – Category 1: Oxidizing gases – Category 1
Gases under pressure – Liquefied gas: Gases under pressure – Liquefied gas
Skin corrosion/irritation – Category 2: Skin corrosion/irritation – Category 2
Eye damage/irritation – Category 2A: Serious eye damage/eye irritation – Category 2A
Specific target organ toxicity (single exposure) – Category 3: Specific target organ toxicity (single exposure) – Category 3

· *** Data compared to the previous version altered.**

AU