Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.07.2026 Version number 35 (replaces version 34) Revision: 17.07.2026

*

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name:** GRF UNI-100 GT TI 5L*1 L001

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.

· **Application of the substance / the mixture** Adhesive

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**
Bison International
Dr.A.F.Philipsstraat 9
NL-4462 EW Goes
PO Box 160
NL-4460 AD Goes
tel. +31 88 3235700
fax. +31 88 3235800
e mail: sds@boltonadhesives.com

· **Further information obtainable from:** PSRA

· **1.4 Emergency telephone number:**
National Poisons Information Centre: +353 (1) 809 2166 (8.00 a.m. to 10.00 p.m. 7 days a week)
Healthcare Professionals: +353 (1) 809 2566 (24 hour service)

*

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 2	H225 Highly flammable liquid and vapour.
Acute Tox. 4	H302 Harmful if swallowed.
Skin Irrit. 2	H315 Causes skin irritation.
Eye Dam. 1	H318 Causes serious eye damage.
Carc. 2	H351 Suspected of causing cancer.
STOT SE 3	H335 May cause respiratory irritation.

· **2.2 Label elements**

· **Classification needs to be in accordance with the NZ Hazardous Substances (Hazard Classification) Notice 2020**
The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02 GHS05 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**
Cyclohexanone
Tetrahydrofuran

(Contd. on page 2)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.07.2026 Version number 35 (replaces version 34) Revision: 17.07.2026

Trade name: GRF UNI-100 GT TI 5L*1 L001

(Contd. of page 1)

· **Hazard statements**
H225 Highly flammable liquid and vapour.
H302 Harmful if swallowed.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H351 Suspected of causing cancer.
H335 May cause respiratory irritation.
· **Precautionary statements**

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing vapours.
P280	Wear protective gloves / eye protection.
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container in accordance with national regulations.

· **2.3 Other hazards**
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable

· **Determination of endocrine-disrupting properties**

128-37-0	Butylated hydroxytoluene	List II

*
SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**
· **Description:** Adhesive

· **Dangerous components:**

CAS: 108-94-1 EINECS: 203-631-1 Index number: 606-010-00-7 Reg.nr.: 01-2119453616-35-XXXX	Cyclohexanone Flam. Liq. 3, H226; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; STOT SE 3, H335	25-50%

(Contd. on page 3)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.07.2026 Version number 35 (replaces version 34) Revision: 17.07.2026

Trade name: GRF UNI-100 GT TI 5L*1 L001

(Contd. of page 2)

CAS: 109-99-9 EINECS: 203-726-8 Index number: 603-025-00-0 Reg.nr.: 01-2119444314-46-XXXX	Tetrahydrofuran Flam. Liq. 2, H225; Carc. 2, H351; Acute Tox. 4, H302; Eye Irrit. 2, H319; STOT SE 3, H335, EUH019 Specific concentration limits: Eye Irrit. 2; H319:C ≥ 25 % STOT SE 3; H335: C ≥ 25 %	25-50%
CAS: 128-37-0 EINECS: 204-881-4 Reg.nr.: 01-2119555270-46-XXXX 01-2119565113-46-XXXX	Butylated hydroxytoluene Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥0.025-<0.25%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

*
SECTION 4: First aid measures

· **4.1 Description of first aid measures**
· **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
· **After inhalation:**
Call a doctor immediately.
In case of unconsciousness place patient stably in side position for transportation.
· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
· **After eye contact:**
Rinse opened eye for several minutes under running water. Then consult a doctor.
· **After swallowing:**
Rinse out mouth and then drink plenty of water.
Call for a doctor immediately.
· **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
· **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**
· **Suitable extinguishing agents:**
Water haze
Alcohol resistant foam
Fire-extinguishing powder
Carbon dioxide
· **For safety reasons unsuitable extinguishing agents:** Water with full jet
· **5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
· **5.3 Advice for firefighters**
· **Protective equipment:** No special measures required.

(Contd. on page 4)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.07.2026 Version number 35 (replaces version 34) Revision: 17.07.2026

Trade name: GRF UNI-100 GT TI 5L*1 L001

(Contd. of page 3)

· **Additional information**
Cool endangered receptacles with water spray.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
· **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
· **6.3 Methods and material for containment and cleaning up:**
Send for recovery or disposal in suitable receptacles.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralising agent.
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
· **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

*
SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
· **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.

· **7.2 Conditions for safe storage, including any incompatibilities**
· **Storage:**
· **Requirements to be met by storerooms and receptacles:** Store in a cool location.
· **Information about storage in one common storage facility:** Not required
· **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
· **Storage class:** 3
· **7.3 Specific end use(s)** No further relevant information available.

IE

(Contd. on page 5)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.07.2026 Version number 35 (replaces version 34) Revision: 17.07.2026

Trade name: GRF UNI-100 GT TI 5L*1 L001

(Contd. of page 4)

*

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**	
108-94-1 Cyclohexanone	
OEL (Ireland)	Short-term value: 81.6 mg/m³, 20 ppm Long-term value: 40.8 mg/m³, 10 ppm Skin, IOELV
IOELV (EU)	Short-term value: 81.6 mg/m³, 20 ppm Long-term value: 40.8 mg/m³, 10 ppm Skin
109-99-9 Tetrahydrofuran	
OEL (Ireland)	Short-term value: 300 mg/m³, 100 ppm Long-term value: 150 mg/m³, 50 ppm Skin, IOELV
IOELV (EU)	Short-term value: 300 mg/m³, 100 ppm Long-term value: 150 mg/m³, 50 ppm Skin
128-37-0 Butylated hydroxytoluene	
OEL (Ireland)	Long-term value: 2 mg/m³

· **DNELs**		
108-94-1 Cyclohexanone		
Oral	Consumer, oral, shortterm exposition	1.5 mg/kg bw/day
	Consumer, oral, longterm exposition	1.5 mg/kg bw/day
Dermal	Worker, dermal, shortterm exposition	4 mg/kg bw/day
	Worker, dermal, longterm exposition	4 mg/kg bw/day
	Consumer, dermal, shortterm exposition	1 mg/kg bw/day
	Consumer, dermal, longterm exposition	1 mg/kg bw/day
Inhalative	Worker, inhalative, shortterm exposition	20 mg/m³
	Worker, inhalative, longterm exposition	10 mg/m³
	Consumer DNEL, acute inhalation	5 mg/m³
	Consumer, inhalative, longterm exposition	2.55 mg/m³
109-99-9 Tetrahydrofuran		
Oral	Consumer, oral, longterm exposition	1.5 mg/kg bw/day
Dermal	Worker, dermal, longterm exposition	12.6 mg/kg bw/day
	Consumer, dermal, longterm exposition	1.5 mg/kg bw/day
Inhalative	Worker, inhalative, shortterm exposition	96 mg/m³
	Worker, inhalative, longterm exposition	72.4 mg/m³
	Consumer DNEL, acute inhalation	52 mg/m³
	Consumer, inhalative, longterm exposition	13 mg/m³
128-37-0 Butylated hydroxytoluene		
Oral	Consumer, oral, longterm exposition	0.25 mg/kg bw/day

(Contd. on page 6)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.07.2026 Version number 35 (replaces version 34) Revision: 17.07.2026

Trade name: GRF UNI-100 GT TI 5L*1 L001

(Contd. of page 5)

Dermal	Worker, dermal, longterm exposition	0.5 mg/kg bw/day
	Consumer, dermal, longterm exposition	0.25 mg/kg bw/day
Inhalative	Worker, inhalative, longterm exposition	1.76 mg/m³
	Consumer, inhalative, longterm exposition	0.435 mg/m³

· **PNECs**

108-94-1 Cyclohexanone

	Fresh water	0.356 mg/l
	Fresh water sediment	2.69 mg/kg dry weight
	Marine water	0.036 mg/l
	Marine sediment	0.269 mg/kg dry weight
	Soil	0.328 mg/kg
	Sewage treatment plant	10 mg/l
	Sporadic release	3.23 mg/l

109-99-9 Tetrahydrofuran

Oral	Secondary Poisoning	67 mg/kg
	Fresh water	4.32 mg/l
	Fresh water sediment	23.3 mg/kg dry weight
	Marine water	0.432 mg/l
	Marine sediment	2.33 mg/kg dry weight
	Soil	2.13 mg/kg
	Sewage treatment plant	4.6 mg/l
	Sporadic release	21.6 mg/l

128-37-0 Butylated hydroxytoluene

	Fresh water	0.000199 mg/l
	Fresh water sediment	0.45819 mg/kg dry weight
	Marine water	0.0000199 mg/l
	Marine sediment	0.04582 mg/kg dry weight
	Soil	0.0539 mg/kg
	Sewage treatment plant	0.017 mg/l

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**
· **Appropriate engineering controls** No further data; see section 7.
· **Individual protection measures, such as personal protective equipment**
· **General protective and hygienic measures:**
The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Do not inhale gases / fumes / aerosols.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

(Contd. on page 7)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.07.2026 Version number 35 (replaces version 34) Revision: 17.07.2026

Trade name: GRF UNI-100 GT TI 5L*1 L001

(Contd. of page 6)

· **Respiratory protection:**
Suitable respiratory protective device recommended.
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Use suitable respiratory protective device in case of insufficient ventilation.
· **Recommended filter device for short term use:** Filter A
· **Hand protection**
Solvent resistant gloves


Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
· **Material of gloves**
Recommended thickness of the material: > 0,12 mm
Nitrile rubber, NBR
· **Penetration time of glove material**
For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).
· **Eye/face protection**


Tightly sealed goggles

Goggles recommended during refilling
· **Body protection:**
Use protective suit.
Solvent resistant protective clothing

*
SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**	
· **General Information**	
· **Physical state**	Liquid
· **Colour:**	According to product specification
· **Odour:**	Characteristic
· **Odour threshold:**	Not determined
· **Melting point/freezing point:**	Undetermined
· **Boiling point or initial boiling point and boiling range**	65.5 °C
· **Flammability**	Highly flammable.
· **Lower and upper explosion limit**	
· **Lower:**	1.3 Vol %
· **Upper:**	12 Vol %

(Contd. on page 8)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.07.2026 Version number 35 (replaces version 34) Revision: 17.07.2026

Trade name: GRF UNI-100 GT TI 5L*1 L001

(Contd. of page 7)

· **Flash point:**	-21 °C
· **Auto-ignition temperature:**	230 °C
· **Decomposition temperature:**	Not determined
· **pH**	Not determined
· **Viscosity:**	
· **Kinematic viscosity**	Not determined
· **Dynamic at 20 °C:**	1325 mPas
· **Solubility**	
· **water:**	Not miscible or difficult to mix.
· **Partition coefficient n-octanol/water (log value)**	Not determined
· **Vapour pressure at 20 °C:**	200 hPa
· **Density and/or relative density**	
· **Density at 20 °C:**	0.998 g/cm³
· **Relative density**	Not determined
· **Vapour density**	Not determined

· **9.2 Other information**	All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.
· **Appearance:**	
· **Form:**	Fluid
· **Important information on protection of health and environment, and on safety.**	
· **Ignition temperature:**	Product is not selfigniting.
· **Explosive properties:**	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· **Solvent content:**	
· **Organic solvents:**	79.1 %
· **VOC (EC)**	79.10 %
· **Change in condition**	
· **Evaporation rate**	Not determined

· **Information with regard to physical hazard classes**	
· **Explosives**	Void
· **Flammable gases**	Void
· **Aerosols**	Void
· **Oxidising gases**	Void
· **Gases under pressure**	Void
· **Flammable liquids**	Highly flammable liquid and vapour.
· **Flammable solids**	Void
· **Self-reactive substances and mixtures**	Void
· **Pyrophoric liquids**	Void
· **Pyrophoric solids**	Void
· **Self-heating substances and mixtures**	Void
· **Substances and mixtures, which emit flammable gases in contact with water**	Void

(Contd. on page 9)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.07.2026 Version number 35 (replaces version 34) Revision: 17.07.2026

Trade name: GRF UNI-100 GT TI 5L*1 L001

(Contd. of page 8)

· **Oxidising liquids**	Void
· **Oxidising solids**	Void
· **Organic peroxides**	Void
· **Corrosive to metals**	Void
· **Desensitised explosives**	Void

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.
· **10.2 Chemical stability**
· **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
· **10.3 Possibility of hazardous reactions** Corrosive action on metals.
· **10.4 Conditions to avoid** No further relevant information available.
· **10.5 Incompatible materials:** No further relevant information available.
· **10.6 Hazardous decomposition products:** Danger of forming toxic pyrolysis products.

*
SECTION 11: Toxicological information

· **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
· **Acute toxicity** Harmful if swallowed.

· **LD/LC50 values relevant for classification:**

108-94-1 Cyclohexanone		
Oral	LD50	1620 mg/kg (rat)
Dermal	LD50	1100 mg/kg (rabbit)
109-99-9 Tetrahydrofuran		
Oral	LD50	500 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50/4 h	>5000 mg/l (rat)
128-37-0 Butylated hydroxytoluene		
Oral	LD50	>2930 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)

· **Primary irritant effect:**
· **Skin corrosion/irritation**
Causes skin irritation.
· **Serious eye damage/irritation**
Causes serious eye damage.
· **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
· **Germ cell mutagenicity**
Not applicable
Based on available data, the classification criteria are not met.
· **Carcinogenicity** Suspected of causing cancer.
· **Reproductive toxicity** Based on available data, the classification criteria are not met.
· **STOT-single exposure** May cause respiratory irritation.

(Contd. on page 10)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.07.2026 Version number 35 (replaces version 34) Revision: 17.07.2026

Trade name: GRF UNI-100 GT TI 5L*1 L001

(Contd. of page 9)

· **STOT-repeated exposure** Based on available data, the classification criteria are not met.
· **Aspiration hazard** Based on available data, the classification criteria are not met.
· **Additional toxicological information:**
· **Acute effects (acute toxicity, irritation and corrosivity)** Not applicable
· **Sensitisation** Not applicable
· **Repeated dose toxicity** Not applicable
· **11.2 Information on other hazards**

· **Endocrine disrupting properties**		
128-37-0	Butylated hydroxytoluene	List II

*
SECTION 12: Ecological information

· **12.1 Toxicity**
· **Aquatic toxicity:** No further relevant information available.
· **12.2 Persistence and degradability** No further relevant information available.
· **12.3 Bioaccumulative potential** No further relevant information available.
· **12.4 Mobility in soil** No further relevant information available.
· **12.5 Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable
· **12.6 Endocrine disrupting properties**
For information on endocrine disrupting properties see section 11.
· **12.7 Other adverse effects**
· **Additional ecological information:**
· **General notes:**
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Must not reach sewage water or drainage ditch undiluted or unneutralised.

*
SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**
· **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Disposal must be made according to official regulations.

· **European waste catalogue**	
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances

· **Uncleaned packaging:**
· **Recommendation:**
Packagings that may not be cleansed are to be disposed of in the same manner as the product.

IE

(Contd. on page 11)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.07.2026 Version number 35 (replaces version 34) Revision: 17.07.2026

Trade name: GRF UNI-100 GT TI 5L*1 L001

(Contd. of page 10)

SECTION 14: Transport information

· **14.1 UN number or ID number**	
· **ADR/ADN, IMDG, IATA**	UN1133
· **14.2 UN proper shipping name**	
· **ADR/ADN**	1133 ADHESIVES
· **IMDG, IATA**	ADHESIVES
· **14.3 Transport hazard class(es)**	
· **ADR/ADN**	



· **Class**	3 (F1) Flammable liquids.
· **Label**	3
· **IMDG, IATA**	



· **Class**	3 Flammable liquids.
· **Label**	3
· **14.4 Packing group**	
· **ADR/ADN, IMDG, IATA**	III
· **14.5 Environmental hazards:**	
· **Marine pollutant:**	No
· **14.6 Special precautions for user**	Warning: Flammable liquids.
· **Hazard identification number (Kemler code):**	-
· **EMS Number:**	F-E,S-D
· **Stowage Category**	A
· **14.7 Maritime transport in bulk according to IMO instruments**	Not applicable
· **Transport/Additional information:**	
· **Quantity limitations**	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· **ADR/ADN**	
· **Limited quantities (LQ)**	5L
· **Excepted quantities (EQ)**	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· **Transport category**	3
· **Tunnel restriction code**	E

(Contd. on page 12)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.07.2026 Version number 35 (replaces version 34) Revision: 17.07.2026

Trade name: GRF UNI-100 GT TI 5L*1 L001

(Contd. of page 11)

· **IMDG**	
· **Limited quantities (LQ)**	5L
· **Excepted quantities (EQ)**	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· **Remarks:**	For substances with class 3 according to IMDG-Code chapter 2.3.2.2 packing group is classified in packing group III, as viscosity is in accordance with requirements (flow time t > 100s).
· **UN "Model Regulation":**	UN 1133 ADHESIVES, 3, III

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Directive 2012/18/EU**
· **Named dangerous substances - ANNEX I** None of the ingredients is listed.
· **Seveso category** P5c FLAMMABLE LIQUIDS
· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5000 t
· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50000 t
· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**

· **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H318 Causes serious eye damage.

(Contd. on page 13)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.07.2026 Version number 35 (replaces version 34) Revision: 17.07.2026

Trade name: GRF UNI-100 GT TI 5L*1 L001

(Contd. of page 12)

H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
EUH019 May form explosive peroxides.

· **Classification according to Regulation (EC) No 1272/2008**
The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Flammable liquids	Bridging principles
Acute toxicity - oral Skin corrosion/irritation Serious eye damage/irritation Carcinogenicity Specific target organ toxicity (single exposure)	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· **Department issuing SDS:** PSRA
· **Contact:** PSRA
· **Date of previous version:** 19.06.2021
· **Version number of previous version:** 34
· **Abbreviations and acronyms:**
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Carc. 2: Carcinogenicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
· *** Data compared to the previous version altered.**

IE