Safety Data Sheet
acc. to OSHA HCS

Printing date 07/17/2026 Reviewed on 07/17/2026

1 Identification

· **Product identifier**

· **Trade name:** GRF RAPID CEMENT JR 1KG*12 L001
· **Application of the substance / the mixture** Sealant

· **Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**
Bison International
Dr.A.F.Philipsstraat 9
NL-4462 EW Goes
PO Box 160
NL-4460 AD Goes
tel. +31 88 3235700
fax. +31 88 3235800
e mail: sds@boltonadhesives.com

· **Information department:** PSRA
· **Emergency telephone number:**
Bison and Griffon products: +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET)
UHU products: + 49 (0) 30/19240 (Notruf). Operating hours mo-fr 08:00h-17:00h (CET)

For detailed information contact the national Poison Centre @
https://poisoncentres.echa.europa.eu/appointed-bodies

2 Hazard(s) identification

· **Classification of the substance or mixture**

Skin Irritation 2	H315 Causes skin irritation.
Eye Damage 1	H318 Causes serious eye damage.
Sensitization - Skin 1	H317 May cause an allergic skin reaction.
Carcinogenicity 1A	H350 May cause cancer.
Specific Target Organ Toxicity - Single Exposure 3	H335 May cause respiratory irritation.

· **Label elements**
· **Hazard pictograms**



GHS05 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**
Portland Cement
Quartz (SiO2)
· **Hazard statements**
H315 Causes skin irritation.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.
H350 May cause cancer.
H335 May cause respiratory irritation.

(Contd. on page 2)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/17/2026 Reviewed on 07/17/2026

Trade name: GRF RAPID CEMENT JR 1KG*12 L001

(Contd. of page 1)

· **Precautionary statements**

P261	Avoid breathing vapours.
P280	Wear protective gloves / eye protection / face protection.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a poison center/doctor.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container in accordance with national regulations.

· **Classification system:**
· **NFPA ratings (scale 0 - 4)**



Health = 3
Fire = 0
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = *3
Fire = 0
Reactivity = 0

· **Other hazards**
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**
· **Description:** Sealant

· **Dangerous components:**

471-34-1	calcium carbonate	25-50%
65997-15-1	Portland Cement	25-50%
14808-60-7	Quartz (SiO2)	2.5-10%
14808-60-7	Quartz (SiO2)	≥0.1-<1%

4 First-aid measures

· **Description of first aid measures**
· **General information:** No special measures required.
· **After inhalation:**
Call a doctor immediately.
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
· **After eye contact:**
Rinse opened eye for several minutes under running water. Then consult a doctor.
· **After swallowing:** Rinse out mouth and then drink plenty of water.

(Contd. on page 3)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/17/2026 Reviewed on 07/17/2026

Trade name: GRF RAPID CEMENT JR 1KG*12 L001

(Contd. of page 2)

· **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**
· **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
· **Special hazards arising from the substance or mixture**
No further relevant information available.
· **Advice for firefighters**
· **Protective equipment:** No special measures required.

*
6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
· **Methods and material for containment and cleaning up:**
Use neutralizing agent.
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
· **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
· **Protective Action Criteria for Chemicals**

· **PAC-1:**		
471-34-1	calcium carbonate	45 mg/m3
14808-60-7	Quartz (SiO2)	0.075 mg/m3
14808-60-7	Quartz (SiO2)	0.075 mg/m³

· **PAC-2:**		
471-34-1	calcium carbonate	210 mg/m3
14808-60-7	Quartz (SiO2)	8.3 mg/m3
14808-60-7	Quartz (SiO2)	33 mg/m³

· **PAC-3:**		
471-34-1	calcium carbonate	1300 mg/m3
14808-60-7	Quartz (SiO2)	50 mg/m3
14808-60-7	Quartz (SiO2)	200 mg/m³

US

(Contd. on page 4)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/17/2026 Reviewed on 07/17/2026

Trade name: GRF RAPID CEMENT JR 1KG*12 L001

(Contd. of page 3)

7 Handling and storage

· **Handling:**
· **Precautions for safe handling**
Thorough dedusting.
Ensure good ventilation/exhaustion at the workplace.
· **Information about protection against explosions and fires:** No special measures required.

· **Conditions for safe storage, including any incompatibilities**
· **Storage:**
· **Requirements to be met by storerooms and receptacles:** No special requirements.
· **Information about storage in one common storage facility:** Not required
· **Further information about storage conditions:** Keep receptacle tightly sealed.
· **Storage class:** 13
· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see section 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**	
471-34-1 calcium carbonate	
PEL	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction
TLV	TLV withdrawn
65997-15-1 Portland Cement	
PEL	Long-term value: 50 mppcf or 15* 5** mg/m³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction
TLV	Long-term value: 1* mg/m³ E; *as respirable fraction, A4
14808-60-7 Quartz (SiO2)	
PEL	Long-term value: 0.05* mg/m³ *resp. dust; 30mg/m3/%SiO2+2
REL	Long-term value: 0.05* mg/m³ *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m³ *respirable particulate matter, A2
14808-60-7 Quartz (SiO2)	
PEL	Long-term value: 0.05* mg/m³ *resp. dust; 30mg/m3/%SiO2+2

(Contd. on page 5)

US

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/17/2026 Reviewed on 07/17/2026

Trade name: GRF RAPID CEMENT JR 1KG*12 L001

(Contd. of page 4)

REL	Long-term value: 0.05* mg/m³ *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m³ *respirable particulate matter, A2

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**
· **Personal protective equipment:**
· **General protective and hygienic measures:**
The usual precautionary measures for handling chemicals should be followed.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Do not inhale gases / fumes / aerosols.
Avoid contact with the skin.
Avoid contact with the eyes and skin.
· **Breathing equipment:** Suitable respiratory protective device recommended.
· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
· **Material of gloves**
Recommended thickness of the material: > 0,12 mm
Nitrile rubber, NBR
· **Penetration time of glove material**
For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).
· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Use protective suit.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**
· **General Information**
· **Appearance:**

Form:	Solid
Color:	According to product specification

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/17/2026 Reviewed on 07/17/2026

Trade name: GRF RAPID CEMENT JR 1KG*12 L001

(Contd. of page 5)

· **Odor:**	Characteristic
· **Odor threshold:**	Not determined
· **pH-value:**	Not applicable
· **Change in condition**	
Melting point/Melting range:	Undetermined
Boiling point/Boiling range:	2230 °C (4046 °F)
· **Flash point:**	Not applicable
· **Flammability:**	Not determined
· **Decomposition temperature:**	Not determined
· **Ignition temperature:**	Product is not selfigniting.
· **Danger of explosion:**	Product does not present an explosion hazard.
· **Explosion limits:**	
Lower:	Not determined
Upper:	Not determined
· **Vapor pressure at 1732 °C (3149.6 °F):**	13.5 hPa (10.1 mm Hg)
· **Density at 20 °C (68 °F):**	2.47 g/cm³ (20.612 lbs/gal)
· **Relative density**	Not determined
· **Vapor density**	Not applicable
· **Evaporation rate**	Not applicable.
· **Solubility in / Miscibility with**	
Water:	Insoluble.
· **Partition coefficient (n-octanol/water):**	Not determined
· **Viscosity:**	
Dynamic:	Not applicable
Kinematic:	Not applicable
· **Solvent content:**	
VOC content:	0.00 %
Solids content:	100.0 %
· **Other information**	All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.

10 Stability and reactivity

· **Reactivity** No further relevant information available.
· **Chemical stability**
· **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
· **Possibility of hazardous reactions** Corrosive action on metals.
· **Conditions to avoid** No further relevant information available.

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/17/2026 Reviewed on 07/17/2026

Trade name: GRF RAPID CEMENT JR 1KG*12 L001

(Contd. of page 6)

· **Incompatible materials:** No further relevant information available.
· **Hazardous decomposition products:** Danger of toxic pyrolysis products.

11 Toxicological information

· **Information on toxicological effects**
· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**		
471-34-1 calcium carbonate		
Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)

· **Primary irritant effect:**
· **on the skin:** Irritant to skin and mucous membranes.
· **on the eye:** Strong irritant with the danger of severe eye injury.
· **Sensitization:** Sensitization possible through skin contact.
· **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**		
14808-60-7	Quartz (SiO2)	1

· **NTP (National Toxicology Program)**		
14808-60-7	Quartz (SiO2)	K

· **OSHA-Ca (Occupational Safety & Health Administration)**
None of the ingredients is listed.

· **Germ cell mutagenicity** Not applicable

12 Ecological information

· **Toxicity**
· **Aquatic toxicity:** No further relevant information available.
· **Persistence and degradability** No further relevant information available.
· **Behavior in environmental systems:**
· **Bioaccumulative potential** No further relevant information available.
· **Mobility in soil** No further relevant information available.
· **Additional ecological information:**
· **General notes:**
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Must not reach bodies of water or drainage ditch undiluted or unneutralized.
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/17/2026 Reviewed on 07/17/2026

Trade name: GRF RAPID CEMENT JR 1KG*12 L001

(Contd. of page 7)

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**
· **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
Disposal must be made according to official regulations.

· **Uncleaned packagings:**
· **Recommendation:**
Packagings that cannot be cleansed are to be disposed of in the same manner as the product.

14 Transport information

· **UN-Number**	
· **DOT, ADN**	not regulated
· **ADR/ADN, IMDG, IATA**	not regulated -
· **UN proper shipping name**	
· **DOT, ADR/ADN, ADN, IMDG, IATA**	not regulated
· **Transport hazard class(es)**	
· **DOT, ADR/ADN, ADN, IMDG, IATA**	
· **Class**	not regulated
· **Packing group**	
· **DOT, ADR/ADN, IMDG, IATA**	not regulated
· **Environmental hazards:**	
· **Marine pollutant:**	No
· **Special precautions for user**	Not applicable
· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**	Not applicable
· **Transport/Additional information:**	Not dangerous according to the above specifications.
· **UN "Model Regulation":**	not regulated

US

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/17/2026 Reviewed on 07/17/2026

Trade name: GRF RAPID CEMENT JR 1KG*12 L001

(Contd. of page 8)

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
· **Sara**

· **Section 355 (extremely hazardous substances):**
None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**
None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**
All components have the value ACTIVE.

· **Hazardous Air Pollutants**
None of the ingredients is listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

14808-60-7	Quartz (SiO2)

· **Chemicals known to cause reproductive toxicity for females:**
None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**
None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**
None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**
None of the ingredients is listed.

· **TLV (Threshold Limit Value)**

14808-60-7	Quartz (SiO2)	A2

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

14808-60-7	Quartz (SiO2)

· **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
· **Hazard pictograms**



GHS05 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**
Portland Cement
Quartz (SiO2)

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/17/2026 Reviewed on 07/17/2026

Trade name: GRF RAPID CEMENT JR 1KG*12 L001

(Contd. of page 9)

· **Hazard statements**
H315 Causes skin irritation.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.
H350 May cause cancer.
H335 May cause respiratory irritation.

· **Precautionary statements**

P261	Avoid breathing vapours.
P280	Wear protective gloves / eye protection / face protection.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a poison center/doctor.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container in accordance with national regulations.

· **National regulations:**

· **Information about limitation of use:**
Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** PSRA
· **Contact:** PSRA
· **Date of preparation / last revision** 07/17/2026 / 61
· **Abbreviations and acronyms:**
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Skin Irritation 2: Skin corrosion/irritation – Category 2
Eye Damage 1: Serious eye damage/eye irritation – Category 1
Sensitization - Skin 1: Skin sensitisation – Category 1
Carcinogenicity 1A: Carcinogenicity – Category 1A
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3
· *** Data compared to the previous version altered.**

US