Safety Data Sheet
acc. to OSHA HCS

Printing date 07/13/2026 Reviewed on 07/13/2026

1 Identification

· **Product identifier**

· **Trade name:** GRF PM FIX&SEAL EXP WH CQ 425G*12 L221
· **Application of the substance / the mixture** Adhesive

· **Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**
Bison International
Dr.A.F.Philipsstraat 9
NL-4462 EW Goes
PO Box 160
NL-4460 AD Goes
tel. +31 88 3235700
fax. +31 88 3235800
e mail: sds@boltonadhesives.com

· **Information department:** PSRA
· **Emergency telephone number:**
Bison and Griffon products: +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET)
UHU products: + 49 (0) 30/19240 (Notruf). Operating hours mo-fr 08:00h-17:00h (CET)

For detailed information contact the national Poison Centre @
https://poisoncentres.echa.europa.eu/appointed-bodies

*
2 Hazard(s) identification

· **Classification of the substance or mixture**


Carcinogenicity 2	H351 Suspected of causing cancer.
Toxic to Reproduction 2	H361 Suspected of damaging fertility or the unborn child.

· **Label elements**
· **Hazard pictograms**



GHS08

· **Signal word** Warning
· **Hazard statements**
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
· **Precautionary statements**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P308+P313 IF exposed or concerned: Get medical advice/attention.
· **Classification system:**
· **NFPA ratings (scale 0 - 4)**



Health = 0
Fire = 0
Reactivity = 0

(Contd. on page 2)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/13/2026 Reviewed on 07/13/2026

Trade name: GRF PM FIX&SEAL EXP WH CQ 425G*12 L221

(Contd. of page 1)

· **HMIS-ratings (scale 0 - 4)**



Health = *1
Fire = 0
Reactivity = 0

· **Other hazards** During curing methanol (CAS 67-56-1) is produced.
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**
· **Description:** Adhesive

· **Dangerous components:**		
2768-02-7	trimethoxyvinylsilane	2.5-10%
13822-56-5	3-(trimethoxysilyl)propylamine	1-2.5%
13463-67-7	Titanium dioxide	≥0.1-<1%
52829-07-9	bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	≥0.1-<1%

4 First-aid measures

· **Description of first aid measures**
· **General information:** No special measures required.
· **After inhalation:**
Supply fresh air; consult doctor in case of complaints.
No special measures required.
· **After skin contact:** Generally the product does not irritate the skin.
· **After eye contact:** Rinse opened eye for several minutes under running water.
· **After swallowing:** If symptoms persist consult doctor.
· **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**
· **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
· **Special hazards arising from the substance or mixture**
No further relevant information available.

(Contd. on page 3)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/13/2026 Reviewed on 07/13/2026

Trade name: GRF PM FIX&SEAL EXP WH CQ 425G*12 L221

(Contd. of page 2)

· **Advice for firefighters**
· **Protective equipment:** No special measures required.

*
6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures** Not required
· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
· **Methods and material for containment and cleaning up:**
Send for recovery or disposal in suitable receptacles.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
· **Reference to other sections**
No dangerous substances are released.
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
· **Protective Action Criteria for Chemicals**

· **PAC-1:**		
471-34-1	calcium carbonate	45 mg/m3
2768-02-7	trimethoxyvinylsilane	10 ppm
13822-56-5	3-(trimethoxysilyl)propylamine	9.0 mg/m3
13463-67-7	Titanium dioxide	15 mg/m3
1185-55-3	Trimethoxy(methyl)silane	35 mg/m3
67-56-1	Methanol	530 ppm

· **PAC-2:**		
471-34-1	calcium carbonate	210 mg/m3
2768-02-7	trimethoxyvinylsilane	20 ppm
13822-56-5	3-(trimethoxysilyl)propylamine	99 mg/m3
13463-67-7	Titanium dioxide	170 mg/m3
1185-55-3	Trimethoxy(methyl)silane	390 mg/m3
67-56-1	Methanol	2100 ppm

· **PAC-3:**		
471-34-1	calcium carbonate	1300 mg/m3
2768-02-7	trimethoxyvinylsilane	120 ppm
13822-56-5	3-(trimethoxysilyl)propylamine	600 mg/m3
13463-67-7	Titanium dioxide	990 mg/m3
1185-55-3	Trimethoxy(methyl)silane	2300 mg/m3
67-56-1	Methanol	7200 ppm

7 Handling and storage

· **Handling:**
· **Precautions for safe handling** Open and handle receptacle with care.

(Contd. on page 4)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/13/2026 Reviewed on 07/13/2026

Trade name: GRF PM FIX&SEAL EXP WH CQ 425G*12 L221

(Contd. of page 3)

· **Information about protection against explosions and fires:**
Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**
· **Storage:**
· **Requirements to be met by storerooms and receptacles:** No special requirements.
· **Information about storage in one common storage facility:** Not required
· **Further information about storage conditions:** Keep receptacle tightly sealed.
· **Storage class:** 12
· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see section 7.

· **Control parameters**
· **Components with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**
· **Personal protective equipment:**
· **General protective and hygienic measures:**
The usual precautionary measures for handling chemicals should be followed.
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
· **Breathing equipment:** Not necessary if room is well-ventilated.
· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
· **Material of gloves**
Recommended thickness of the material: > 0,12 mm
Nitrile rubber, NBR
· **Penetration time of glove material**
For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).
· **Eye protection:** Goggles recommended during refilling.

US

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/13/2026 Reviewed on 07/13/2026

Trade name: GRF PM FIX&SEAL EXP WH CQ 425G*12 L221

(Contd. of page 4)

9 Physical and chemical properties

· **Information on basic physical and chemical properties**	
· **General Information**	
· **Appearance:**	
Form:	Pasty
Color:	White
· **Odor:**	Recognizable
· **Odor threshold:**	Not determined
· **pH-value:**	Not determined
· **Change in condition**	
Melting point/Melting range:	Undetermined
Boiling point/Boiling range:	Undetermined
· **Flash point:**	Not applicable
· **Flammability:**	Not applicable
· **Decomposition temperature:**	Not determined
· **Ignition temperature:**	Product is not selfigniting.
· **Danger of explosion:**	Product does not present an explosion hazard.
· **Explosion limits:**	
Lower:	Not determined
Upper:	Not determined
· **Vapor pressure:**	Not determined
· **Density:**	Not determined
· **Relative density**	Not determined
· **Vapor density**	Not determined
· **Evaporation rate**	Not determined
· **Solubility in / Miscibility with**	
Water:	Not miscible or difficult to mix.
· **Partition coefficient (n-octanol/water):**	Not determined
· **Viscosity:**	
Dynamic:	Not determined
Kinematic:	Not determined
· **Solvent content:**	
Organic solvents:	0.0 %
VOC content:	0.01 % 0.1 g/l / 0.00 lb/gal
Solids content:	75.8 %

(Contd. on page 6)

US

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/13/2026 Reviewed on 07/13/2026

Trade name: GRF PM FIX&SEAL EXP WH CQ 425G*12 L221

(Contd. of page 5)

· **Other information** All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.

10 Stability and reactivity

· **Reactivity** No further relevant information available.
· **Chemical stability**
· **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
· **Possibility of hazardous reactions** No dangerous reactions known.
· **Conditions to avoid** No further relevant information available.
· **Incompatible materials:** No further relevant information available.
· **Hazardous decomposition products:** Possible in traces.
· **Additional information:** During curing methanol (CAS 67-56-1) is produced.

11 Toxicological information

· **Information on toxicological effects**
· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**		
2768-02-7 trimethoxyvinylsilane		
Oral	LD50	6899 mg/kg (rat)
Dermal	LD50	3158 mg/kg (rabbit)
Inhalative	LC50/4 h	16.8 mg/l (rat)
13822-56-5 3-(trimethoxysilyl)propylamine		
Oral	LD50	3030 mg/kg (rat)
Dermal	LD50	10000 mg/kg (rabbit)
13463-67-7 Titanium dioxide		
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
52829-07-9 bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate		
Oral	LD50	3700 mg/kg (rat)
Dermal	LD50	>3170 mg/kg (rat)
Inhalative	LC50/4 h	7.7 mg/l (rat)

· **Primary irritant effect:**
· **on the skin:**

Component	CAS No.	Method	Species	Conclusion
Vinyltrimethoxysilane	2768-02-7	OECD No. 429	mouse, dermal	no sensitisation

· **on the eye:**

Component	CAS No.	Method	Species	Conclusion
3-Aminopropyl trimethoxysilane	13822-56-5	BCOP OECD 437	cattle, eye	no ocular irritation

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/13/2026 Reviewed on 07/13/2026

Trade name: GRF PM FIX&SEAL EXP WH CQ 425G*12 L221

(Contd. of page 6)

· **Sensitization:** No sensitizing effects known.
· **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**		
13463-67-7	Titanium dioxide	2B

· **NTP (National Toxicology Program)**
None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**
None of the ingredients is listed.

· **Germ cell mutagenicity** Not applicable

12 Ecological information

· **Toxicity**
· **Aquatic toxicity:** No further relevant information available.
· **Persistence and degradability** No further relevant information available.
· **Behavior in environmental systems:**
· **Bioaccumulative potential** No further relevant information available.
· **Mobility in soil** No further relevant information available.
· **Additional ecological information:**
· **General notes:**
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable
· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**
· **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
Disposal must be made according to official regulations.

· **Uncleaned packagings:**
· **Recommendation:**
Packagings that cannot be cleansed are to be disposed of in the same manner as the product.

US

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/13/2026 Reviewed on 07/13/2026

Trade name: GRF PM FIX&SEAL EXP WH CQ 425G*12 L221

(Contd. of page 7)

14 Transport information

· **UN-Number**	
· **DOT, ADN**	not regulated
· **ADR/ADN, IMDG, IATA**	not regulated
	-
· **UN proper shipping name**	
· **DOT, ADR/ADN, ADN, IMDG, IATA**	not regulated
· **Transport hazard class(es)**	
· **DOT, ADR/ADN, ADN, IMDG, IATA**	
· **Class**	not regulated
· **Packing group**	
· **DOT, ADR/ADN, IMDG, IATA**	not regulated
· **Environmental hazards:**	
· **Marine pollutant:**	No
· **Special precautions for user**	Not applicable
· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**	Not applicable
· **Transport/Additional information:**	Not dangerous according to the above specifications.
· **UN "Model Regulation":**	not regulated

*

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

67-56-1	Methanol

· **TSCA (Toxic Substances Control Act):**

471-34-1	calcium carbonate	ACTIVE
611222-18-5	Dimethoxy(methyl)silylmethylcarbamate-terminated polyether	ACTIVE
2768-02-7	trimethoxyvinylsilane	ACTIVE
13822-56-5	3-(trimethoxysilyl)propylamine	ACTIVE
13463-67-7	Titanium dioxide	ACTIVE
68441-17-8	Oxydised polyethylene wax	ACTIVE
52829-07-9	bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	ACTIVE
23949-66-8	N-(2-ethoxyphenyl)-N'-(2-ethylphenyl)oxamide	ACTIVE

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/13/2026 Reviewed on 07/13/2026

Trade name: GRF PM FIX&SEAL EXP WH CQ 425G*12 L221

(Contd. of page 8)

77-99-6	propylidynetrimethanol	ACTIVE
1185-55-3	Trimethoxy(methyl)silane	ACTIVE
68611-44-9	Silane, dichlorodimethyl-, reaction products with silica	ACTIVE
67-56-1	Methanol	ACTIVE

· **Hazardous Air Pollutants**

67-56-1	Methanol

· **Proposition 65**

· **Chemicals known to cause cancer:**

13463-67-7	Titanium dioxide

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

67-56-1	Methanol

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value)**

13463-67-7	Titanium dioxide	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	Titanium dioxide

· **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
· **Hazard pictograms**



GHS08

· **Signal word** Warning
· **Hazard statements**
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
· **Precautionary statements**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P308+P313 IF exposed or concerned: Get medical advice/attention.
· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

US

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/13/2026 Reviewed on 07/13/2026

Trade name: GRF PM FIX&SEAL EXP WH CQ 425G*12 L221

(Contd. of page 9)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** PSRA
· **Contact:** PSRA
· **Date of preparation / last revision** 07/13/2026 / 40
· **Abbreviations and acronyms:**
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Carcinogenicity 2: Carcinogenicity – Category 2
Toxic to Reproduction 2: Reproductive toxicity – Category 2
· *** Data compared to the previous version altered.**

US