# Safety Data Sheet
## according to WHS Regulations

Date of issue: 07.08.2026 Version number 40 Revision: 17.07.2026

Hazardous according to criteria of Australian Safety and Compensation Council.

## 1 Identification

· **Other means of identification**

· **Trade name:** GRF SEALANT REMOVER BO 250ML*6 L221
· **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
· **Application of the substance / the mixture** Cleaning agent/ Cleaner

· **Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**
Bison International B.V.
Dr.A.F.Philipsstraat 9
NL-4462 EW Goes
PO Box 160
NL-4460 AD Goes
tel. +31 88 3235700
fax. +31 88 3235800
e-mail: sds@boltonadhesives.com

FABER - CASTELL
15 GIBBON RD.
WINSTON HILL
NSW 2153
Toll Free: 1800 677 885
Free Fax: 1800 678 608
EMAIL: enquiries@faber-castell.com.au

· **Further information obtainable from:** PSRA
· **Emergency telephone number:**
POISONS INFORMATION CENTRE (PIC)
TEL: 13 11 26

* 
## 2 Hazard(s) Identification

· **Classification of the substance or mixture**

| | |
|---|---|
| Flammable liquids – Category 3 | H226 Flammable liquid and vapour. |
| Acute toxicity - oral – Category 4 | H302 Harmful if swallowed. |
| Skin corrosion/irritation – Category 1C | H314 Causes severe skin burns and eye damage. |
| Eye damage/irritation – Category 1 | H318 Causes serious eye damage. |

· **Label elements**
· **Hazard pictograms**



GHS02 GHS05 GHS07

· **Signal word** Danger

(Contd. on page 2)

# Safety Data Sheet
## according to WHS Regulations

Date of issue: 07.08.2026 Version number 40 Revision: 17.07.2026

**Trade name:** GRF SEALANT REMOVER BO 250ML*6 L221

(Contd. of page 1)

· **Hazard-determining components of labelling:**
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives (10-<30 %)
Quaternary ammonium compounds, benzyl-C16-18 (even numbered)-alkyldimethyl, chlorides (<1 %)
· **Hazard statements**
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
· **Precautionary statements**

| | |
|---|---|
| P101 | If medical advice is needed, have product container or label at hand. |
| P102 | Keep out of reach of children. |
| P210 | Keep away from heat/sparks/open flames/hot surfaces. No smoking. |
| P260 | Do not breathe dust. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P301+P312 | IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. |
| P301+P330+P331 | IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. |
| P303+P361+P353 | IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. |
| P304+P340 | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. |
| P310 | Immediately call a POISON CENTER/doctor. |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P321 | Specific treatment (see on this label). |
| P501 | Dispose of contents/container in accordance with national regulations. |

· **Other hazards**
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable

* 
## 3 Composition and Information on Ingredients

· **Chemical characterisation: Mixtures**
· **Description:** Cleansing agent

· **Dangerous components:**

| | | |
|---|---|---|
| | Hydrocarbons, C11-C12, isoalkanes, <2% aromatics<br>Flammable liquids – Category 3, H226; Aspiration hazard – Category 1, H304 | >60% |
| 85536-14-7 | Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives<br>Skin corrosion/irritation – Category 1C, H314; Eye damage/irritation – Category 1, H318; Acute toxicity - oral – Category 4, H302 | 10-<30% |
| 67-63-0 | propan-2-ol<br>Flammable liquids – Category 2, H225; Eye damage/irritation – Category 2A, H319; Specific target organ toxicity (single exposure) – Category 3, H336 | <10% |
| | Quaternary ammonium compounds, benzyl-C16-18 (even numbered)-alkyldimethyl, chlorides<br>Acute toxicity - oral – Category 3, H301; Skin corrosion/irritation – Category 1B, H314; Eye damage/irritation – Category 1, H318 | <1% |

(Contd. on page 3)

# Safety Data Sheet
## according to WHS Regulations

Date of issue: 07.08.2026 Version number 40 Revision: 17.07.2026

**Trade name:** GRF SEALANT REMOVER BO 250ML*6 L221

(Contd. of page 2)

| | | |
|---|---|---|
| 78-93-3 | Butanone<br>Flammable liquids – Category 2, H225; Eye damage/irritation – Category 2A, H319; Specific target organ toxicity (single exposure) – Category 3, H335; Specific target organ toxicity (single exposure) – Category 3, H336 | <10% |

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

* 
## 4 First Aid Measures

· **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
· **After inhalation:** Call a doctor immediately.
· **After skin contact:** Immediately rinse with water.
· **After eye contact:**
Rinse opened eye for several minutes under running water. Then consult a doctor.
· **After swallowing:**
Rinse out mouth and then drink plenty of water.
Call for a doctor immediately.
· **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

## 5 Fire Fighting Measures

· **Suitable extinguishing agents:**
Water haze
Alcohol resistant foam
Fire-extinguishing powder
Carbon dioxide
· **For safety reasons unsuitable extinguishing agents:** Water with full jet
· **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
· **Protective equipment:** Mouth respiratory protective device.
· **Additional information**
Cool endangered receptacles with water spray.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

## 6 Accidental Release Measures

· **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

# Safety Data Sheet
## according to WHS Regulations

Date of issue: 07.08.2026 Version number 40 Revision: 17.07.2026

**Trade name:** GRF SEALANT REMOVER BO 250ML*6 L221

(Contd. of page 3)

· **Methods and material for containment and cleaning up:**
Send for recovery or disposal in suitable receptacles.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralising agent.
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
· **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

## 7 Handling and Storage

· **Handling:**
· **Precautions for safe handling**
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
· **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
· **Storage:**
· **Requirements to be met by storerooms and receptacles:** No special requirements.
· **Information about storage in one common storage facility:** Not required
· **Further information about storage conditions:** Keep container tightly sealed.
· **Storage class:** 3
· **Specific end use(s)** No further relevant information available.

## 8 Exposure controls and personal protection

· **Appropriate engineering controls** No further data; see section 7.

| · **Ingredients with limit values that require monitoring at the workplace:** | |
|---|---|
| **67-63-0 propan-2-ol** | |
| WES | Short-term value: 1230 mg/m³, 500 ppm<br>Long-term value: 983 mg/m³, 400 ppm |
| **78-93-3 Butanone** | |
| WES | Short-term value: 890 mg/m³, 300 ppm<br>Long-term value: 445 mg/m³, 150 ppm |

| · **DNELs** | | |
|---|---|---|
| **85536-14-7 Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives** | | |
| Oral | Consumer, oral, longterm exposition | 0.425 mg/kg bw/day |
| Dermal | Worker, dermal, longterm exposition | 85 mg/kg bw/day |
| | Consumer, dermal, longterm exposition | 42.5 mg/kg bw/day |
| Inhalative | Worker, inhalative, longterm exposition | 6 mg/m³ |

(Contd. on page 5)

# Safety Data Sheet
## according to WHS Regulations

Date of issue: 07.08.2026 Version number 40 Revision: 17.07.2026

**Trade name:** GRF SEALANT REMOVER BO 250ML*6 L221

(Contd. of page 4)

| | | |
|---|---|---|
| | Consumer, inhalative, longterm exposition | 1.5 mg/m³ |
| **67-63-0 propan-2-ol** | | |
| Oral | Consumer, oral, longterm exposition | 26 mg/kg bw/day |
| Dermal | Worker, dermal, longterm exposition | 888 mg/kg bw/day |
| | Consumer, dermal, longterm exposition | 319 mg/kg bw/day |
| Inhalative | Worker, inhalative, longterm exposition | 500 mg/m³ |
| | Consumer, inhalative, longterm exposition | 89 mg/m³ |
| **78-93-3 Butanone** | | |
| Oral | Consumer, oral, longterm exposition | 31 mg/kg bw/day |
| Dermal | Worker, dermal, longterm exposition | 1161 mg/kg bw/day |
| | Consumer, dermal, longterm exposition | 412 mg/kg bw/day |
| Inhalative | Worker, inhalative, shortterm exposition | 900 mg/m³ |
| | Worker, inhalative, longterm exposition | 600 mg/m³ |
| | Consumer DNEL, acute inhalation | 450 mg/m³ |
| | Consumer, inhalative, longterm exposition | 106 mg/m³ |

· **PNECs**

| | | |
|---|---|---|
| **85536-14-7 Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives** | | |
| | Fresh water | 0.268 mg/l |
| | Fresh water sediment | 8.1 mg/kg dry weight |
| | Marine water | 0.027 mg/l |
| | Marine sediment | 6.8 mg/kg dry weight |
| | Soil | 35 mg/kg |
| | Sewage treatment plant | 3.43 mg/l |
| | Sporadic release | 0.017 mg/l |
| **67-63-0 propan-2-ol** | | |
| Oral | Secondary Poisoning | 160 mg/kg |
| | Fresh water | 140.9 mg/l |
| | Fresh water sediment | 552 mg/kg dry weight |
| | Marine water | 140.9 mg/l |
| | Marine sediment | 552 mg/kg dry weight |
| | Soil | 28 mg/kg |
| | Sewage treatment plant | 2251 mg/l |
| | Sporadic release | 140.9 mg/l |
| **78-93-3 Butanone** | | |
| Oral | Secondary Poisoning | 1000 mg/kg |
| | Fresh water | 55.8 mg/l |
| | Fresh water sediment | 284.7 mg/kg dry weight |
| | Marine water | 55.8 mg/l |
| | Marine sediment | 284.7 mg/kg dry weight |
| | Soil | 22.5 mg/kg |

(Contd. on page 6)

# Safety Data Sheet
## according to WHS Regulations

Date of issue: 07.08.2026 Version number 40 Revision: 17.07.2026

**Trade name:** GRF SEALANT REMOVER BO 250ML*6 L221

(Contd. of page 5)

| | | |
|---|---|---|
| | Sewage treatment plant | 709 mg/l |
| | Sporadic release | 55.8 mg/l |

· **Additional information:** The lists valid during the making were used as basis.
· **Personal protective equipment:**
· **General protective and hygienic measures:**
The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.
· **Respiratory protection:**
Use suitable respiratory protective device in case of insufficient ventilation.
· **Recommended filter device for short term use:** Filter A
· **Protection of hands:**
Solvent resistant gloves


Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
· **Material of gloves**
Recommended thickness of the material: > 0,12 mm
Nitrile rubber, NBR
· **Penetration time of glove material**
For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).
· **Eye protection:**


Tightly sealed goggles

Goggles recommended during refilling
· **Body protection:** Solvent resistant protective clothing

## 9 Physical and Chemical Properties

| | |
|---|---|
| · **General Information** | |
| · **Appearance:** | |
| · **Form:** | Fluid |
| · **Colour:** | Brown |
| · **Odour:** | Characteristic |
| · **Odour threshold:** | Not determined |
| · **pH-value:** | Not determined |

(Contd. on page 7)

# Safety Data Sheet
## according to WHS Regulations

Date of issue: 07.08.2026 Version number 40 Revision: 17.07.2026

**Trade name:** GRF SEALANT REMOVER BO 250ML*6 L221

(Contd. of page 6)

| | |
|---|---|
| · **Change in condition** | |
| · **Melting point/freezing point:** | -25 °C |
| · **Initial boiling point and boiling range:** | 36 °C |
| · **Flash point:** | ≤60 °C |
| · **Flammability** | Flammable. |
| · **Auto-ignition temperature:** | ~310 °C |
| · **Decomposition temperature:** | Not determined |
| · **Ignition temperature:** | Product is not selfigniting. |
| · **Explosive properties:** | Not determined |
| · **Explosion limits:** | |
| · **Lower:** | 0.7 Vol % |
| · **Upper:** | 6.5 Vol % |
| · **Vapour pressure:** | Not determined |
| · **Density at 20 °C:** | ~0.81 g/cm³ |
| · **Relative density** | Not determined |
| · **Vapour density** | Not determined |
| · **Evaporation rate** | Not determined |
| · **Solubility in / Miscibility with** | |
| · **water at 20 °C:** | 0.04 g/l |
| · **Partition coefficient: n-octanol/water:** | Not determined |
| · **Viscosity:** | |
| · **Dynamic at 20 °C:** | 140000 mPas |
| · **Kinematic:** | Not determined |
| · **Solvent content:** | |
| · **Organic solvents:** | 0.9 % |
| · **VOC (EC)** | 80.61 % |
| · **Solids content:** | 5.7 % |
| · **Other information** | All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture. |
| · **Particle characteristics** | Not applicable |
| · **Physical state** | Liquid |

## 10 Stability and Reactivity

· **Reactivity** No further relevant information available.
· **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
· **Possibility of hazardous reactions** Corrosive action on metals.
· **Conditions to avoid** No further relevant information available.
· **Incompatible materials:** No further relevant information available.
· **Hazardous decomposition products:** Danger of forming toxic pyrolysis products.

AU

(Contd. on page 8)

# Safety Data Sheet
## according to WHS Regulations

Date of issue: 07.08.2026 Version number 40 Revision: 17.07.2026

**Trade name:** GRF SEALANT REMOVER BO 250ML*6 L221

(Contd. of page 7)

## 11 Toxicological Information

· **Information on toxicological effects**
· **Acute toxicity** Harmful if swallowed.

| · **LD/LC50 values relevant for classification:** | | |
|---|---|---|
| **Hydrocarbons, C11-C12, isoalkanes, <2% aromatics** | | |
| Oral | LD50 | >5000 mg/kg (rat) |
| Dermal | LD50 | >5000 mg/kg (rat) |
| Inhalative | LC50/4 h | >5000 mg/l (rat) |
| **85536-14-7 Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives** | | |
| Oral | LD50 | >300-2000 mg/kg (rat) |
| Dermal | LD50 | >2000 mg/kg (rat) |
| **67-63-0 propan-2-ol** | | |
| Oral | LD50 | 5045 mg/kg (rat) |
| Dermal | LD50 | 12800 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 30 mg/l (rat) |
| **78-93-3 Butanone** | | |
| Oral | LD50 | >2193 mg/kg (rat) |
| Dermal | LD50 | >8050 mg/kg (rat) |

· **Primary irritant effect:**
· **Skin corrosion/irritation**
Causes severe skin burns and eye damage.
· **Serious eye damage/irritation**
Causes serious eye damage.
· **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
· **Germ cell mutagenicity**
Not applicable
Based on available data, the classification criteria are not met.
· **Carcinogenicity** Based on available data, the classification criteria are not met.
· **Reproductive toxicity** Based on available data, the classification criteria are not met.
· **STOT-single exposure** Based on available data, the classification criteria are not met.
· **STOT-repeated exposure** Based on available data, the classification criteria are not met.
· **Aspiration hazard** Based on available data, the classification criteria are not met.
· **Interactive effects**
· **Acute effects (acute toxicity, irritation and corrosivity)** Not applicable
· **Sensitisation** Not applicable
· **Repeated dose toxicity** Not applicable

## 12 Ecological Information

· **Toxicity**
· **Aquatic toxicity:** No further relevant information available.
· **Persistence and degradability** No further relevant information available.
· **Behaviour in environmental systems:**
· **Bioaccumulative potential** No further relevant information available.

(Contd. on page 9)

# Safety Data Sheet
## according to WHS Regulations

Date of issue: 07.08.2026 Version number 40 Revision: 17.07.2026

**Trade name:** GRF SEALANT REMOVER BO 250ML*6 L221

(Contd. of page 8)

· **Mobility in soil** No further relevant information available.
· **Additional ecological information:**
· **General notes:**
Do not allow product to reach ground water, water course or sewage system.
Must not reach sewage water or drainage ditch undiluted or unneutralised.
Danger to drinking water if even small quantities leak into the ground.
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable
· **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

· **Waste treatment methods**
· **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Disposal must be made according to official regulations.

· **Uncleaned packaging:**
· **Recommendation:**
Packagings that may not be cleansed are to be disposed of in the same manner as the product.

## 14 Transport information

| | |
|---|---|
| · **UN-Number** | |
| · **ADG, IMDG, IATA** | UN2924 |
| · **UN proper shipping name** | |
| · **ADG** | 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ISOPROPANOL (ISOPROPYL ALCOHOL)) |
| · **IMDG, IATA** | FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives, ISOPROPANOL (ISOPROPYL ALCOHOL)) |
| · **Transport hazard class(es)** | |
| · **ADG** |  |
| · **Class** | 3 (FC) Flammable liquids. |

(Contd. on page 10)

# Safety Data Sheet
## according to WHS Regulations

Date of issue: 07.08.2026 Version number 40 Revision: 17.07.2026

**Trade name:** GRF SEALANT REMOVER BO 250ML*6 L221

(Contd. of page 9)

| | |
|---|---|
| · **Label** | 3+8 |
| · **IMDG** | |
|  | |
| · **Class** | 3 Flammable liquids. |
| · **Label** | 3/8 |
| · **IATA** | |
|  | |
| · **Class** | 3 Flammable liquids. |
| · **Label** | 3 (8) |
| · **Packing group** | |
| · **ADG, IMDG, IATA** | III |
| · **Environmental hazards:** | |
| · **Marine pollutant:** | No |
| · **Special precautions for user** | Warning: Flammable liquids. |
| · **Hazard identification number (Kemler code):** | 38 |
| · **EMS Number:** | F-E,S-C |
| · **Segregation groups** | (SGG1) Acids |
| · **Stowage Category** | A |
| · **Stowage Code** | SW2 Clear of living quarters. |
| · **Transport in bulk according to Annex II of Marpol and the IBC Code** | Not applicable |
| · **Transport/Additional information:** | |
| · **Quantity limitations** | On passenger aircraft/rail: 5 L<br>On cargo aircraft only: 60 L |
| · **ADG** | |
| · **Limited quantities (LQ)** | 5L |
| · **Excepted quantities (EQ)** | Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml |
| · **Transport category** | 3 |
| · **Tunnel restriction code** | D/E |
| · **IMDG** | |
| · **Limited quantities (LQ)** | 5L |

(Contd. on page 11)

# Safety Data Sheet
## according to WHS Regulations

Date of issue: 07.08.2026 Version number 40 Revision: 17.07.2026

**Trade name:** GRF SEALANT REMOVER BO 250ML*6 L221

(Contd. of page 10)

| | |
|---|---|
| · **Excepted quantities (EQ)** | Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml |
| · **Remarks:** | For substances with class 3 according to IMDG-Code chapter 2.3.2.2 packing group is classified in packing group III, as viscosity is in accordance with requirements (flow time t > 100s). |
| · **UN "Model Regulation":** | UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ISOPROPANOL (ISOPROPYL ALCOHOL)), 3 (8), III |

* 
## 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

| · **Australian Inventory of Industrial Chemicals** | |
|---|---|
| 85536-14-7 | Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives |
| 63800-37-3 | Sepiolite |
| 112945-52-5 | fumed silica |
| 67-63-0 | propan-2-ol |
| 78-93-3 | Butanone |
| 7664-93-9 | sulphuric acid |
| 14808-60-7 | Quartz (SiO2) |
| 9003-39-8 | Polyvinylpyrrolidon |
| 616-45-5 | 2-pyrrolidone |

| · **Standard for the Uniform Scheduling of Medicines and Poisons** | | |
|---|---|---|
| 78-93-3 | Butanone | S5 |
| 7664-93-9 | sulphuric acid | S6 |

| · **Australia: Priority Existing Chemicals** |
|---|
| None of the ingredients is listed. |

· **GHS label elements**
The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms**



GHS02 GHS05 GHS07

· **Signal word** Danger

· **Hazard-determining components of labelling:**
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives (10-<30 %)

(Contd. on page 12)

# Safety Data Sheet
## according to WHS Regulations

Date of issue: 07.08.2026 Version number 40 Revision: 17.07.2026

**Trade name:** GRF SEALANT REMOVER BO 250ML*6 L221

(Contd. of page 11)

Quaternary ammonium compounds, benzyl-C16-18 (even numbered)-alkyldimethyl, chlorides (<1 %)

· **Hazard statements**
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.

· **Precautionary statements**

| | |
|---|---|
| P101 | If medical advice is needed, have product container or label at hand. |
| P102 | Keep out of reach of children. |
| P210 | Keep away from heat/sparks/open flames/hot surfaces. No smoking. |
| P260 | Do not breathe dust. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P301+P312 | IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. |
| P301+P330+P331 | IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. |
| P303+P361+P353 | IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. |
| P304+P340 | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. |
| P310 | Immediately call a POISON CENTER/doctor. |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P321 | Specific treatment (see on this label). |
| P501 | Dispose of contents/container in accordance with national regulations. |

· **Directive 2012/18/EU**
· **Named dangerous substances - ANNEX I** None of the ingredients is listed.
· **Seveso category** P5c FLAMMABLE LIQUIDS
· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5000 t
· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50000 t
· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H314 Causes severe skin burns and eye damage.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

· **Department issuing SDS:** PSRA
· **Contact:** PSRA

(Contd. on page 13)

# Safety Data Sheet
## according to WHS Regulations

Date of issue: 07.08.2026 Version number 40 Revision: 17.07.2026

**Trade name:** GRF SEALANT REMOVER BO 250ML*6 L221

(Contd. of page 12)

· **Abbreviations and acronyms:**
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flammable liquids – Category 2: Flammable liquids – Category 2
Flammable liquids – Category 3: Flammable liquids – Category 3
Acute toxicity - oral – Category 3: Acute toxicity – Category 3
Acute toxicity - oral – Category 4: Acute toxicity – Category 4
Skin corrosion/irritation – Category 1B: Skin corrosion/irritation – Category 1B
Skin corrosion/irritation – Category 1C: Skin corrosion/irritation – Category 1C
Eye damage/irritation – Category 1: Serious eye damage/eye irritation – Category 1
Eye damage/irritation – Category 2A: Serious eye damage/eye irritation – Category 2A
Specific target organ toxicity (single exposure) – Category 3: Specific target organ toxicity (single exposure) – Category 3
Aspiration hazard – Category 1: Aspiration hazard – Category 1

· *** Data compared to the previous version altered.**

AU