# Safety data sheet

**according to Regulation (EC) No 1907/2006, Article 31**

Printing date 18.07.2026 Version number 16 (replaces version 15) Revision: 18.07.2026

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name:** GRF EPOXY REPAIR STICK DP 114G*12 L729

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.

· **Application of the substance / the mixture** Adhesive

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**
UHU GmbH
Herrmannstraße 7
D-77815 Bühl (Baden)
Tel.:0049-(0)7223-284-0 Fax: 0049-(0)7223-284-245
E-mail: sds@boltonadhesives.com

· **Further information obtainable from:** PSRA

· **1.4 Emergency telephone number:**
Emergency medical information: 8am-10pm (seven days) contact
National Poisons Information Centre, Beaumont Hospital, Dublin 9. Tel 01 8092566

## SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**

| | |
|---|---|
| Skin Irrit. 2 | H315 Causes skin irritation. |
| Eye Irrit. 2 | H319 Causes serious eye irritation. |
| Skin Sens. 1 | H317 May cause an allergic skin reaction. |
| Aquatic Chronic 3 | H412 Harmful to aquatic life with long lasting effects. |

· **2.2 Label elements**

· **Classification needs to be in accordance with the NZ Hazardous Substances (Hazard Classification) Notice 2020**
The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS07

· **Signal word** Warning

· **Hazard-determining components of labelling:**
mercaptan polymer
bis-[4-(2,3-epoxipropoxi)phenyl]propane

· **Hazard statements**
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

# Safety data sheet
## according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.07.2026 Version number 16 (replaces version 15) Revision: 18.07.2026

**Trade name:** GRF EPOXY REPAIR STICK DP 114G*12 L729

(Contd. of page 1)

· **Precautionary statements**

| | |
|---|---|
| P101 | If medical advice is needed, have product container or label at hand. |
| P102 | Keep out of reach of children. |
| P280 | Wear protective gloves. |
| P302+P352 | IF ON SKIN: Wash with plenty of water. |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P501 | Dispose of contents/container in accordance with national regulations. |

· **Additional information:**
EUH205 Contains epoxy constituents. May produce an allergic reaction.
· **2.3 Other hazards**
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable

## SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**
· **Description:** Adhesive

· **Dangerous components:**

| | | |
|---|---|---|
| CAS: 72244-98-5<br>EC number: 615-735-8<br>Reg.nr.: 01-2120118957-46-XXXX | mercaptan polymer<br>Skin Sens. 1, H317; Aquatic Chronic 3, H412 | ≥10-<25% |
| CAS: 1675-54-3<br>EINECS: 216-823-5<br>Index number: 603-073-00-2<br>Reg.nr.: 01-2119456619-26-XXXX | bis-[4-(2,3-epoxipropoxi)phenyl]propane<br>Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205<br>Specific concentration limits:<br>Skin Irrit. 2; H315: C ≥5 %<br>Eye Irrit. 2; H319: C ≥ 5 % | ≥10-<25% |
| CAS: 90-72-2<br>EINECS: 202-013-9<br>Index number: 603-069-00-0<br>Reg.nr.: 01-2119560597-27 | 2,4,6-tris(dimethylaminomethyl)phenol<br>Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319 | 1-2.5% |

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

· **4.1 Description of first aid measures**
· **General information:** No special measures required.
· **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
· **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
· **After swallowing:** If symptoms persist consult doctor.

(Contd. on page 3)

# Safety data sheet
## according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.07.2026 Version number 16 (replaces version 15) Revision: 18.07.2026

**Trade name:** GRF EPOXY REPAIR STICK DP 114G*12 L729

(Contd. of page 2)

· **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
· **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

## SECTION 5: Firefighting measures

· **5.1 Extinguishing media**
· **Suitable extinguishing agents:**
Use fire extinguishing methods suitable to surrounding conditions.
· **5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
· **5.3 Advice for firefighters**
· **Protective equipment:** No special measures required.

## SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures** Not required
· **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
· **6.3 Methods and material for containment and cleaning up:**
Send for recovery or disposal in suitable receptacles.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
· **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

## SECTION 7: Handling and storage

· **7.1 Precautions for safe handling** No special precautions are necessary if used correctly.
· **Information about fire - and explosion protection:** No special measures required.

· **7.2 Conditions for safe storage, including any incompatibilities**
· **Storage:**
· **Requirements to be met by storerooms and receptacles:** No special requirements.
· **Information about storage in one common storage facility:** Not required
· **Further information about storage conditions:** Keep container tightly sealed.
· **Storage class:** 10
· **7.3 Specific end use(s)** No further relevant information available.



(Contd. on page 4)

# Safety data sheet
## according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.07.2026 Version number 16 (replaces version 15) Revision: 18.07.2026

**Trade name:** GRF EPOXY REPAIR STICK DP 114G*12 L729

(Contd. of page 3)

## SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**
· **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

| · **DNELs** | | |
|---|---|---|
| **1675-54-3 bis-[4-(2,3-epoxipropoxi)phenyl]propane** | | |
| Oral | Consumer, oral, longterm exposition | 0.5 mg/kg bw/day (rat) |
| Dermal | Worker, dermal, shortterm exposition | 8.3 mg/kg bw/day |
| | Worker, dermal, longterm exposition | 0.75 mg/kg bw/day (rat) |
| | Consumer, dermal, longterm exposition | 0.0893 mg/kg bw/day (rat) |
| Inhalative | Worker, inhalative, shortterm exposition | 12.3 mg/m³ |
| | Worker, inhalative, longterm exposition | 4.93 mg/m³ (rat) |
| | Consumer, inhalative, longterm exposition | 0.87 mg/m³ (rat) |
| **90-72-2 2,4,6-tris(dimethylaminomethyl)phenol** | | |
| Oral | Consumer, oral, longterm exposition | 0.075 mg/kg bw/day |
| Dermal | Worker, dermal, shortterm exposition | 0.6 mg/kg bw/day |
| | Worker, dermal, longterm exposition | 0.15 mg/kg bw/day |
| | Consumer, dermal, shortterm exposition | 0.075 mg/kg bw/day |
| | Consumer, dermal, longterm exposition | 0.075 mg/kg bw/day |
| Inhalative | Worker, inhalative, shortterm exposition | 2.1 mg/m³ |
| | Worker, inhalative, longterm exposition | 0.53 mg/m³ |
| | Consumer DNEL, acute inhalation | 0.13 mg/m³ |
| | Consumer, inhalative, longterm exposition | 0.13 mg/m³ |

| · **PNECs** | | |
|---|---|---|
| **1675-54-3 bis-[4-(2,3-epoxipropoxi)phenyl]propane** | | |
| Oral | Secondary Poisoning | 11 mg/kg (rat) |
| | Fresh water | 0.006 mg/l (rat) |
| | Fresh water sediment | 0.341 mg/kg dry weight (rat) |
| | Marine water | 0.001 mg/l (rat) |
| | Marine sediment | 0.034 mg/kg dry weight (rat) |
| | Soil | 0.065 mg/kg (rat) |
| | Sewage treatment plant | 10 mg/l (rat) |
| **90-72-2 2,4,6-tris(dimethylaminomethyl)phenol** | | |
| | Fresh water | 0.046 mg/l |
| | Fresh water sediment | 0.262 mg/kg dry weight |
| | Marine water | 0.005 mg/l |
| | Marine sediment | 0.026 mg/kg dry weight |
| | Soil | 0.025 mg/kg |
| | Sewage treatment plant | 0.2 mg/l |

(Contd. on page 5)

# Safety data sheet
## according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.07.2026 Version number 16 (replaces version 15) Revision: 18.07.2026

**Trade name:** GRF EPOXY REPAIR STICK DP 114G*12 L729

(Contd. of page 4)

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**
· **Appropriate engineering controls** No further data; see section 7.
· **Individual protection measures, such as personal protective equipment**
· **General protective and hygienic measures:**
The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
· **Respiratory protection:** Not required
· **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
· **Material of gloves**
Recommended thickness of the material: > 0,12 mm
Nitrile rubber, NBR
· **Penetration time of glove material**
For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).
· **Eye/face protection**



Tightly sealed goggles

Goggles recommended during refilling

## SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**
· **General Information**

| | |
|---|---|
| · **Physical state** | Liquid |
| · **Colour:** | According to product specification |
| · **Odour:** | Characteristic |
| · **Odour threshold:** | Not determined |
| · **Melting point/freezing point:** | Undetermined |
| · **Boiling point or initial boiling point and boiling range** | Undetermined |
| · **Flammability** | Not applicable |
| · **Lower and upper explosion limit** | |
| · **Lower:** | Not determined |

(Contd. on page 6)

# Safety data sheet
## according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.07.2026 Version number 16 (replaces version 15) Revision: 18.07.2026

**Trade name:** GRF EPOXY REPAIR STICK DP 114G*12 L729

(Contd. of page 5)

| | |
|---|---|
| · **Upper:** | Not determined |
| · **Flash point:** | >100 °C |
| · **Decomposition temperature:** | Not determined |
| · **pH** | Not determined |
| · **Viscosity:** | |
| · **Kinematic viscosity** | Not determined |
| · **Dynamic:** | Not determined |
| · **Solubility** | |
| · **water:** | Not miscible or difficult to mix. |
| · **Partition coefficient n-octanol/water (log value)** | Not determined |
| · **Vapour pressure:** | Not determined |
| · **Density and/or relative density** | |
| · **Density at 20 °C:** | 1.9 g/cm³ |
| · **Relative density** | Not determined |
| · **Vapour density** | Not determined |

| | |
|---|---|
| · **9.2 Other information** | All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture. |
| · **Appearance:** | |
| · **Form:** | Solid |
| · **Important information on protection of health and environment, and on safety.** | |
| · **Ignition temperature:** | Product is not selfigniting. |
| · **Explosive properties:** | Product does not present an explosion hazard. |
| · **Solvent content:** | |
| · **Solids content:** | 70.8 % |
| · **Change in condition** | |
| · **Evaporation rate** | Not determined |

| | |
|---|---|
| · **Information with regard to physical hazard classes** | |
| · **Explosives** | Void |
| · **Flammable gases** | Void |
| · **Aerosols** | Void |
| · **Oxidising gases** | Void |
| · **Gases under pressure** | Void |
| · **Flammable liquids** | Void |
| · **Flammable solids** | Void |
| · **Self-reactive substances and mixtures** | Void |
| · **Pyrophoric liquids** | Void |
| · **Pyrophoric solids** | Void |
| · **Self-heating substances and mixtures** | Void |
| · **Substances and mixtures, which emit flammable gases in contact with water** | Void |
| · **Oxidising liquids** | Void |
| · **Oxidising solids** | Void |

(Contd. on page 7)

# Safety data sheet
## according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.07.2026 Version number 16 (replaces version 15) Revision: 18.07.2026

**Trade name:** GRF EPOXY REPAIR STICK DP 114G*12 L729

(Contd. of page 6)

| | |
|---|---|
| · **Organic peroxides** | Void |
| · **Corrosive to metals** | Void |
| · **Desensitised explosives** | Void |

## SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.
· **10.2 Chemical stability**
· **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
· **10.3 Possibility of hazardous reactions** No dangerous reactions known.
· **10.4 Conditions to avoid** No further relevant information available.
· **10.5 Incompatible materials:** No further relevant information available.
· **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

## SECTION 11: Toxicological information

· **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
· **Acute toxicity** Based on available data, the classification criteria are not met.

| · **LD/LC50 values relevant for classification:** | | |
|---|---|---|
| **1675-54-3 bis-[4-(2,3-epoxipropoxi)phenyl]propane** | | |
| Oral | LD50 | >2000 mg/kg (rat) |
| Dermal | LD50 | >2000 mg/kg (rat) |
| **90-72-2 2,4,6-tris(dimethylaminomethyl)phenol** | | |
| Oral | LD50 | 500 mg/kg (rat) |

· **Primary irritant effect:**
· **Skin corrosion/irritation**
Causes skin irritation.
· **Serious eye damage/irritation**
Causes serious eye irritation.
· **Respiratory or skin sensitisation** May cause an allergic skin reaction.
· **Germ cell mutagenicity**
Not applicable
Based on available data, the classification criteria are not met.
· **Carcinogenicity** Based on available data, the classification criteria are not met.
· **Reproductive toxicity** Based on available data, the classification criteria are not met.
· **STOT-single exposure** Based on available data, the classification criteria are not met.
· **STOT-repeated exposure** Based on available data, the classification criteria are not met.
· **Aspiration hazard** Based on available data, the classification criteria are not met.
· **Additional toxicological information:**
· **Acute effects (acute toxicity, irritation and corrosivity)** Not applicable
· **Sensitisation** Not applicable
· **Repeated dose toxicity** Not applicable

(Contd. on page 8)

# Safety data sheet
## according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.07.2026 Version number 16 (replaces version 15) Revision: 18.07.2026

**Trade name:** GRF EPOXY REPAIR STICK DP 114G*12 L729

(Contd. of page 7)

· **11.2 Information on other hazards**

| · **Endocrine disrupting properties** |
|---|
| None of the ingredients is listed. |

* 

## SECTION 12: Ecological information

· **12.1 Toxicity**

| · **Aquatic toxicity:** | |
|---|---|
| **72244-98-5 mercaptan polymer** | |
| EC50 | 12 mg/l (crustaceans) |

· **12.2 Persistence and degradability** No further relevant information available.
· **12.3 Bioaccumulative potential** No further relevant information available.
· **12.4 Mobility in soil** No further relevant information available.
· **12.5 Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable
· **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
· **12.7 Other adverse effects**
· **Remark:** Harmful to fish
· **Additional ecological information:**
· **General notes:**
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms

## SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**
· **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Disposal must be made according to official regulations.

· **Uncleaned packaging:**
· **Recommendation:** Disposal must be made according to official regulations.

## SECTION 14: Transport information

· **14.1 UN number or ID number**

| | |
|---|---|
| · **ADR/ADN, IMDG, IATA** | not regulated |
| | - |
| · **ADN** | not regulated |

(Contd. on page 9)

# Safety data sheet
## according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.07.2026 Version number 16 (replaces version 15) Revision: 18.07.2026

**Trade name:** GRF EPOXY REPAIR STICK DP 114G*12 L729

(Contd. of page 8)

| | |
|---|---|
| · **14.2 UN proper shipping name**<br>· **ADR/ADN, ADN, IMDG, IATA** | not regulated |
| · **14.3 Transport hazard class(es)**<br>· **ADR/ADN, ADN, IMDG, IATA**<br>· **Class** | not regulated |
| · **14.4 Packing group**<br>· **ADR/ADN, IMDG, IATA** | not regulated |
| · **14.5 Environmental hazards:** | Not applicable |
| · **14.6 Special precautions for user** | Not applicable |
| · **14.7 Maritime transport in bulk according to IMO instruments** | Not applicable |
| · **Transport/Additional information:** | Not dangerous according to the above specifications. |
| · **UN "Model Regulation":** | not regulated |

## SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Directive 2012/18/EU**
· **Named dangerous substances - ANNEX I** None of the ingredients is listed.
· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**

· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

· **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

· **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

IE

(Contd. on page 10)

# Safety data sheet
## according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.07.2026 Version number 16 (replaces version 15) Revision: 18.07.2026

**Trade name:** GRF EPOXY REPAIR STICK DP 114G*12 L729

(Contd. of page 9)

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**
H302 Harmful if swallowed.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
EUH205 Contains epoxy constituents. May produce an allergic reaction.

· **Classification according to Regulation (EC) No 1272/2008**

| | |
|---|---|
| Skin corrosion/irritation<br>Serious eye damage/irritation<br>Skin sensitisation<br>Hazardous to the aquatic environment - long-term (chronic) aquatic hazard | The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008. |

· **Department issuing SDS:** PSRA
· **Contact:** PSRA
· **Date of previous version:** 26.04.2022
· **Version number of previous version:** 15
· **Abbreviations and acronyms:**
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
· *** Data compared to the previous version altered.**

IE