Safety Data Sheet
acc. to OSHA HCS

Printing date 07/18/2026 Reviewed on 07/18/2026

1 Identification

· **Product identifier**

· **Trade name:** GRF EPOXY REPAIR STICK DP 114G*12 L729
· **Application of the substance / the mixture** Adhesive

· **Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**
UHU GmbH
Herrmannstraße 7
D-77815 Bühl (Baden)
Tel.:0049-(0)7223-284-0 Fax: 0049-(0)7223-284-245
E-mail: sds@boltonadhesives.com

· **Information department:** PSRA
· **Emergency telephone number:**
Tel.: + 49 30 30686 700 (Notruf)
Tel.: + 49 (0) 30/19240 (Notruf)
Tel.: + 49 (0) 72 23/28 40

2 Hazard(s) identification

· **Classification of the substance or mixture**

Skin Irritation 2	H315 Causes skin irritation.
Eye Irritation 2A	H319 Causes serious eye irritation.
Sensitization - Skin 1	H317 May cause an allergic skin reaction.

· **Label elements**
· **Hazard pictograms**



GHS07

· **Signal word** Warning

· **Hazard-determining components of labeling:**
mercaptan polymer
bis-[4-(2,3-epoxipropoxi)phenyl]propane
· **Hazard statements**
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
· **Precautionary statements**

P280	Wear protective gloves.
P302+P352	If on skin: Wash with plenty of water.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501	Dispose of contents/container in accordance with national regulations.

(Contd. on page 2)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/18/2026 Reviewed on 07/18/2026

Trade name: GRF EPOXY REPAIR STICK DP 114G*12 L729

(Contd. of page 1)

· **Classification system:**
· **NFPA ratings (scale 0 - 4)**



Health = 2
Fire = 1
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = *2
Fire = 1
Reactivity = 0

· **Other hazards**
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**
· **Description:** Adhesive

· **Dangerous components:**		
14807-96-6	Talc (Mg3H2(SiO3)4)	25-50%
72244-98-5	mercaptan polymer	10-25%
1675-54-3	bis-[4-(2,3-epoxipropoxi)phenyl]propane	10-25%
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	1-2.5%

4 First-aid measures

· **Description of first aid measures**
· **General information:** No special measures required.
· **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
· **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
· **After swallowing:** If symptoms persist consult doctor.
· **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

US

(Contd. on page 3)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/18/2026 Reviewed on 07/18/2026

Trade name: GRF EPOXY REPAIR STICK DP 114G*12 L729

(Contd. of page 2)

5 Fire-fighting measures

· **Extinguishing media**
· **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
· **Special hazards arising from the substance or mixture**
No further relevant information available.
· **Advice for firefighters**
· **Protective equipment:** No special measures required.

*
6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures** Not required
· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
· **Methods and material for containment and cleaning up:**
Send for recovery or disposal in suitable receptacles.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
· **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
· **Protective Action Criteria for Chemicals**

· **PAC-1:**		
1675-54-3	bis-[4-(2,3-epoxipropoxi)phenyl]propane	39 mg/m3
471-34-1	calcium carbonate	45 mg/m3
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	0.60 mg/m3

· **PAC-2:**		
1675-54-3	bis-[4-(2,3-epoxipropoxi)phenyl]propane	430 mg/m3
471-34-1	calcium carbonate	210 mg/m3
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	6.6 mg/m3

· **PAC-3:**		
1675-54-3	bis-[4-(2,3-epoxipropoxi)phenyl]propane	2600 mg/m3
471-34-1	calcium carbonate	1300 mg/m3
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	40 mg/m3

7 Handling and storage

· **Handling:**
· **Precautions for safe handling** No special precautions are necessary if used correctly.
· **Information about protection against explosions and fires:** No special measures required.

· **Conditions for safe storage, including any incompatibilities**
· **Storage:**
· **Requirements to be met by storerooms and receptacles:** No special requirements.
· **Information about storage in one common storage facility:** Not required
· **Further information about storage conditions:** Keep receptacle tightly sealed.

(Contd. on page 4)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/18/2026 Reviewed on 07/18/2026

Trade name: GRF EPOXY REPAIR STICK DP 114G*12 L729

(Contd. of page 3)

· **Storage class:** 10
· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see section 7.

· **Control parameters**
· **Components with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**
· **Personal protective equipment:**
· **General protective and hygienic measures:**
The usual precautionary measures for handling chemicals should be followed.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
· **Breathing equipment:** Not required
· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
· **Material of gloves**
Recommended thickness of the material: > 0,12 mm
Nitrile rubber, NBR
· **Penetration time of glove material**
For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).
· **Eye protection:**



Tightly sealed goggles

Goggles recommended during refilling.

US

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/18/2026 Reviewed on 07/18/2026

Trade name: GRF EPOXY REPAIR STICK DP 114G*12 L729

(Contd. of page 4)

9 Physical and chemical properties

· **Information on basic physical and chemical properties**	
· **General Information**	
· **Appearance:**	
Form:	Solid
Color:	According to product specification
· **Odor:**	Characteristic
· **Odor threshold:**	Not determined
· **pH-value:**	Not determined
· **Change in condition**	
Melting point/Melting range:	Undetermined
Boiling point/Boiling range:	Undetermined
· **Flash point:**	>100 °C (>212 °F)
· **Flammability:**	Not applicable
· **Decomposition temperature:**	Not determined
· **Ignition temperature:**	Product is not selfigniting.
· **Danger of explosion:**	Product does not present an explosion hazard.
· **Explosion limits:**	
Lower:	Not determined
Upper:	Not determined
· **Vapor pressure:**	Not determined
· **Density at 20 °C (68 °F):**	1.9 g/cm³ (15.856 lbs/gal)
· **Relative density**	Not determined
· **Vapor density**	Not determined
· **Evaporation rate**	Not determined
· **Solubility in / Miscibility with**	
Water:	Not miscible or difficult to mix.
· **Partition coefficient (n-octanol/water):**	Not determined
· **Viscosity:**	
Dynamic:	Not determined
Kinematic:	Not determined
· **Solvent content:**	
VOC content:	0.00 %
Solids content:	70.8 %
· **Other information**	All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.

US

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/18/2026 Reviewed on 07/18/2026

Trade name: GRF EPOXY REPAIR STICK DP 114G*12 L729

(Contd. of page 5)

10 Stability and reactivity

· **Reactivity** No further relevant information available.
· **Chemical stability**
· **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
· **Possibility of hazardous reactions** No dangerous reactions known.
· **Conditions to avoid** No further relevant information available.
· **Incompatible materials:** No further relevant information available.
· **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· **Information on toxicological effects**
· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**		
1675-54-3 bis-[4-(2,3-epoxipropoxi)phenyl]propane		
Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
90-72-2 2,4,6-tris(dimethylaminomethyl)phenol		
Oral	LD50	500 mg/kg (rat)

· **Primary irritant effect:**
· **on the skin:** Irritant to skin and mucous membranes.
· **on the eye:** Irritating effect.
· **Sensitization:** Sensitization possible through skin contact.
· **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**		
14807-96-6	Talc (Mg3H2(SiO3)4)	2A
60676-86-0	Silica, vitreous	3
1675-54-3	bis-[4-(2,3-epoxipropoxi)phenyl]propane	3

· **NTP (National Toxicology Program)**
None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**
None of the ingredients is listed.

· **Germ cell mutagenicity** Not applicable

US

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/18/2026 Reviewed on 07/18/2026

Trade name: GRF EPOXY REPAIR STICK DP 114G*12 L729

(Contd. of page 6)

*
12 Ecological information

· **Toxicity**

· **Aquatic toxicity:**	
72244-98-5 mercaptan polymer	
EC50	12 mg/l (crustaceans)

· **Persistence and degradability** No further relevant information available.
· **Behavior in environmental systems:**
· **Bioaccumulative potential** No further relevant information available.
· **Mobility in soil** No further relevant information available.
· **Additional ecological information:**
· **General notes:**
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable
· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**
· **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
Disposal must be made according to official regulations.

· **Uncleaned packagings:**
· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**	
· **DOT, ADN**	not regulated
· **ADR/ADN, IMDG, IATA**	not regulated
	-
· **UN proper shipping name**	
· **DOT, ADR/ADN, ADN, IMDG, IATA**	not regulated
· **Transport hazard class(es)**	
· **DOT, ADR/ADN, ADN, IMDG, IATA**	
· **Class**	not regulated
· **Packing group**	
· **DOT, ADR/ADN, IMDG, IATA**	not regulated

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/18/2026 Reviewed on 07/18/2026

Trade name: GRF EPOXY REPAIR STICK DP 114G*12 L729

(Contd. of page 7)

· **Environmental hazards:**	Not applicable
· **Special precautions for user**	Not applicable
· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**	Not applicable
· **Transport/Additional information:**	Not dangerous according to the above specifications.
· **UN "Model Regulation":**	not regulated

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**

14807-96-6	Talc (Mg3H2(SiO3)4)	ACTIVE
60676-86-0	Silica, vitreous	ACTIVE
72244-98-5	mercaptan polymer	ACTIVE
1675-54-3	bis-[4-(2,3-epoxipropoxi)phenyl]propane	ACTIVE
471-34-1	calcium carbonate	ACTIVE
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	ACTIVE

· **Hazardous Air Pollutants**

None of the ingredients is listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/18/2026 Reviewed on 07/18/2026

Trade name: GRF EPOXY REPAIR STICK DP 114G*12 L729

(Contd. of page 8)

· **TLV (Threshold Limit Value)**

14807-96-6	Talc (Mg3H2(SiO3)4)	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
· **Hazard pictograms**



GHS07

· **Signal word** Warning

· **Hazard-determining components of labeling:**
mercaptan polymer
bis-[4-(2,3-epoxipropoxi)phenyl]propane
· **Hazard statements**
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
· **Precautionary statements**
P280 Wear protective gloves.
P302+P352 If on skin: Wash with plenty of water.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501 Dispose of contents/container in accordance with national regulations.
· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** PSRA
· **Contact:** PSRA
· **Date of preparation / last revision** 07/18/2026 / 15
· **Abbreviations and acronyms:**
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/18/2026 Reviewed on 07/18/2026

Trade name: GRF EPOXY REPAIR STICK DP 114G*12 L729

(Contd. of page 9)

vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Skin Irritation 2: Skin corrosion/irritation – Category 2
Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A
Sensitization - Skin 1: Skin sensitisation – Category 1
· *** Data compared to the previous version altered.**

US