Safety Data Sheet
acc. to OSHA HCS

Printing date 07/15/2026 Reviewed on 07/15/2026

1 Identification

· **Product identifier**

· **Trade name:** GRF STEX LIQUID BO 1L*6 NLFR
· **Application of the substance / the mixture** Cleaning agent/ Cleaner

· **Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**
Bison International
Dr.A.F.Philipsstraat 9
NL-4462 EW Goes
PO Box 160
NL-4460 AD Goes
tel. +31 88 3235700
fax. +31 88 3235800
e mail: sds@boltonadhesives.com

· **Information department:** PSRA
· **Emergency telephone number:**
Bison and Griffon products: +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET)
UHU products: + 49 (0) 30/19240 (Notruf). Operating hours mo-fr 08:00h-17:00h (CET)

For detailed information contact the national Poison Centre @
https://poisoncentres.echa.europa.eu/appointed-bodies

2 Hazard(s) identification

· **Classification of the substance or mixture**
Skin Corrosion 1A H314 Causes severe skin burns and eye damage.
Eye Damage 1 H318 Causes serious eye damage.

· **Label elements**
· **Hazard pictograms**



GHS05

· **Signal word** Danger

· **Hazard-determining components of labeling:**
??
· **Hazard statements**
H314 Causes severe skin burns and eye damage.
· **Precautionary statements**
P260 Do not breathe vapours.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a poison center/doctor.

(Contd. on page 2)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/15/2026 Reviewed on 07/15/2026

Trade name: GRF STEX LIQUID BO 1L*6 NLFR

(Contd. of page 1)

P501 Dispose of contents/container in accordance with national regulations.

· **Classification system:**
· **NFPA ratings (scale 0 - 4)**



Health = 3
Fire = 0
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = *3
Fire = 0
Reactivity = 0

· **Other hazards**
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**
· **Description:** Cleansing agent

· **Dangerous components:**

1310-73-2	sodium hydroxide	25-50%

4 First-aid measures

· **Description of first aid measures**
· **General information:** Immediately remove any clothing soiled by the product.
· **After inhalation:**
Call a doctor immediately.
In case of unconsciousness place patient stably in side position for transportation.
· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
· **After eye contact:**
Rinse opened eye for several minutes under running water. Then consult a doctor.
· **After swallowing:**
Rinse out mouth and then drink plenty of water.
Drink copious amounts of water and provide fresh air. Immediately call a doctor.
· **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

US

(Contd. on page 3)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/15/2026 Reviewed on 07/15/2026

Trade name: GRF STEX LIQUID BO 1L*6 NLFR

(Contd. of page 2)

5 Fire-fighting measures

· **Extinguishing media**
· **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
· **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
· **Advice for firefighters**
· **Protective equipment:** Mouth respiratory protective device.

*

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
· **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
· **Methods and material for containment and cleaning up:**
Send for recovery or disposal in suitable receptacles.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
· **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
· **Protective Action Criteria for Chemicals**

· **PAC-1:**		
1310-73-2	sodium hydroxide	0.50 mg/m3
· **PAC-2:**		
1310-73-2	sodium hydroxide	5.0 mg/m3
· **PAC-3:**		
1310-73-2	sodium hydroxide	50 mg/m3

7 Handling and storage

· **Handling:**
· **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
· **Information about protection against explosions and fires:**
Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**
· **Storage:**
· **Requirements to be met by storerooms and receptacles:** No special requirements.

(Contd. on page 4)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/15/2026 Reviewed on 07/15/2026

Trade name: GRF STEX LIQUID BO 1L*6 NLFR

(Contd. of page 3)

· **Information about storage in one common storage facility:** Not required
· **Further information about storage conditions:** Keep receptacle tightly sealed.
· **Storage class:** 8 B
· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see section 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**	
1310-73-2 sodium hydroxide	
PEL	Long-term value: 2 mg/m³
REL	Ceiling limit value: 2 mg/m³
TLV	Ceiling limit value: 2 mg/m³

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**
· **Personal protective equipment:**
· **General protective and hygienic measures:**
The usual precautionary measures for handling chemicals should be followed.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.
· **Breathing equipment:** Not required
· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
· **Material of gloves**
Recommended thickness of the material: > 0,12 mm
Nitrile rubber, NBR
· **Penetration time of glove material**
For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/15/2026 Reviewed on 07/15/2026

Trade name: GRF STEX LIQUID BO 1L*6 NLFR

(Contd. of page 4)

· **Eye protection:**



Tightly sealed goggles

Goggles recommended during refilling.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**	
· **General Information**	
· **Appearance:**	
Form:	Fluid
Color:	Clear
· **Odor:**	Recognizable
· **Odor threshold:**	Not determined
· **pH-value at 20 °C (68 °F):**	14
· **Change in condition**	
Melting point/Melting range:	Undetermined
Boiling point/Boiling range:	100 °C (212 °F)
· **Flash point:**	Not applicable
· **Flammability:**	Not applicable
· **Decomposition temperature:**	Not determined
· **Ignition temperature:**	Product is not selfigniting.
· **Danger of explosion:**	Product does not present an explosion hazard.
· **Explosion limits:**	
Lower:	Not determined
Upper:	Not determined
· **Vapor pressure at 20 °C (68 °F):**	23 hPa (17.3 mm Hg)
· **Density at 20 °C (68 °F):**	1.564 g/cm³ (13.052 lbs/gal)
· **Relative density**	Not determined
· **Vapor density**	Not determined
· **Evaporation rate**	Not determined
· **Solubility in / Miscibility with**	
Water:	Fully miscible.
· **Partition coefficient (n-octanol/water):**	Not determined
· **Viscosity:**	
Dynamic:	Not determined
Kinematic:	Not determined

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/15/2026 Reviewed on 07/15/2026

Trade name: GRF STEX LIQUID BO 1L*6 NLFR

(Contd. of page 5)

· **Solvent content:**	
Water:	50.1 %
VOC content:	0.00 %
Solids content:	49.9 %
· **Other information**	All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.

10 Stability and reactivity

· **Reactivity** No further relevant information available.
· **Chemical stability**
· **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
· **Possibility of hazardous reactions** Corrosive action on metals.
· **Conditions to avoid** No further relevant information available.
· **Incompatible materials:** No further relevant information available.
· **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· **Information on toxicological effects**
· **Acute toxicity:**
· **Primary irritant effect:**
· **on the skin:** Strong caustic effect on skin and mucous membranes.
· **on the eye:**
Strong caustic effect.
Strong irritant with the danger of severe eye injury.
· **Sensitization:** No sensitizing effects known.
· **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Corrosive
Irritant
Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**
None of the ingredients is listed.

· **NTP (National Toxicology Program)**
None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**
None of the ingredients is listed.

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/15/2026 Reviewed on 07/15/2026

Trade name: GRF STEX LIQUID BO 1L*6 NLFR

(Contd. of page 6)

· **Germ cell mutagenicity** Not applicable

12 Ecological information

· **Toxicity**
· **Aquatic toxicity:** No further relevant information available.
· **Persistence and degradability** No further relevant information available.
· **Behavior in environmental systems:**
· **Bioaccumulative potential** No further relevant information available.
· **Mobility in soil** No further relevant information available.
· **Additional ecological information:**
· **General notes:**
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Must not reach bodies of water or drainage ditch undiluted or unneutralized.
Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable
· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**
· **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
Disposal must be made according to official regulations.

· **Uncleaned packagings:**
· **Recommendation:**
Packagings that cannot be cleansed are to be disposed of in the same manner as the product.
· **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

· **UN-Number**	
· **DOT, ADR/ADN, IMDG, IATA**	UN1824
· **UN proper shipping name**	
· **DOT**	Sodium hydroxide solution
· **ADR/ADN**	1824 SODIUM HYDROXIDE SOLUTION
· **IMDG, IATA**	SODIUM HYDROXIDE SOLUTION

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/15/2026 Reviewed on 07/15/2026

Trade name: GRF STEX LIQUID BO 1L*6 NLFR

(Contd. of page 7)

· **Transport hazard class(es)**

· **DOT**



· **Class**	8 Corrosive substances
· **Label**	8

· **ADR/ADN**



· **Class**	8 (C5) Corrosive substances
· **Label**	8

· **IMDG, IATA**



· **Class**	8 Corrosive substances
· **Label**	8
· **Packing group**	
· **DOT, ADR/ADN, IMDG, IATA**	II
· **Environmental hazards:**	
· **Marine pollutant:**	No
· **Special precautions for user**	Warning: Corrosive substances
· **Hazard identification number (Kemler code):**	80
· **EMS Number:**	F-A,S-B
· **Segregation groups**	(SGG18) Alkalis
· **Stowage Category**	A
· **Segregation Code**	SG35 Stow "separated from" SGG1-acids
· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**	Not applicable
· **Transport/Additional information:**	
· **DOT**	
· **Quantity limitations**	On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L

· **ADR/ADN**

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/15/2026 Reviewed on 07/15/2026

Trade name: GRF STEX LIQUID BO 1L*6 NLFR

(Contd. of page 8)

· **Excepted quantities (EQ)**	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· **IMDG**	
· **Limited quantities (LQ)**	1L
· **Excepted quantities (EQ)**	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· **UN "Model Regulation":**	UN 1824 SODIUM HYDROXIDE SOLUTION, 8, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**
None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**
None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**
All components have the value ACTIVE.

· **Hazardous Air Pollutants**
None of the ingredients is listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**
None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**
None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**
None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**
None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**
None of the ingredients is listed.

· **TLV (Threshold Limit Value)**
None of the ingredients is listed.

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/15/2026 Reviewed on 07/15/2026

Trade name: GRF STEX LIQUID BO 1L*6 NLFR

(Contd. of page 9)

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
· **Hazard pictograms**



GHS05

· **Signal word** Danger

· **Hazard-determining components of labeling:**
??
· **Hazard statements**
H314 Causes severe skin burns and eye damage.
· **Precautionary statements**

P260	Do not breathe vapours.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331	If swallowed: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a poison center/doctor.
P501	Dispose of contents/container in accordance with national regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** PSRA
· **Contact:** PSRA
· **Date of preparation / last revision** 07/15/2026 / 23
· **Abbreviations and acronyms:**
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/15/2026 Reviewed on 07/15/2026

Trade name: GRF STEX LIQUID BO 1L*6 NLFR

(Contd. of page 10)

PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Skin Corrosion 1A: Skin corrosion/irritation – Category 1A
Eye Damage 1: Serious eye damage/eye irritation – Category 1
· *** Data compared to the previous version altered.**

US