Safety Data Sheet
according to WHS Regulations

Date of issue: 16.07.2026 Version number 48 Revision: 16.07.2026

Hazardous according to criteria of Australian Safety and Compensation Council.

1 Identification

· **Other means of identification**

· **Trade name:** GRF SPRAY ADHESIVE AE 500ML*12 L221
· **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
· **Application of the substance / the mixture** Adhesive

· **Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**
Bison International B.V.
Dr.A.F.Philipsstraat 9
NL-4462 EW Goes
PO Box 160
NL-4460 AD Goes
tel. +31 88 3235700
fax. +31 88 3235800
e-mail: sds@boltonadhesives.com

FABER - CASTELL
15 GIBBON RD.
WINSTON HILL
NSW 2153
Toll Free: 1800 677 885
Free Fax: 1800 678 608
EMAIL: enquiries@faber-castell.com.au

· **Further information obtainable from:** PSRA
· **Emergency telephone number:**
POISONS INFORMATION CENTRE (PIC)
TEL: 13 11 26

2 Hazard(s) Identification

· **Classification of the substance or mixture**

Aerosols – Category 1	H222 Extremely flammable aerosol.
	H229 Pressurized container: may burst if heated.
Skin corrosion/irritation – Category 2	H315 Causes skin irritation.
Germ cell mutagenicity – Category 1B	H340 May cause genetic defects.
Carcinogenicity – Category 1B	H350 May cause cancer.
Specific target organ toxicity (single exposure) – Category 3	H336 May cause drowsiness or dizziness.

(Contd. on page 2)

Safety Data Sheet
according to WHS Regulations

Date of issue: 16.07.2026 Version number 48 Revision: 16.07.2026

Trade name: GRF SPRAY ADHESIVE AE 500ML*12 L221

(Contd. of page 1)

· **Label elements**
· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (30-60 %)
Hydrocarbons, C6, isoalkanes, <5% n-hexane (≥0.1-<10 %)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane (≥0.1-<10 %)
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane (<10 %)
· **Hazard statements**
H222 Extremely flammable aerosol.
H229 Pressurized container: may burst if heated.
H315 Causes skin irritation.
H340 May cause genetic defects.
H350 May cause cancer.
H336 May cause drowsiness or dizziness.
· **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P261 Avoid breathing spray.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with national regulations.
· **Other hazards**
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable

*

3 Composition and Information on Ingredients

· **Chemical characterisation: Mixtures**
· **Description:** Adhesive

· **Dangerous components:**		
115-10-6	dimethyl ether Flammable gases – Category 1A, H220; Gases under pressure – Compressed gas, H280	30-60%
	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics Flammable liquids – Category 2, H225; Aspiration hazard – Category 1, H304; Skin corrosion/irritation – Category 2, H315; Specific target organ toxicity (single exposure) – Category 3, H336	30-60%

(Contd. on page 3)

Safety Data Sheet
according to WHS Regulations

Date of issue: 16.07.2026 Version number 48 Revision: 16.07.2026

Trade name: GRF SPRAY ADHESIVE AE 500ML*12 L221

(Contd. of page 2)

	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane Flammable liquids – Category 2, H225; Aspiration hazard – Category 1, H304; Specific target organ toxicity (single exposure) – Category 3, H336	<10%
	Hydrocarbons, C6, isoalkanes, <5% n-hexane Flammable liquids – Category 2, H225; Germ cell mutagenicity – Category 1B, H340; Carcinogenicity – Category 1B, H350; Aspiration hazard – Category 1, H304; Skin corrosion/irritation – Category 2, H315; Specific target organ toxicity (single exposure) – Category 3, H336	≥0.1-<10%
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Flammable liquids – Category 2, H225; Germ cell mutagenicity – Category 1B, H340; Carcinogenicity – Category 1B, H350; Aspiration hazard – Category 1, H304; Skin corrosion/irritation – Category 2, H315; Specific target organ toxicity (single exposure) – Category 3, H336	≥0.1-<10%
110-82-7	cyclohexane Flammable liquids – Category 2, H225; Aspiration hazard – Category 1, H304; Skin corrosion/irritation – Category 2, H315; Specific target organ toxicity (single exposure) – Category 3, H336	≥2.5-<10%
108-87-2	Methylcyclohexane Flammable liquids – Category 2, H225; Aspiration hazard – Category 1, H304; Skin corrosion/irritation – Category 2, H315; Specific target organ toxicity (single exposure) – Category 3, H336	≥0.25-<2.5%
110-54-3	n-hexane Flammable liquids – Category 2, H225; Reproductive toxicity – Category 2, H361; Specific target organ toxicity (repeated exposure) – Category 2, H373; Aspiration hazard – Category 1, H304; Skin corrosion/irritation – Category 2, H315; Specific target organ toxicity (single exposure) – Category 3, H336	<0.25%
128-37-0	Butylated hydroxytoluene	<10%

· **SVHC**

110-54-3	n-hexane

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

· **General information:** No special measures required.
· **After inhalation:**
In case of unconsciousness place patient stably in side position for transportation.
· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
· **After eye contact:** Rinse opened eye for several minutes under running water.
· **After swallowing:** If symptoms persist consult doctor.
· **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed**
No further relevant information available.

(Contd. on page 4)

Safety Data Sheet
according to WHS Regulations

Date of issue: 16.07.2026 Version number 48 Revision: 16.07.2026

Trade name: GRF SPRAY ADHESIVE AE 500ML*12 L221

(Contd. of page 3)

· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire Fighting Measures

· **Suitable extinguishing agents:**
CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
· **Special hazards arising from the substance or mixture**
No further relevant information available.
· **Protective equipment:** No special measures required.

6 Accidental Release Measures

· **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
· **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
· **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and Storage

· **Handling:**
· **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
· **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
· **Storage:**
· **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
· **Information about storage in one common storage facility:** Not required
· **Further information about storage conditions:** Keep container tightly sealed.
· **Storage class:** 2 B
· **Specific end use(s)** No further relevant information available.

8 Exposure controls and personal protection

· **Appropriate engineering controls** No further data; see section 7.

(Contd. on page 5)

Safety Data Sheet
according to WHS Regulations

Date of issue: 16.07.2026 Version number 48 Revision: 16.07.2026

Trade name: GRF SPRAY ADHESIVE AE 500ML*12 L221

(Contd. of page 4)

· **Ingredients with limit values that require monitoring at the workplace:**

115-10-6 dimethyl ether	
WES	Short-term value: 950 mg/m³, 500 ppm Long-term value: 760 mg/m³, 400 ppm
110-82-7 cyclohexane	
WES	Short-term value: 1050 mg/m³, 300 ppm Long-term value: 350 mg/m³, 100 ppm
108-87-2 Methylcyclohexane	
WES	Long-term value: 1610 mg/m³, 400 ppm
110-54-3 n-hexane	
WES	Long-term value: 72 mg/m³, 20 ppm
128-37-0 Butylated hydroxytoluene	
WES	Long-term value: 10 mg/m³

· **DNELs**

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics		
Oral	Consumer, oral, longterm exposition	149 mg/kg bw/day (rat)
Dermal	Worker, dermal, longterm exposition	300 mg/kg bw/day (rat)
	Consumer, dermal, longterm exposition	149 mg/kg bw/day (rat)
Inhalative	Worker, inhalative, longterm exposition	2085 mg/m³ (rat)
	Consumer, inhalative, longterm exposition	477 mg/m³ (rat)
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane		
Oral	Consumer, oral, longterm exposition	1301 mg/kg bw/day (rat)
Dermal	Worker, dermal, longterm exposition	13964 mg/kg bw/day (rat)
	Consumer, dermal, longterm exposition	1377 mg/kg bw/day (rat)
Inhalative	Worker, inhalative, longterm exposition	5306 mg/m³ (rat)
	Consumer, inhalative, longterm exposition	1131 mg/m³ (rat)
Hydrocarbons, C6, isoalkanes, <5% n-hexane		
Oral	Consumer, oral, longterm exposition	1301 mg/kg bw/day (rat)
Dermal	Worker, dermal, longterm exposition	13964 mg/kg bw/day (rat)
	Consumer, dermal, longterm exposition	1377 mg/kg bw/day (rat)
Inhalative	Worker, inhalative, longterm exposition	5306 mg/m³ (rat)
	Consumer, inhalative, longterm exposition	1131 mg/m³ (rat)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
Oral	Consumer, oral, longterm exposition	699 mg/kg bw/day (rat)
Dermal	Worker, dermal, longterm exposition	773 mg/kg bw/day (rat)
	Consumer, dermal, longterm exposition	699 mg/kg bw/day (rat)
Inhalative	Worker, inhalative, longterm exposition	2035 mg/m³ (rat)
	Consumer, inhalative, longterm exposition	608 mg/m³ (rat)
110-82-7 cyclohexane		
Oral	Consumer, oral, longterm exposition	59.4 mg/kg bw/day (rat)
Dermal	Worker, dermal, longterm exposition	2016 mg/kg bw/day (rat)

(Contd. on page 6)

Safety Data Sheet
according to WHS Regulations

Date of issue: 16.07.2026 Version number 48 Revision: 16.07.2026

Trade name: GRF SPRAY ADHESIVE AE 500ML*12 L221

(Contd. of page 5)

	Consumer, dermal, longterm exposition	1186 mg/kg bw/day (rat)
Inhalative	Worker, inhalative, shortterm exposition	700 mg/m³ (rat)
	Worker, inhalative, longterm exposition	700 mg/m³ (rat)
	Consumer DNEL, acute inhalation	412 mg/m³ (rat)
	Consumer, inhalative, longterm exposition	206 mg/m³ (rat)
108-87-2 Methylcyclohexane		
Oral	Consumer, oral, longterm exposition	0.4 mg/kg bw/day
Dermal	Worker, dermal, longterm exposition	1.7 mg/kg bw/day
	Consumer, dermal, longterm exposition	0.8 mg/kg bw/day
Inhalative	Worker, inhalative, shortterm exposition	1354.6 mg/m³
	Worker, inhalative, longterm exposition	64.3 mg/m³
	Consumer DNEL, acute inhalation	1016 mg/m³
	Consumer, inhalative, longterm exposition	16 mg/m³
128-37-0 Butylated hydroxytoluene		
Oral	Consumer, oral, longterm exposition	0.25 mg/kg bw/day
Dermal	Worker, dermal, longterm exposition	0.5 mg/kg bw/day
	Consumer, dermal, longterm exposition	0.25 mg/kg bw/day
Inhalative	Worker, inhalative, longterm exposition	1.76 mg/m³
	Consumer, inhalative, longterm exposition	0.435 mg/m³

· **PNECs**

110-82-7 cyclohexane	
Fresh water	0.207 mg/l (rat)
Fresh water sediment	3.627 mg/kg dry weight (rat)
Marine water	0.207 mg/l (rat)
Marine sediment	3.627 mg/kg dry weight (rat)
Soil	2.99 mg/kg (rat)
Sewage treatment plant	3.24 mg/l (rat)
Sporadic release	0.207 mg/l
108-87-2 Methylcyclohexane	
Fresh water	0.00134 mg/l
Fresh water sediment	0.0362 mg/kg dry weight
Marine water	0.000134 mg/l
Marine sediment	0.00362 mg/kg dry weight
Soil	0.0097 mg/kg
Sewage treatment plant	0.273 mg/l
128-37-0 Butylated hydroxytoluene	
Fresh water	0.000199 mg/l
Fresh water sediment	0.45819 mg/kg dry weight
Marine water	0.0000199 mg/l
Marine sediment	0.04582 mg/kg dry weight

(Contd. on page 7)

Safety Data Sheet
according to WHS Regulations

Date of issue: 16.07.2026 Version number 48 Revision: 16.07.2026

Trade name: GRF SPRAY ADHESIVE AE 500ML*12 L221

(Contd. of page 6)

Soil	0.0539 mg/kg
Sewage treatment plant	0.017 mg/l

· **Additional information:** The lists valid during the making were used as basis.
· **Personal protective equipment:**
· **General protective and hygienic measures:**
The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Do not inhale gases / fumes / aerosols.
Avoid contact with the skin.
Avoid contact with the eyes and skin.
· **Respiratory protection:**
Use suitable respiratory protective device in case of insufficient ventilation.
· **Recommended filter device for short term use:** Filter A
· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
· **Material of gloves**
Recommended thickness of the material: > 0,12 mm
Nitrile rubber, NBR
· **Penetration time of glove material**
For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).
· **Eye protection:**
Safety glasses



Tightly sealed goggles

· **Body protection:** Use protective suit.

*
9 Physical and Chemical Properties

· **General Information**	
· **Appearance:**	
· **Form:**	Aerosol
· **Colour:**	According to product specification
· **Odour:**	Characteristic
· **Odour threshold:**	Not determined

(Contd. on page 8)

Safety Data Sheet
according to WHS Regulations

Date of issue: 16.07.2026 Version number 48 Revision: 16.07.2026

Trade name: GRF SPRAY ADHESIVE AE 500ML*12 L221

(Contd. of page 7)

· **pH-value:**	Mixture is a gas.
· **Change in condition**	
· **Melting point/freezing point:**	Undetermined
· **Initial boiling point and boiling range:**	-24.9 °C
· **Flash point:**	-42 °C
· **Flammability**	Not applicable
· **Auto-ignition temperature:**	235 °C
· **Decomposition temperature:**	Not determined
· **Ignition temperature:**	Product is not selfigniting.
· **Explosive properties:**	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· **Explosion limits:**	
· **Lower:**	0.7 Vol %
· **Upper:**	18.6 Vol %
· **Vapour pressure at 20 °C:**	5200 hPa
· **Density at 20 °C:**	0.75 g/cm³
· **Relative density**	Not determined
· **Vapour density**	Not determined
· **Evaporation rate**	Not applicable.
· **Solubility in / Miscibility with**	
· **water:**	Not miscible or difficult to mix.
· **Partition coefficient: n-octanol/water:**	Not determined
· **Viscosity:**	
· **Dynamic:**	Not determined
· **Kinematic:**	Not determined
· **Solvent content:**	
· **Organic solvents:**	86.1 %
· **VOC (EC)**	86.11 %
· **Solids content:**	13.5 %
· **Other information**	All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.
· **Particle characteristics**	Not applicable
· **Physical state**	Aerosol

10 Stability and Reactivity

· **Reactivity** No further relevant information available.
· **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
· **Possibility of hazardous reactions** No dangerous reactions known.
· **Conditions to avoid** No further relevant information available.
· **Incompatible materials:** No further relevant information available.
· **Hazardous decomposition products:** Danger of forming toxic pyrolysis products.

AU

(Contd. on page 9)

Safety Data Sheet
according to WHS Regulations

Date of issue: 16.07.2026 Version number 48 Revision: 16.07.2026

Trade name: GRF SPRAY ADHESIVE AE 500ML*12 L221

(Contd. of page 8)

11 Toxicological Information

· **Information on toxicological effects**
· **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**		
115-10-6 dimethyl ether		
Inhalative	LC50/4 h	308 mg/l (rat)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics		
Oral	LD50	>5840 mg/kg (rat)
Dermal	LD50	>2920 mg/kg (rat)
Inhalative	LC50/4 h	>23.3 mg/l (rat)
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane		
Oral	LD50	>3350 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50/4 h	>20 mg/l (rat)
Hydrocarbons, C6, isoalkanes, <5% n-hexane		
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>3000 mg/kg (rat)
Inhalative	LC50/4 h	>20 mg/l (rat)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50/4 h	>20 mg/l (rat)
110-82-7 cyclohexane		
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4 h	32.88 mg/l (rat)
108-87-2 Methylcyclohexane		
Oral	LD50	4000-4500 mg/kg (rabbit)
Dermal	LD50	>2000 mg/kg (rabbit)
110-54-3 n-hexane		
Oral	LD50	16000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50/4 h	172 mg/l (rat)
128-37-0 Butylated hydroxytoluene		
Oral	LD50	>2930 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)

· **Primary irritant effect:**
· **Skin corrosion/irritation**
Causes skin irritation.
· **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
· **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

(Contd. on page 10)

Safety Data Sheet
according to WHS Regulations

Date of issue: 16.07.2026 Version number 48 Revision: 16.07.2026

Trade name: GRF SPRAY ADHESIVE AE 500ML*12 L221

(Contd. of page 9)

· **Germ cell mutagenicity**
Not applicable
May cause genetic defects.
· **Carcinogenicity** May cause cancer.
· **Reproductive toxicity** Based on available data, the classification criteria are not met.
· **STOT-single exposure** May cause drowsiness or dizziness.
· **STOT-repeated exposure** Based on available data, the classification criteria are not met.
· **Aspiration hazard** Based on available data, the classification criteria are not met.
· **Interactive effects**
· **Acute effects (acute toxicity, irritation and corrosivity)** Not applicable
· **Sensitisation** Not applicable
· **Repeated dose toxicity** Not applicable

12 Ecological Information

· **Toxicity**
· **Aquatic toxicity:** No further relevant information available.
· **Persistence and degradability** No further relevant information available.
· **Behaviour in environmental systems:**
· **Bioaccumulative potential** No further relevant information available.
· **Mobility in soil** No further relevant information available.
· **Additional ecological information:**
· **General notes:**
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable
· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**
· **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Disposal must be made according to official regulations.

· **Uncleaned packaging:**
· **Recommendation:**
Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14 Transport information

· **UN-Number**
· **ADG, IMDG, IATA** UN1950

(Contd. on page 11)

Safety Data Sheet
according to WHS Regulations

Date of issue: 16.07.2026 Version number 48 Revision: 16.07.2026

Trade name: GRF SPRAY ADHESIVE AE 500ML*12 L221

(Contd. of page 10)

· **UN proper shipping name**	
· **ADG**	1950 AEROSOLS
· **IMDG**	AEROSOLS, MARINE POLLUTANT
· **IATA**	AEROSOLS, flammable
· **Transport hazard class(es)**	
· **ADG**	
· **Class**	2 5F Gases.
· **Label**	2.1
· **IMDG**	
· **Class**	2.1 Gases.
· **Label**	2.1
· **IATA**	
· **Class**	2.1 Gases.
· **Label**	2.1
· **Packing group**	
· **ADG, IMDG, IATA**	not regulated
· **Environmental hazards:**	Product contains environmentally hazardous substances: Naphtha (petroleum), hydrotreated light
· **Marine pollutant:**	Yes Symbol (fish and tree)
· **Special marking (ADG):**	Symbol (fish and tree)
· **Special precautions for user**	Warning: Gases.
· **Hazard identification number (Kemler code):**	-
· **EMS Number:**	F-D,S-U
· **Stowage Code**	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· **Segregation Code**	SG69 For AEROSOLS with a maximum capacity of 1 litre:

(Contd. on page 12)

Safety Data Sheet
according to WHS Regulations

Date of issue: 16.07.2026 Version number 48 Revision: 16.07.2026

Trade name: GRF SPRAY ADHESIVE AE 500ML*12 L221

(Contd. of page 11)

·	Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· **Transport in bulk according to Annex II of Marpol and the IBC Code**	Not applicable
· **Transport/Additional information:**	
· **Quantity limitations**	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg
· **ADG**	
· **Limited quantities (LQ)**	1L
· **Excepted quantities (EQ)**	Code: E0 Not permitted as Excepted Quantity
· **Transport category**	2
· **Tunnel restriction code**	D
· **IMDG**	
· **Limited quantities (LQ)**	1L
· **Excepted quantities (EQ)**	Code: E0 Not permitted as Excepted Quantity
· **UN "Model Regulation":**	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Australian Inventory of Industrial Chemicals**	
64365-17-9	Resin acids and Rosin acids, hydrogenated, esters with pentaerythritol
9003-55-8	1,3 Butadiene/styrene copolymer
110-82-7	cyclohexane
108-87-2	Methylcyclohexane
110-54-3	n-hexane
128-37-0	Butylated hydroxytoluene
68442-68-2	benzenamine, N-phenyl-, styrenated
122-39-4	diphenylamine

· **Standard for the Uniform Scheduling of Medicines and Poisons**
None of the ingredients is listed.

(Contd. on page 13)

Safety Data Sheet
according to WHS Regulations

Date of issue: 16.07.2026 Version number 48 Revision: 16.07.2026

Trade name: GRF SPRAY ADHESIVE AE 500ML*12 L221

(Contd. of page 12)

· **Australia: Priority Existing Chemicals**
None of the ingredients is listed.

· **GHS label elements**
The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (30-60 %)
Hydrocarbons, C6, isoalkanes, <5% n-hexane (≥0.1-<10 %)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane (≥0.1-<10 %)
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane (<10 %)

· **Hazard statements**
H222 Extremely flammable aerosol.
H229 Pressurized container: may burst if heated.
H315 Causes skin irritation.
H340 May cause genetic defects.
H350 May cause cancer.
H336 May cause drowsiness or dizziness.

· **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P261 Avoid breathing spray.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with national regulations.

· **Directive 2012/18/EU**
· **Named dangerous substances - ANNEX I** None of the ingredients is listed.
· **Seveso category**
P3a FLAMMABLE AEROSOLS
E2 Hazardous to the Aquatic Environment
· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **National regulations:**

· **Information about limitation of use:**
Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

(Contd. on page 14)

Safety Data Sheet
according to WHS Regulations

Date of issue: 16.07.2026 Version number 48 Revision: 16.07.2026

Trade name: GRF SPRAY ADHESIVE AE 500ML*12 L221

(Contd. of page 13)

· **Other regulations, limitations and prohibitive regulations**

· **Substances of very high concern (SVHC) according to REACH, Article 57**	
110-54-3	n-hexane

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**
H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H340 May cause genetic defects.
H350 May cause cancer.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.

· **Department issuing SDS:** PSRA
· **Contact:** PSRA
· **Abbreviations and acronyms:**
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern
vPvB: very Persistent and very Bioaccumulative
Flammable gases – Category 1A: Flammable gases – Category 1A
Aerosols – Category 1: Aerosols – Category 1
: Aerosols – Category 3
Gases under pressure – Compressed gas: Gases under pressure – Compressed gas
Flammable liquids – Category 2: Flammable liquids – Category 2
Skin corrosion/irritation – Category 2: Skin corrosion/irritation – Category 2
Germ cell mutagenicity – Category 1B: Germ cell mutagenicity – Category 1B
Carcinogenicity – Category 1B: Carcinogenicity – Category 1B
Reproductive toxicity – Category 2: Reproductive toxicity – Category 2
Specific target organ toxicity (single exposure) – Category 3: Specific target organ toxicity (single exposure) – Category 3
Specific target organ toxicity (repeated exposure) – Category 2: Specific target organ toxicity (repeated exposure) – Category 2
Aspiration hazard – Category 1: Aspiration hazard – Category 1
· *** Data compared to the previous version altered.**

AU