Safety Data Sheet
acc. to OSHA HCS

Printing date 07/16/2026 Reviewed on 07/16/2026

1 Identification

· **Product identifier**

· **Trade name:** GRF SPRAY ADHESIVE AE 500ML*12 L221
· **Application of the substance / the mixture** Adhesive

· **Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**
Bison International
Dr.A.F.Philipsstraat 9
NL-4462 EW Goes
PO Box 160
NL-4460 AD Goes
tel. +31 88 3235700
fax. +31 88 3235800
e mail: sds@boltonadhesives.com

· **Information department:** PSRA
· **Emergency telephone number:**
Bison and Griffon products: +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET)
UHU products: + 49 (0) 30/19240 (Notruf). Operating hours mo-fr 08:00h-17:00h (CET)

For detailed information contact the national Poison Centre @
https://poisoncentres.echa.europa.eu/appointed-bodies

2 Hazard(s) identification

· **Classification of the substance or mixture**

Aerosols 1	H222 Extremely flammable aerosol.
Skin Irritation 2	H315 Causes skin irritation.
Toxic to Reproduction 2	H361 Suspected of damaging fertility or the unborn child.
Specific Target Organ Toxicity - Single Exposure 3	H336 May cause drowsiness or dizziness.

· **Label elements**
· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics
n-hexane
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane
Hydrocarbons, C6, isoalkanes, <5% n-hexane
· **Hazard statements**
H222 Extremely flammable aerosol.
H315 Causes skin irritation.
H361 Suspected of damaging fertility or the unborn child.

(Contd. on page 2)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/16/2026 Reviewed on 07/16/2026

Trade name: GRF SPRAY ADHESIVE AE 500ML*12 L221

(Contd. of page 1)

H336 May cause drowsiness or dizziness.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P261 Avoid breathing spray.
P302+P352 If on skin: Wash with plenty of soap and water.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501 Dispose of contents/container in accordance with national regulations.

· **Classification system:**
· **NFPA ratings (scale 0 - 4)**



Health = 1
Fire = 4
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 1
Fire = 4
Reactivity = 3

· **Other hazards**
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**
· **Description:** Adhesive

· **Dangerous components:**

115-10-6	dimethyl ether	25-50%
	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	25-50%
	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	2.5-10%
	Hydrocarbons, C6, isoalkanes, <5% n-hexane	≥2.5-<10%
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	≥2.5-<10%
110-82-7	cyclohexane	≥2.5-<10%
108-87-2	Methylcyclohexane	1-2.5%
110-54-3	n-hexane	≥0.1-<1%
128-37-0	Butylated hydroxytoluene	<1%

4 First-aid measures

· **Description of first aid measures**
· **General information:** No special measures required.

(Contd. on page 3)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/16/2026 Reviewed on 07/16/2026

Trade name: GRF SPRAY ADHESIVE AE 500ML*12 L221

(Contd. of page 2)

· **After inhalation:**
In case of unconsciousness place patient stably in side position for transportation.
· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
· **After eye contact:** Rinse opened eye for several minutes under running water.
· **After swallowing:** If symptoms persist consult doctor.
· **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**
· **Suitable extinguishing agents:**
CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
· **Special hazards arising from the substance or mixture**
No further relevant information available.
· **Advice for firefighters**
· **Protective equipment:** No special measures required.

*

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
· **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
· **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
· **Protective Action Criteria for Chemicals**

· **PAC-1:**		
115-10-6	dimethyl ether	3,000 ppm
	Hydrocarbons, C6, isoalkanes, <5% n-hexane	1,000 mg/m³
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	1,000 mg/m³
110-82-7	cyclohexane	800 ppm
108-87-2	Methylcyclohexane	400 ppm
110-54-3	n-hexane	400 ppm
122-39-4	diphenylamine	6.0 mg/m3

· **PAC-2:**		
115-10-6	dimethyl ether	3800* ppm

(Contd. on page 4)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/16/2026 Reviewed on 07/16/2026

Trade name: GRF SPRAY ADHESIVE AE 500ML*12 L221

(Contd. of page 3)

	Hydrocarbons, C6, isoalkanes, <5% n-hexane	11,000 mg/m³
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	11,000 mg/m³
110-82-7	cyclohexane	1700 ppm
108-87-2	Methylcyclohexane	1700 ppm
110-54-3	n-hexane	2900 ppm
122-39-4	diphenylamine	37 mg/m3

· **PAC-3:**		
115-10-6	dimethyl ether	7200* ppm
	Hydrocarbons, C6, isoalkanes, <5% n-hexane	66,000 mg/m³
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	66,000 mg/m³
110-82-7	cyclohexane	10000 ppm
108-87-2	Methylcyclohexane	10000 ppm
110-54-3	n-hexane	8600 ppm
122-39-4	diphenylamine	220 mg/m3

7 Handling and storage

· **Handling:**
· **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
· **Information about protection against explosions and fires:**
Do not spray on a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· **Conditions for safe storage, including any incompatibilities**
· **Storage:**
· **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurized containers.
· **Information about storage in one common storage facility:** Not required
· **Further information about storage conditions:** Keep receptacle tightly sealed.
· **Storage class:** 2 B
· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see section 7.

· **Control parameters**
· **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

115-10-6 dimethyl ether	
WEEL	Long-term value: 1000 ppm

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/16/2026 Reviewed on 07/16/2026

Trade name: GRF SPRAY ADHESIVE AE 500ML*12 L221

(Contd. of page 4)

110-82-7 cyclohexane	
PEL	Long-term value: 1050 mg/m³, 300 ppm
REL	Long-term value: 1050 mg/m³, 300 ppm
TLV	Long-term value: 100 ppm BEI
108-87-2 Methylcyclohexane	
PEL	Long-term value: 2000 mg/m³, 500 ppm
REL	Long-term value: 1600 mg/m³, 400 ppm
TLV	Long-term value: 100 ppm
110-54-3 n-hexane	
PEL	Long-term value: 1800 mg/m³, 500 ppm
REL	Long-term value: 180 mg/m³, 50 ppm
TLV	Long-term value: 176 mg/m³, 50 ppm Skin; BEI
128-37-0 Butylated hydroxytoluene	
REL	Long-term value: 10 mg/m³
TLV	Long-term value: 2* mg/m³ *as inhalable fraction and vapor, A4

· **Ingredients with biological limit values:**

110-82-7 cyclohexane	
BEI	50 mg/g creatinine Medium: - Time: End of shift, end of working week Parameter: 1.2-Cyclohexanediol (non-specific, with hydrolysis)
110-54-3 n-hexane	
BEI	0.5 mg/L Medium: urine Time: end of shift Parameter: 2.5-Hexanedione without hydrolysis

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**
· **Personal protective equipment:**
· **General protective and hygienic measures:**
The usual precautionary measures for handling chemicals should be followed.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the skin.
Avoid contact with the eyes and skin.
· **Breathing equipment:**
Use suitable respiratory protective device in case of insufficient ventilation.
· **Recommended filter device for short term use:** Filter A

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/16/2026 Reviewed on 07/16/2026

Trade name: GRF SPRAY ADHESIVE AE 500ML*12 L221

(Contd. of page 5)

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**
Recommended thickness of the material: > 0,12 mm
Nitrile rubber, NBR

· **Penetration time of glove material**
For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

· **Eye protection:** Not required

· **Body protection:** Use protective suit.

*

9 Physical and chemical properties

· **Information on basic physical and chemical properties**	
· **General Information**	
· **Appearance:**	
Form:	Aerosol
Color:	According to product specification
· **Odor:**	Characteristic
· **Odor threshold:**	Not determined
· **pH-value:**	Mixture is a gas.
· **Change in condition**	
Melting point/Melting range:	Undetermined
Boiling point/Boiling range:	-24.9 °C (-12.8 °F)
· **Flash point:**	-42 °C (-43.6 °F)
· **Flammability:**	Not applicable
· **Auto igniting:**	235 °C (455 °F)
· **Decomposition temperature:**	Not determined
· **Ignition temperature:**	Product is not selfigniting.
· **Danger of explosion:**	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· **Explosion limits:**	
Lower:	0.7 Vol %
Upper:	18.6 Vol %
· **Vapor pressure at 20 °C (68 °F):**	5200 hPa (3900.3 mm Hg)

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/16/2026 Reviewed on 07/16/2026

Trade name: GRF SPRAY ADHESIVE AE 500ML*12 L221

(Contd. of page 6)

· **Density at 20 °C (68 °F):**	0.75 g/cm³ (6.259 lbs/gal)
· **Relative density**	Not determined
· **Vapor density**	Not determined
· **Evaporation rate**	Not applicable.
· **Solubility in / Miscibility with**	
Water:	Not miscible or difficult to mix.
· **Partition coefficient (n-octanol/water):**	Not determined
· **Viscosity:**	
Dynamic:	Not determined
Kinematic:	Not determined
· **Solvent content:**	
Organic solvents:	86.1 %
VOC content:	86.11 % 645.8 g/l / 5.39 lb/gal
Solids content:	13.5 %
· **Other information**	All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.

10 Stability and reactivity

· **Reactivity** No further relevant information available.
· **Chemical stability**
· **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
· **Possibility of hazardous reactions** No dangerous reactions known.
· **Conditions to avoid** No further relevant information available.
· **Incompatible materials:** No further relevant information available.
· **Hazardous decomposition products:** Danger of toxic pyrolysis products.

11 Toxicological information

· **Information on toxicological effects**
· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**		
115-10-6 dimethyl ether		
Inhalative	LC50/4 h	308 mg/l (rat)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics		
Oral	LD50	>5840 mg/kg (rat)
Dermal	LD50	>2920 mg/kg (rat)
Inhalative	LC50/4 h	>23.3 mg/l (rat)

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/16/2026 Reviewed on 07/16/2026

Trade name: GRF SPRAY ADHESIVE AE 500ML*12 L221

(Contd. of page 7)

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane		
Oral	LD50	>3350 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50/4 h	>20 mg/l (rat)
Hydrocarbons, C6, isoalkanes, <5% n-hexane		
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>3000 mg/kg (rat)
Inhalative	LC50/4 h	>20 mg/l (rat)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50/4 h	>20 mg/l (rat)
110-82-7 cyclohexane		
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4 h	32.88 mg/l (rat)
108-87-2 Methylcyclohexane		
Oral	LD50	4000-4500 mg/kg (rabbit)
Dermal	LD50	>2000 mg/kg (rabbit)
110-54-3 n-hexane		
Oral	LD50	16000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50/4 h	172 mg/l (rat)
128-37-0 Butylated hydroxytoluene		
Oral	LD50	>2930 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)

· **Primary irritant effect:**
· **on the skin:** Irritant to skin and mucous membranes.
· **on the eye:** No irritating effect.
· **Sensitization:** No sensitizing effects known.
· **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**		
9003-55-8	1,3 Butadiene/styrene copolymer	3
128-37-0	Butylated hydroxytoluene	3
122-39-4	diphenylamine	2B

· **NTP (National Toxicology Program)**
None of the ingredients is listed.

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/16/2026 Reviewed on 07/16/2026

Trade name: GRF SPRAY ADHESIVE AE 500ML*12 L221

(Contd. of page 8)

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

· **Germ cell mutagenicity** Not applicable

12 Ecological information

· **Toxicity**
· **Aquatic toxicity:** No further relevant information available.
· **Persistence and degradability** No further relevant information available.
· **Behavior in environmental systems:**
· **Bioaccumulative potential** No further relevant information available.
· **Mobility in soil** No further relevant information available.
· **Additional ecological information:**
· **General notes:**
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable
· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**
· **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
Disposal must be made according to official regulations.

· **Uncleaned packagings:**
· **Recommendation:**
Packagings that cannot be cleansed are to be disposed of in the same manner as the product.

14 Transport information

· **UN-Number**	
· **DOT, ADR/ADN, IMDG, IATA**	UN1950
· **UN proper shipping name**	
· **DOT**	Aerosols, flammable
· **ADR/ADN**	1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
· **IMDG**	AEROSOLS, MARINE POLLUTANT
· **IATA**	AEROSOLS, flammable

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS


Printing date 07/16/2026 Reviewed on 07/16/2026

Trade name: GRF SPRAY ADHESIVE AE 500ML*12 L221

(Contd. of page 9)

· **Transport hazard class(es)**

· **DOT**



· **Class**	2.1 Gases
· **Label**	2.1

· **ADR/ADN**



· **Class**	2 5F Gases
· **Label**	2.1

· **IMDG**



· **Class**	2.1 Gases
· **Label**	2.1

· **IATA**



· **Class**	2.1 Gases
· **Label**	2.1

· **Packing group**	
· **DOT, ADR/ADN, IMDG, IATA**	not regulated

· **Environmental hazards:**	Product contains environmentally hazardous substances: Naphtha (petroleum), hydrotreated light
· **Marine pollutant:**	Yes Symbol (fish and tree)
· **Special marking (ADR/ADN):**	Symbol (fish and tree)

· **Special precautions for user**	Warning: Gases
· **Hazard identification number (Kemler code):**	-
· **EMS Number:**	F-D,S-U
· **Stowage Code**	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE

(Contd. on page 11)

US

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/16/2026 Reviewed on 07/16/2026

Trade name: GRF SPRAY ADHESIVE AE 500ML*12 L221

(Contd. of page 10)

·	AEROSOLS: Category C, Clear of living quarters.
· **Segregation Code**	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**	Not applicable
· **Transport/Additional information:**	
· **DOT**	
· **Quantity limitations**	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg
· **Remarks:**	Special marking with the symbol (fish and tree).
· **ADR/ADN**	
· **Excepted quantities (EQ)**	Code: E0 Not permitted as Excepted Quantity
· **IMDG**	
· **Limited quantities (LQ)**	1L
· **Excepted quantities (EQ)**	Code: E0 Not permitted as Excepted Quantity
· **UN "Model Regulation":**	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
· **Sara**

· **Section 355 (extremely hazardous substances):**
None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

110-82-7	cyclohexane
110-54-3	n-hexane
122-39-4	diphenylamine

· **TSCA (Toxic Substances Control Act):**
None

115-10-6	dimethyl ether	ACTIVE

(Contd. on page 12)

US

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/16/2026 Reviewed on 07/16/2026

Trade name: GRF SPRAY ADHESIVE AE 500ML*12 L221

(Contd. of page 11)

64365-17-9	Resin acids and Rosin acids, hydrogenated, esters with pentaerythritol	ACTIVE
9003-55-8	1,3 Butadiene/styrene copolymer	ACTIVE
	Hydrocarbons, C6, isoalkanes, <5% n-hexane	ACTIVE
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	ACTIVE
110-82-7	cyclohexane	ACTIVE
108-87-2	Methylcyclohexane	ACTIVE
110-54-3	n-hexane	ACTIVE
128-37-0	Butylated hydroxytoluene	ACTIVE
68442-68-2	benzenamine, N-phenyl-, styrenated	ACTIVE
122-39-4	diphenylamine	ACTIVE

· **Hazardous Air Pollutants**

110-54-3	n-hexane

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

110-54-3	n-hexane

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

110-82-7	cyclohexane	I
110-54-3	n-hexane	II

· **TLV (Threshold Limit Value)**

128-37-0	Butylated hydroxytoluene	A4
122-39-4	diphenylamine	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

(Contd. on page 13)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/16/2026 Reviewed on 07/16/2026

Trade name: GRF SPRAY ADHESIVE AE 500ML*12 L221

(Contd. of page 12)

n-hexane
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane
Hydrocarbons, C6, isoalkanes, <5% n-hexane

· **Hazard statements**
H222 Extremely flammable aerosol.
H315 Causes skin irritation.
H361 Suspected of damaging fertility or the unborn child.
H336 May cause drowsiness or dizziness.

· **Precautionary statements**
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P261 Avoid breathing spray.
P302+P352 If on skin: Wash with plenty of soap and water.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501 Dispose of contents/container in accordance with national regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** PSRA
· **Contact:** PSRA
· **Date of preparation / last revision** 07/16/2026 / 47
· **Abbreviations and acronyms:**
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Aerosols 1: Aerosols – Category 1
Skin Irritation 2: Skin corrosion/irritation – Category 2
Toxic to Reproduction 2: Reproductive toxicity – Category 2
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

· *** Data compared to the previous version altered.**

US