Safety Data Sheet
acc. to OSHA HCS

Printing date 07/14/2026 Reviewed on 07/14/2026

1 Identification

· **Product identifier**

· **Trade name:** GRF WOOD MAX POWER CQ 380G*12 L221
· **Application of the substance / the mixture** Adhesive

· **Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**
Bison International
Dr.A.F.Philipsstraat 9
NL-4462 EW Goes
PO Box 160
NL-4460 AD Goes
tel. +31 88 3235700
fax. +31 88 3235800
e mail: sds@boltonadhesives.com

· **Information department:** PSRA
· **Emergency telephone number:**
Bison and Griffon products: +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET)
UHU products: + 49 (0) 30/19240 (Notruf). Operating hours mo-fr 08:00h-17:00h (CET)

For detailed information contact the national Poison Centre @
https://poisoncentres.echa.europa.eu/appointed-bodies

2 Hazard(s) identification

· **Classification of the substance or mixture**

Specific Target Organ Toxicity - Repeated Exposure 2	H373 May cause damage to organs through prolonged or repeated exposure.


· **Label elements**
· **Hazard pictograms**



GHS08

· **Signal word** Warning

· **Hazard-determining components of labeling:**
Trimethoxyphenylsilane
· **Hazard statements**
H373 May cause damage to organs through prolonged or repeated exposure.
· **Precautionary statements**
P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P314 Get medical advice/attention if you feel unwell.
· **Classification system:**
· **NFPA ratings (scale 0 - 4)**



Health = 0
Fire = 0
Reactivity = 0

(Contd. on page 2)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/14/2026 Reviewed on 07/14/2026

Trade name: GRF WOOD MAX POWER CQ 380G*12 L221

(Contd. of page 1)

· **HMIS-ratings (scale 0 - 4)**



Health = *0
Fire = 0
Reactivity = 0

· **Other hazards** During curing methanol (CAS 67-56-1) is produced.
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**
· **Description:** Adhesive

· **Dangerous components:**

2996-92-1	Trimethoxyphenylsilane	1-2.5%
2768-02-7	trimethoxyvinylsilane	≥0.1-<1%
52829-07-9	bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	≥0.1-<1%

4 First-aid measures

· **Description of first aid measures**
· **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
· **After inhalation:**
Supply fresh air; consult doctor in case of complaints.
No special measures required.
· **After skin contact:** Generally the product does not irritate the skin.
· **After eye contact:** Rinse opened eye for several minutes under running water.
· **After swallowing:** If symptoms persist consult doctor.
· **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**
· **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
· **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.

(Contd. on page 3)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/14/2026 Reviewed on 07/14/2026

Trade name: GRF WOOD MAX POWER CQ 380G*12 L221

(Contd. of page 2)

· **Advice for firefighters**
· **Protective equipment:** Mouth respiratory protective device.

*
6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
· **Methods and material for containment and cleaning up:**
Send for recovery or disposal in suitable receptacles.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
· **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
· **Protective Action Criteria for Chemicals**

· **PAC-1:**		
2996-92-1	Trimethoxyphenylsilane	0.59 mg/m3
2768-02-7	trimethoxyvinylsilane	10 ppm
13822-56-5	3-(trimethoxysilyl)propylamine	9.0 mg/m3
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	3.4 mg/m3
67-56-1	Methanol	530 ppm

· **PAC-2:**		
2996-92-1	Trimethoxyphenylsilane	6.5 mg/m3
2768-02-7	trimethoxyvinylsilane	20 ppm
13822-56-5	3-(trimethoxysilyl)propylamine	99 mg/m3
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	38 mg/m3
67-56-1	Methanol	2100 ppm

· **PAC-3:**		
2996-92-1	Trimethoxyphenylsilane	39 mg/m3
2768-02-7	trimethoxyvinylsilane	120 ppm
13822-56-5	3-(trimethoxysilyl)propylamine	600 mg/m3
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	230 mg/m3
67-56-1	Methanol	7200 ppm

7 Handling and storage

· **Handling:**
· **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.

(Contd. on page 4)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/14/2026 Reviewed on 07/14/2026

Trade name: GRF WOOD MAX POWER CQ 380G*12 L221

(Contd. of page 3)

· **Information about protection against explosions and fires:**
Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**
· **Storage:**
· **Requirements to be met by storerooms and receptacles:** No special requirements.
· **Information about storage in one common storage facility:** Not required
· **Further information about storage conditions:** None.
· **Storage class:** 12
· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see section 7.

· **Control parameters**
· **Components with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**
· **Personal protective equipment:**
· **General protective and hygienic measures:**
The usual precautionary measures for handling chemicals should be followed.
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
· **Breathing equipment:** Not necessary if room is well-ventilated.
· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
· **Material of gloves**
Recommended thickness of the material: > 0,12 mm
Nitrile rubber, NBR
· **Penetration time of glove material**
For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).
· **Eye protection:**



Tightly sealed goggles

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/14/2026 Reviewed on 07/14/2026

Trade name: GRF WOOD MAX POWER CQ 380G*12 L221

(Contd. of page 4)

Goggles recommended during refilling.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**	
· **General Information**	
· **Appearance:**	
Form:	Fluid
Color:	According to product specification
· **Odor:**	Characteristic
· **Odor threshold:**	Not determined
· **pH-value:**	Not determined
· **Change in condition**	
Melting point/Melting range:	Undetermined
Boiling point/Boiling range:	2230 °C (4046 °F)
· **Flash point:**	Not applicable
· **Flammability:**	Not applicable
· **Decomposition temperature:**	Not determined
· **Ignition temperature:**	Product is not selfigniting.
· **Danger of explosion:**	Product does not present an explosion hazard.
· **Explosion limits:**	
Lower:	Not determined
Upper:	Not determined
· **Vapor pressure:**	Not determined
· **Density:**	Not determined
· **Relative density**	Not determined
· **Vapor density**	Not determined
· **Evaporation rate**	Not determined
· **Solubility in / Miscibility with**	
Water:	Not miscible or difficult to mix.
· **Partition coefficient (n-octanol/water):**	Not determined
· **Viscosity:**	
Dynamic:	Not determined
Kinematic:	Not determined
· **Solvent content:**	
Organic solvents:	0.0 %
VOC content:	0.00 %
Solids content:	94.6 %

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/14/2026 Reviewed on 07/14/2026

Trade name: GRF WOOD MAX POWER CQ 380G*12 L221

(Contd. of page 5)

· **Other information** All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.

10 Stability and reactivity

· **Reactivity** No further relevant information available.
· **Chemical stability**
· **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
· **Possibility of hazardous reactions** No dangerous reactions known.
· **Conditions to avoid** No further relevant information available.
· **Incompatible materials:** No further relevant information available.
· **Hazardous decomposition products:** Possible in traces.
· **Additional information:** During curing methanol (CAS 67-56-1) is produced.

11 Toxicological information

· **Information on toxicological effects**
· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**		
2996-92-1 Trimethoxyphenylsilane		
Oral	LD50	1049 mg/kg (rat)
Dermal	LD50	3014 mg/kg (rat)
2768-02-7 trimethoxyvinylsilane		
Oral	LD50	6899 mg/kg (rat)
Dermal	LD50	3158 mg/kg (rabbit)
Inhalative	LC50/4 h	16.8 mg/l (rat)
52829-07-9 bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate		
Oral	LD50	3700 mg/kg (rat)
Dermal	LD50	>3170 mg/kg (rat)
Inhalative	LC50/4 h	7.7 mg/l (rat)

· **Primary irritant effect:**
· **on the skin:** No irritant effect.
· **on the eye:** No irritating effect.
· **Sensitization:** No sensitizing effects known.
· **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**
None of the ingredients is listed.

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/14/2026 Reviewed on 07/14/2026

Trade name: GRF WOOD MAX POWER CQ 380G*12 L221

(Contd. of page 6)

· **NTP (National Toxicology Program)**
None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**
None of the ingredients is listed.

· **Germ cell mutagenicity** Not applicable

12 Ecological information

· **Toxicity**
· **Aquatic toxicity:** No further relevant information available.
· **Persistence and degradability** No further relevant information available.
· **Behavior in environmental systems:**
· **Bioaccumulative potential** No further relevant information available.
· **Mobility in soil** No further relevant information available.
· **Additional ecological information:**
· **General notes:**
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable
· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**
· **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
Disposal must be made according to official regulations.

· **Uncleaned packagings:**
· **Recommendation:**
Packagings that cannot be cleansed are to be disposed of in the same manner as the product.

14 Transport information

· **UN-Number**	
· **DOT, ADN**	not regulated
· **ADR/ADN, IMDG, IATA**	not regulated
	-
· **UN proper shipping name**	
· **DOT, ADR/ADN, ADN, IMDG, IATA**	not regulated

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/14/2026 Reviewed on 07/14/2026

Trade name: GRF WOOD MAX POWER CQ 380G*12 L221

(Contd. of page 7)

· **Transport hazard class(es)**	
· **DOT, ADR/ADN, ADN, IMDG, IATA**	
· **Class**	not regulated
· **Packing group**	
· **DOT, ADR/ADN, IMDG, IATA**	not regulated
· **Environmental hazards:**	
· **Marine pollutant:**	No
· **Special precautions for user**	Not applicable
· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**	Not applicable
· **Transport/Additional information:**	Not dangerous according to the above specifications.
· **UN "Model Regulation":**	not regulated

*
15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

67-56-1	Methanol

· **TSCA (Toxic Substances Control Act):**

611222-18-5	Dimethoxy(methyl)silylmethylcarbamate-terminated polyether	ACTIVE
3445-11-2	N-(2-Hydroxyethyl)-2-pyrrolidone	ACTIVE
2996-92-1	Trimethoxyphenylsilane	ACTIVE
2768-02-7	trimethoxyvinylsilane	ACTIVE
13822-56-5	3-(trimethoxysilyl)propylamine	ACTIVE
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	ACTIVE
68441-17-8	Oxydised polyethylene wax	ACTIVE
52829-07-9	bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	ACTIVE
67-56-1	Methanol	ACTIVE

· **Hazardous Air Pollutants**

67-56-1	Methanol

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

(Contd. on page 9)

US

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/14/2026 Reviewed on 07/14/2026

Trade name: GRF WOOD MAX POWER CQ 380G*12 L221

(Contd. of page 8)

· **Chemicals known to cause reproductive toxicity for females:**
None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**
None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

67-56-1	Methanol

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**
None of the ingredients is listed.

· **TLV (Threshold Limit Value)**
None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**
None of the ingredients is listed.

· **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
· **Hazard pictograms**



GHS08

· **Signal word** Warning

· **Hazard-determining components of labeling:**
Trimethoxyphenylsilane
· **Hazard statements**
H373 May cause damage to organs through prolonged or repeated exposure.
· **Precautionary statements**
P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P314 Get medical advice/attention if you feel unwell.
· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** PSRA
· **Contact:** PSRA
· **Date of preparation / last revision** 07/14/2026 / 37
· **Abbreviations and acronyms:**
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/14/2026 Reviewed on 07/14/2026

Trade name: GRF WOOD MAX POWER CQ 380G*12 L221

(Contd. of page 9)

ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2
· *** Data compared to the previous version altered.**

US