Safety Data Sheet
acc. to OSHA HCS

Printing date 07/14/2026 Reviewed on 07/14/2026

1 Identification

· **Product identifier**

· **Trade name:** GRF CLEANER TI 5L*1 L221
· **Application of the substance / the mixture**
Thinner, Diluent
Cleaning agent/ Cleaner

· **Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**
Bison International
Dr.A.F.Philipsstraat 9
NL-4462 EW Goes
PO Box 160
NL-4460 AD Goes
tel. +31 88 3235700
fax. +31 88 3235800
e mail: sds@boltonadhesives.com

· **Information department:** PSRA
· **Emergency telephone number:**
Bison and Griffon products: +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET)
UHU products: + 49 (0) 30/19240 (Notruf). Operating hours mo-fr 08:00h-17:00h (CET)

For detailed information contact the national Poison Centre @
https://poisoncentres.echa.europa.eu/appointed-bodies

*
2 Hazard(s) identification

· **Classification of the substance or mixture**

Flammable Liquids 2	H225 Highly flammable liquid and vapor.
Skin Irritation 2	H315 Causes skin irritation.
Eye Irritation 2A	H319 Causes serious eye irritation.
Toxic to Reproduction 2	H361 Suspected of damaging fertility or the unborn child.
Specific Target Organ Toxicity - Single Exposure 3	H336 May cause drowsiness or dizziness.
Specific Target Organ Toxicity - Repeated Exposure 1	H372 Causes damage to the nervous system through prolonged or repeated exposure.
Aspiration Hazard 1	H304 May be fatal if swallowed and enters airways.

· **Label elements**
· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

(Contd. on page 2)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/14/2026 Reviewed on 07/14/2026

Trade name: GRF CLEANER TI 5L*1 L221

(Contd. of page 1)

· **Hazard-determining components of labeling:**
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane
n-hexane
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics
Ethyl acetate
· **Hazard statements**
H225 Highly flammable liquid and vapor.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H361 Suspected of damaging fertility or the unborn child.
H336 May cause drowsiness or dizziness.
H372 Causes damage to the nervous system through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.
· **Precautionary statements**
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P261 Avoid breathing vapours.
P301+P310 If swallowed: Immediately call a poison center/doctor.
P331 Do NOT induce vomiting.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P501 Dispose of contents/container in accordance with national regulations.
· **Classification system:**
· **NFPA ratings (scale 0 - 4)**



Health = 2
Fire = 3
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 2
Fire = 3
Reactivity = 0

· **Other hazards**
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**
· **Description:** Cleansing agent

· **Dangerous components:**		
	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	25-50%
141-78-6	Ethyl acetate	10-25%
	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	10-25%
78-93-3	Butanone	10-25%
110-54-3	n-hexane	1-2.5%

(Contd. on page 3)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/14/2026 Reviewed on 07/14/2026

Trade name: GRF CLEANER TI 5L*1 L221

(Contd. of page 2)

110-82-7	cyclohexane	<1%

*
4 First-aid measures

· **Description of first aid measures**
· **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
· **After inhalation:**
In case of unconsciousness place patient stably in side position for transportation.
· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
· **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
· **After swallowing:** If symptoms persist consult doctor.
· **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**
· **Suitable extinguishing agents:**
Water haze
Alcohol resistant foam
Fire-extinguishing powder
Carbon dioxide
· **For safety reasons unsuitable extinguishing agents:** Water with full jet
· **Special hazards arising from the substance or mixture**
No further relevant information available.
· **Advice for firefighters**
· **Protective equipment:** No special measures required.
· **Additional information**
Cool endangered receptacles with water spray.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

*
6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
· **Methods and material for containment and cleaning up:**
Send for recovery or disposal in suitable receptacles.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.

(Contd. on page 4)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/14/2026 Reviewed on 07/14/2026

Trade name: GRF CLEANER TI 5L*1 L221

(Contd. of page 3)

· **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
· **Protective Action Criteria for Chemicals**

· **PAC-1:**		
141-78-6	Ethyl acetate	1200 ppm
78-93-3	Butanone	200 ppm
110-54-3	n-hexane	400 ppm
110-82-7	cyclohexane	800 ppm

· **PAC-2:**		
141-78-6	Ethyl acetate	1700 ppm
78-93-3	Butanone	2700 ppm
110-54-3	n-hexane	2900 ppm
110-82-7	cyclohexane	1700 ppm

· **PAC-3:**		
141-78-6	Ethyl acetate	10000 ppm
78-93-3	Butanone	4000 ppm
110-54-3	n-hexane	8600 ppm
110-82-7	cyclohexane	10000 ppm

7 Handling and storage

· **Handling:**
· **Precautions for safe handling**
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
· **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

· **Conditions for safe storage, including any incompatibilities**
· **Storage:**
· **Requirements to be met by storerooms and receptacles:** Store in a cool location.
· **Information about storage in one common storage facility:** Not required
· **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
· **Storage class:** 3
· **Specific end use(s)** No further relevant information available.

US

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/14/2026 Reviewed on 07/14/2026

Trade name: GRF CLEANER TI 5L*1 L221

(Contd. of page 4)

*
8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see section 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

141-78-6 Ethyl acetate	
PEL	Long-term value: 1400 mg/m³, 400 ppm
REL	Long-term value: 1400 mg/m³, 400 ppm
TLV	Short-term value: 200 ppm Long-term value: 100 ppm
78-93-3 Butanone	
PEL	Long-term value: 590 mg/m³, 200 ppm
REL	Short-term value: 885 mg/m³, 300 ppm Long-term value: 590 mg/m³, 200 ppm
TLV	Short-term value: 150 ppm Long-term value: 75 ppm BEI, Skin
110-54-3 n-hexane	
PEL	Long-term value: 1800 mg/m³, 500 ppm
REL	Long-term value: 180 mg/m³, 50 ppm
TLV	Long-term value: 176 mg/m³, 50 ppm Skin; BEI
110-82-7 cyclohexane	
PEL	Long-term value: 1050 mg/m³, 300 ppm
REL	Long-term value: 1050 mg/m³, 300 ppm
TLV	Long-term value: 100 ppm BEI

· **Ingredients with biological limit values:**	
78-93-3 Butanone	
BEI	2 mg/L Medium: urine Time: end of shift Parameter: Methyl ethyl ketone (nonspecific)
110-54-3 n-hexane	
BEI	0.5 mg/L Medium: urine Time: end of shift Parameter: 2.5-Hexanedione without hydrolysis

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/14/2026 Reviewed on 07/14/2026

Trade name: GRF CLEANER TI 5L*1 L221

(Contd. of page 5)

110-82-7 cyclohexane	
BEI	50 mg/g creatinine Medium: - Time: End of shift, end of working week Parameter: 1.2-Cyclohexanediol (non-specific, with hydrolysis)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**
· **Personal protective equipment:**
· **General protective and hygienic measures:**
The usual precautionary measures for handling chemicals should be followed.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.
· **Breathing equipment:**
Use suitable respiratory protective device in case of insufficient ventilation.
· **Recommended filter device for short term use:** Filter A
· **Protection of hands:**
Solvent resistant gloves


Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
· **Material of gloves**
Recommended thickness of the material: > 0,12 mm
Butyl rubber, BR
Nitrile rubber, NBR
Recommended thickness of the material: > 0,7 mm
· **Penetration time of glove material**
For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).
For the mixture of chemicals mentioned below the penetration time has to be at least 120 minutes (Permeation according to EN 374 Part 3: Level 4).
· **Eye protection:**


Tightly sealed goggles

Goggles recommended during refilling.
· **Body protection:**
Use protective suit.

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/14/2026 Reviewed on 07/14/2026

Trade name: GRF CLEANER TI 5L*1 L221

(Contd. of page 6)

Solvent resistant protective clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**	
· **General Information**	
· **Appearance:**	
Form:	Fluid
Color:	According to product specification
· **Odor:**	Characteristic
· **Odor threshold:**	Not determined
· **pH-value:**	Not determined
· **Change in condition**	
Melting point/Melting range:	Undetermined
Boiling point/Boiling range:	60 °C (140 °F)
· **Flash point:**	-9 °C (15.8 °F)
· **Flammability:**	Highly flammable.
· **Auto igniting:**	450 °C (842 °F)
· **Decomposition temperature:**	Not determined
· **Ignition temperature:**	Product is not selfigniting.
· **Danger of explosion:**	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· **Explosion limits:**	
Lower:	0.7 Vol %
Upper:	11.5 Vol %
· **Vapor pressure at 20 °C (68 °F):**	105 hPa (78.8 mm Hg)
· **Vapor pressure at 50 °C (122 °F):**	360 hPa (270 mm Hg)
· **Density at 20 °C (68 °F):**	0.79 g/cm³ (6.593 lbs/gal)
· **Relative density**	Not determined
· **Vapor density**	Not determined
· **Evaporation rate**	Not determined
· **Solubility in / Miscibility with**	
Water:	Not miscible or difficult to mix.
· **Partition coefficient (n-octanol/water):**	Not determined
· **Viscosity:**	
Dynamic at 20 °C (68 °F):	5 mPas
Kinematic:	Not determined
· **Solvent content:**	
Organic solvents:	100.0 %
VOC content:	100.00 %

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/14/2026 Reviewed on 07/14/2026

Trade name: GRF CLEANER TI 5L*1 L221

(Contd. of page 7)

Solids content:	0.0 %
· **Other information**	All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.

10 Stability and reactivity

· **Reactivity** No further relevant information available.
· **Chemical stability**
· **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
· **Possibility of hazardous reactions** No dangerous reactions known.
· **Conditions to avoid** No further relevant information available.
· **Incompatible materials:** No further relevant information available.
· **Hazardous decomposition products:** Danger of toxic pyrolysis products.

11 Toxicological information

· **Information on toxicological effects**
· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**		
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane		
Oral	LD50	>3350 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50/4 h	>20 mg/l (rat)
141-78-6 Ethyl acetate		
Oral	LD50	4934 mg/kg (rabbit)
Dermal	LD50	>20000 mg/kg (rabbit)
Inhalative	LC50/4 h	29.3 mg/l (rat)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics		
Oral	LD50	>5840 mg/kg (rat)
Dermal	LD50	>2920 mg/kg (rat)
Inhalative	LC50/4 h	>23.3 mg/l (rat)
78-93-3 Butanone		
Oral	LD50	>2193 mg/kg (rat)
Dermal	LD50	>8050 mg/kg (rat)
110-54-3 n-hexane		
Oral	LD50	16000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50/4 h	172 mg/l (rat)

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/14/2026 Reviewed on 07/14/2026

Trade name: GRF CLEANER TI 5L*1 L221

(Contd. of page 8)

110-82-7 cyclohexane		
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4 h	32.88 mg/l (rat)

· **Primary irritant effect:**
· **on the skin:** Irritant to skin and mucous membranes.
· **on the eye:** Irritating effect.
· **Sensitization:** No sensitizing effects known.
· **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**
None of the ingredients is listed.

· **NTP (National Toxicology Program)**
None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**
None of the ingredients is listed.

· **Germ cell mutagenicity** Not applicable

12 Ecological information

· **Toxicity**
· **Aquatic toxicity:** No further relevant information available.
· **Persistence and degradability** No further relevant information available.
· **Behavior in environmental systems:**
· **Bioaccumulative potential** No further relevant information available.
· **Mobility in soil** No further relevant information available.
· **Additional ecological information:**
· **General notes:**
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable
· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**
· **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/14/2026 Reviewed on 07/14/2026

Trade name: GRF CLEANER TI 5L*1 L221

(Contd. of page 9)

Disposal must be made according to official regulations.

· **Uncleaned packagings:**
· **Recommendation:**
Packagings that cannot be cleansed are to be disposed of in the same manner as the product.

14 Transport information

· **UN-Number**	
· **DOT, ADR/ADN, IMDG, IATA**	UN1993
· **UN proper shipping name**	
· **DOT**	Flammable liquids, n.o.s. (Naphtha (petroleum), hydrotreated light, Ethyl acetate)
· **ADR/ADN**	1993 FLAMMABLE LIQUID, N.O.S. (Naphtha (petroleum), hydrotreated light, ETHYL ACETATE), ENVIRONMENTALLY HAZARDOUS, special provision 640D
· **IMDG**	FLAMMABLE LIQUID, N.O.S. (Naphtha (petroleum), hydrotreated light, ETHYL ACETATE), MARINE POLLUTANT
· **IATA**	FLAMMABLE LIQUID, N.O.S. (Naphtha (petroleum), hydrotreated light, ETHYL ACETATE)
· **Transport hazard class(es)**	
· **DOT**	



· **Class**	3 Flammable liquids
· **Label**	3
· **ADR/ADN**	



· **Class**	3 (F1) Flammable liquids
· **Label**	3
· **IMDG**	



· **Class**	3 Flammable liquids

(Contd. on page 11)

US

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/14/2026 Reviewed on 07/14/2026

Trade name: GRF CLEANER TI 5L*1 L221

(Contd. of page 10)

· **Label**	3
· **IATA**	
	
· **Class**	3 Flammable liquids
· **Label**	3
· **Packing group**	
· **DOT, ADR/ADN, IMDG, IATA**	II
· **Environmental hazards:**	Product contains environmentally hazardous substances: Naphtha (petroleum), hydrotreated light
· **Marine pollutant:**	Yes Symbol (fish and tree)
· **Special marking (ADR/ADN):**	Symbol (fish and tree)
· **Special precautions for user**	Warning: Flammable liquids
· **Hazard identification number (Kemler code):**	33
· **EMS Number:**	F-E,S-E
· **Stowage Category**	B
· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**	Not applicable
· **Transport/Additional information:**	
· **DOT**	
· **Quantity limitations**	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· **Remarks:**	Special marking with the symbol (fish and tree).
· **ADR/ADN**	
· **Excepted quantities (EQ)**	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· **IMDG**	
· **Limited quantities (LQ)**	1L
· **Excepted quantities (EQ)**	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· **Remarks:**	For substances with class 3 according to IMDG-Code chapter 2.3.2.2 packing group is classified in packing group III, as viscosity is in accordance with requirements (flow time t > 100s).
· **UN "Model Regulation":**	UN 1993 FLAMMABLE LIQUID, N.O.S. (NAPHTHA (PETROLEUM), HYDROTREATED LIGHT, ETHYL ACETATE), 3, II,

(Contd. on page 12)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/14/2026 Reviewed on 07/14/2026

Trade name: GRF CLEANER TI 5L*1 L221

(Contd. of page 11)

· ENVIRONMENTALLY HAZARDOUS

*
15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
· **Sara**

· **Section 355 (extremely hazardous substances):**
None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

110-54-3	n-hexane
110-82-7	cyclohexane

· **TSCA (Toxic Substances Control Act):**

141-78-6	Ethyl acetate	ACTIVE
78-93-3	Butanone	ACTIVE
110-54-3	n-hexane	ACTIVE
110-82-7	cyclohexane	ACTIVE

· **Hazardous Air Pollutants**

110-54-3	n-hexane

· **Proposition 65**

· **Chemicals known to cause cancer:**
None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**
None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

110-54-3	n-hexane

· **Chemicals known to cause developmental toxicity:**
None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

78-93-3	Butanone	I
110-54-3	n-hexane	II
110-82-7	cyclohexane	I

· **TLV (Threshold Limit Value)**
None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**
None of the ingredients is listed.

· **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 13)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/14/2026 Reviewed on 07/14/2026

Trade name: GRF CLEANER TI 5L*1 L221

(Contd. of page 12)

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane
n-hexane
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics
Ethyl acetate

· **Hazard statements**
H225 Highly flammable liquid and vapor.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H361 Suspected of damaging fertility or the unborn child.
H336 May cause drowsiness or dizziness.
H372 Causes damage to the nervous system through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.

· **Precautionary statements**
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P261 Avoid breathing vapours.
P301+P310 If swallowed: Immediately call a poison center/doctor.
P331 Do NOT induce vomiting.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P501 Dispose of contents/container in accordance with national regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** PSRA
· **Contact:** PSRA
· **Date of preparation / last revision** 07/14/2026 / 44
· **Abbreviations and acronyms:**
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 14)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/14/2026 Reviewed on 07/14/2026

Trade name: GRF CLEANER TI 5L*1 L221

(Contd. of page 13)

vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flammable Liquids 2: Flammable liquids – Category 2
Skin Irritation 2: Skin corrosion/irritation – Category 2
Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A
Toxic to Reproduction 2: Reproductive toxicity – Category 2
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3
Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) – Category 1
Aspiration Hazard 1: Aspiration hazard – Category 1

· *** Data compared to the previous version altered.**

US