Safety Data Sheet
according to WHS Regulations

Date of issue: 14.07.2026 Version number 18 Revision: 14.07.2026

Hazardous according to criteria of Australian Safety and Compensation Council.

1 Identification

· **Other means of identification**

· **Trade name:** GRF HBS-200 RUBBER TIX JR 1L*6 L221
· **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
· **Application of the substance / the mixture** Sealant

· **Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**
Bison International B.V.
Dr.A.F.Philipsstraat 9
NL-4462 EW Goes
PO Box 160
NL-4460 AD Goes
tel. +31 88 3235700
fax. +31 88 3235800
e-mail: sds@boltonadhesives.com

FABER - CASTELL
15 GIBBON RD.
WINSTON HILL
NSW 2153
Toll Free: 1800 677 885
Free Fax: 1800 678 608
EMAIL: enquiries@faber-castell.com.au

· **Further information obtainable from:** PSRA
· **Emergency telephone number:**
POISONS INFORMATION CENTRE (PIC)
TEL: 13 11 26

*
2 Hazard(s) Identification

· **Classification of the substance or mixture**
Skin sensitisation – Category 1 H317 May cause an allergic skin reaction.

· **Label elements**
· **Hazard pictograms**



GHS07

· **Signal word** Warning

· **Hazard-determining components of labelling:**
Resin acids and Rosin acids, potassium salts (≥1-<10 %)
· **Hazard statements**
H317 May cause an allergic skin reaction.

(Contd. on page 2)

Safety Data Sheet
according to WHS Regulations

Date of issue: 14.07.2026 Version number 18 Revision: 14.07.2026

Trade name: GRF HBS-200 RUBBER TIX JR 1L*6 L221

(Contd. of page 1)

· **Precautionary statements**
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves.
P302+P352 IF ON SKIN: Wash with plenty of water.
P362+P364 Take off contaminated clothing and wash it before reuse.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P321 Specific treatment (see on this label).
· **Other hazards**
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable

3 Composition and Information on Ingredients

· **Chemical characterisation: Mixtures**
· **Description:** Sealant

· **Dangerous components:**

8052-42-4	Asphalt	30-60%
61790-50-9	Resin acids and Rosin acids, potassium salts Eye damage/irritation – Category 2A, H319; Skin sensitisation – Category 1, H317	≥1-<10%
61790-51-0	Resin acids and Rosin acids, sodium salts Eye damage/irritation – Category 2A, H319; Skin sensitisation – Category 1, H317	≥0.1-<1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

· **General information:** Immediately remove any clothing soiled by the product.
· **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
· **After eye contact:** Rinse opened eye for several minutes under running water.
· **After swallowing:** If symptoms persist consult doctor.
· **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire Fighting Measures

· **Suitable extinguishing agents:**
Use fire extinguishing methods suitable to surrounding conditions.

(Contd. on page 3)

Safety Data Sheet
according to WHS Regulations

Date of issue: 14.07.2026 Version number 18 Revision: 14.07.2026

Trade name: GRF HBS-200 RUBBER TIX JR 1L*6 L221

(Contd. of page 2)

· **Special hazards arising from the substance or mixture**
No further relevant information available.
· **Protective equipment:** No special measures required.

6 Accidental Release Measures

· **Personal precautions, protective equipment and emergency procedures** Not required
· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
· **Methods and material for containment and cleaning up:**
Send for recovery or disposal in suitable receptacles.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
· **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and Storage

· **Handling:**
· **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
· **Information about fire - and explosion protection:** No special measures required.
· **Storage:**
· **Requirements to be met by storerooms and receptacles:** No special requirements.
· **Information about storage in one common storage facility:** Not required
· **Further information about storage conditions:** None.
· **Storage class:** 12
· **Specific end use(s)** No further relevant information available.

8 Exposure controls and personal protection

· **Appropriate engineering controls** No further data; see section 7.

· **Ingredients with limit values that require monitoring at the workplace:**	
8052-42-4 Asphalt	
WES	Long-term value: 5 mg/m³ fumes

· **DNELs**		
61790-50-9 Resin acids and Rosin acids, potassium salts		
Oral	Consumer, oral, longterm exposition	1.065 mg/kg bw/day
Dermal	Worker, dermal, longterm exposition	2.131 mg/kg bw/day
	Consumer, dermal, longterm exposition	1.065 mg/kg bw/day
Inhalative	Worker, inhalative, longterm exposition	10 mg/m³

(Contd. on page 4)

Safety Data Sheet
according to WHS Regulations

Date of issue: 14.07.2026 Version number 18 Revision: 14.07.2026

Trade name: GRF HBS-200 RUBBER TIX JR 1L*6 L221

(Contd. of page 3)

61790-51-0 Resin acids and Rosin acids, sodium salts		
Oral	Consumer, oral, longterm exposition	1.0655 mg/kg bw/day
Dermal	Worker, dermal, longterm exposition	2.131 mg/kg bw/day
	Consumer, dermal, longterm exposition	1.0655 mg/kg bw/day
Inhalative	Worker, inhalative, longterm exposition	10 mg/m³

· **PNECs**

61790-50-9 Resin acids and Rosin acids, potassium salts	
Fresh water	0.002 mg/l
Fresh water sediment	0.007 mg/kg dry weight
Marine water	0.0002 mg/l
Marine sediment	0.001 mg/kg dry weight
Soil	0 mg/kg
Sewage treatment plant	1000 mg/l

· **Additional information:** The lists valid during the making were used as basis.
· **Personal protective equipment:**
· **General protective and hygienic measures:**
The usual precautionary measures are to be adhered to when handling chemicals.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
· **Respiratory protection:** Not required
· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
· **Material of gloves**
Recommended thickness of the material: > 0,12 mm
Nitrile rubber, NBR
· **Penetration time of glove material**
For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).
· **Eye protection:** Goggles recommended during refilling

*
9 Physical and Chemical Properties

· **General Information**
· **Appearance:**
· **Form:** Fluid
· **Colour:** According to product specification
· **Odour:** Characteristic

(Contd. on page 5)

Safety Data Sheet
according to WHS Regulations

Date of issue: 14.07.2026 Version number 18 Revision: 14.07.2026

Trade name: GRF HBS-200 RUBBER TIX JR 1L*6 L221

(Contd. of page 4)

· **Odour threshold:**	Not determined
· **pH-value:**	Not determined
· **Change in condition**	
· **Melting point/freezing point:**	Undetermined
· **Initial boiling point and boiling range:**	100 °C
· **Flash point:**	Not applicable
· **Flammability**	Not applicable
· **Decomposition temperature:**	Not determined
· **Ignition temperature:**	Product is not selfigniting.
· **Explosive properties:**	Product does not present an explosion hazard.
· **Explosion limits:**	
· **Lower:**	Not determined
· **Upper:**	Not determined
· **Vapour pressure at 20 °C:**	23 hPa
· **Density:**	Not determined
· **Relative density**	Not determined
· **Vapour density**	Not determined
· **Evaporation rate**	Not determined
· **Solubility in / Miscibility with**	
· **water:**	Not miscible or difficult to mix.
· **Partition coefficient: n-octanol/water:**	Not determined
· **Viscosity:**	
· **Dynamic:**	Not determined
· **Kinematic:**	Not determined
· **Solvent content:**	
· **Water:**	43.3 %
· **VOC (EC)**	0.00 %
· **Solids content:**	15.8 %
· **Other information**	All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.
· **Particle characteristics**	Not applicable
· **Physical state**	Liquid

10 Stability and Reactivity

· **Reactivity** No further relevant information available.
· **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
· **Possibility of hazardous reactions** No dangerous reactions known.
· **Conditions to avoid** No further relevant information available.
· **Incompatible materials:** No further relevant information available.
· **Hazardous decomposition products:** No dangerous decomposition products known.

AU

(Contd. on page 6)

Safety Data Sheet
according to WHS Regulations

Date of issue: 14.07.2026 Version number 18 Revision: 14.07.2026

Trade name: GRF HBS-200 RUBBER TIX JR 1L*6 L221

(Contd. of page 5)

11 Toxicological Information

· **Information on toxicological effects**
· **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**		
8052-42-4 Asphalt		
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)
61790-50-9 Resin acids and Rosin acids, potassium salts		
Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
61790-51-0 Resin acids and Rosin acids, sodium salts		
Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)

· **Primary irritant effect:**
· **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
· **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
· **Respiratory or skin sensitisation** May cause an allergic skin reaction.
· **Germ cell mutagenicity**
Not applicable
Based on available data, the classification criteria are not met.
· **Carcinogenicity** Based on available data, the classification criteria are not met.
· **Reproductive toxicity** Based on available data, the classification criteria are not met.
· **STOT-single exposure** Based on available data, the classification criteria are not met.
· **STOT-repeated exposure** Based on available data, the classification criteria are not met.
· **Aspiration hazard** Based on available data, the classification criteria are not met.
· **Interactive effects**
· **Acute effects (acute toxicity, irritation and corrosivity)** Not applicable
· **Sensitisation** Not applicable
· **Repeated dose toxicity** Not applicable

12 Ecological Information

· **Toxicity**
· **Aquatic toxicity:** No further relevant information available.
· **Persistence and degradability** No further relevant information available.
· **Behaviour in environmental systems:**
· **Bioaccumulative potential** No further relevant information available.
· **Mobility in soil** No further relevant information available.
· **Additional ecological information:**
· **General notes:**
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable

(Contd. on page 7)

Safety Data Sheet
according to WHS Regulations

Date of issue: 14.07.2026 Version number 18 Revision: 14.07.2026

Trade name: GRF HBS-200 RUBBER TIX JR 1L*6 L221

(Contd. of page 6)

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**
· **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Disposal must be made according to official regulations.

· **Uncleaned packaging:**
· **Recommendation:**
Packagings that may not be cleansed are to be disposed of in the same manner as the product.

14 Transport information

· **UN-Number**	
· **ADG, IMDG, IATA**	not regulated
	-
· **ADN**	not regulated
· **UN proper shipping name**	
· **ADG, ADN, IMDG, IATA**	not regulated
· **Transport hazard class(es)**	
· **ADG, ADN, IMDG, IATA**	
· **Class**	not regulated
· **Packing group**	
· **ADG, IMDG, IATA**	not regulated
· **Environmental hazards:**	Not applicable
· **Special precautions for user**	Not applicable
· **Transport in bulk according to Annex II of Marpol and the IBC Code**	Not applicable
· **Transport/Additional information:**	Not dangerous according to the above specifications.
· **UN "Model Regulation":**	not regulated

*
15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Australian Inventory of Industrial Chemicals**	
7732-18-5	water, distilled, conductivity or of similar purity

(Contd. on page 8)

Safety Data Sheet
according to WHS Regulations

Date of issue: 14.07.2026 Version number 18 Revision: 14.07.2026

Trade name: GRF HBS-200 RUBBER TIX JR 1L*6 L221

(Contd. of page 7)

8052-42-4	Asphalt
24937-78-8	Ethylene vinyl acetate copolymer
9010-98-4	polychloroprene
61790-50-9	Resin acids and Rosin acids, potassium salts
9004-62-0	Cellulose, 2-hydroxyethyl ether
9003-11-6	Polyoxyethylene-polyoxypropylene glycol
53320-86-8	Magnesium sodium lithium silicate
61790-51-0	Resin acids and Rosin acids, sodium salts
29329-71-3	(1-hydroxyethylidene)bisphosphonic acid, sodium salt
64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic
2634-33-5	1,2-benzisothiazol-3(2H)-one
52-51-7	Bronopol
7631-99-4	Sodium nitrate
126-99-8	chloroprene (stabilized)
2682-20-4	2-methyl-2H-isothiazol-3-one

· **Standard for the Uniform Scheduling of Medicines and Poisons**

1310-58-3	potassium hydroxide	S5, S6, S10
2682-20-4	2-methyl-2H-isothiazol-3-one	S6

· **Australia: Priority Existing Chemicals**

None of the ingredients is listed.

· **GHS label elements**
The product is classified and labelled according to the Globally Harmonised System (GHS).
· **Hazard pictograms**



GHS07

· **Signal word** Warning

· **Hazard-determining components of labelling:**
Resin acids and Rosin acids, potassium salts (≥1-<10 %)
· **Hazard statements**
H317 May cause an allergic skin reaction.
· **Precautionary statements**
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves.
P302+P352 IF ON SKIN: Wash with plenty of water.
P362+P364 Take off contaminated clothing and wash it before reuse.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P321 Specific treatment (see on this label).

· **Directive 2012/18/EU**
· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

(Contd. on page 9)

Safety Data Sheet
according to WHS Regulations

Date of issue: 14.07.2026 Version number 18 Revision: 14.07.2026

Trade name: GRF HBS-200 RUBBER TIX JR 1L*6 L221

(Contd. of page 8)

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

· **Department issuing SDS:** PSRA
· **Contact:** PSRA
· **Abbreviations and acronyms:**
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Eye damage/irritation – Category 2A: Serious eye damage/eye irritation – Category 2A
Skin sensitisation – Category 1: Skin sensitisation – Category 1
· *** Data compared to the previous version altered.**

AU