# Safety Data Sheet
## according to WHS Regulations

Date of issue: 17.07.2026 Version number 37 Revision: 17.07.2026

Hazardous according to criteria of Australian Safety and Compensation Council.

## 1 Identification

· **Other means of identification**

· **Trade name:** GRF WDF-05 BO 125ML*10 NLFR
· **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
· **Application of the substance / the mixture** Adhesive

· **Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**
Bison International B.V.
Dr.A.F.Philipsstraat 9
NL-4462 EW Goes
PO Box 160
NL-4460 AD Goes
tel. +31 88 3235700
fax. +31 88 3235800
e-mail: sds@boltonadhesives.com

FABER - CASTELL
15 GIBBON RD.
WINSTON HILL
NSW 2153
Toll Free: 1800 677 885
Free Fax: 1800 678 608
EMAIL: enquiries@faber-castell.com.au

· **Further information obtainable from:** PSRA
· **Emergency telephone number:**
POISONS INFORMATION CENTRE (PIC)
TEL: 13 11 26

## 2 Hazard(s) Identification

· **Classification of the substance or mixture**

| | |
|---|---|
| Flammable liquids – Category 2 | H225 Highly flammable liquid and vapour. |
| Skin corrosion/irritation – Category 2 | H315 Causes skin irritation. |
| Eye damage/irritation – Category 2A | H319 Causes serious eye irritation. |
| Specific target organ toxicity (single exposure) – Category 3 | H335 May cause respiratory irritation. |
| Specific target organ toxicity (single exposure) – Category 3 | H336 May cause drowsiness or dizziness. |

(Contd. on page 2)

# Safety Data Sheet
## according to WHS Regulations

Date of issue: 17.07.2026 Version number 37 Revision: 17.07.2026

**Trade name:** GRF WDF-05 BO 125ML*10 NLFR

(Contd. of page 1)

· **Label elements**
· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Danger
· **Hazard statements**
H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
· **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P261 Avoid breathing vapours.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P501 Dispose of contents/container in accordance with national regulations.
· **Additional information:**
AUH066 Repeated exposure may cause skin dryness or cracking.
· **Other hazards**
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable

* 
## 3 Composition and Information on Ingredients

· **Chemical characterisation: Mixtures**
· **Description:** Adhesive

· **Dangerous components:**

| | | |
|---|---|---|
| 109-99-9 | Tetrahydrofuran<br>Flammable liquids – Category 2, H225; Acute toxicity - oral – Category 4, H302; Skin corrosion/irritation – Category 2, H315; Eye damage/ irritation – Category 2A, H319; Specific target organ toxicity (single exposure) – Category 3, H335 | 30-60% |
| 78-93-3 | Butanone<br>Flammable liquids – Category 2, H225; Eye damage/irritation – Category 2A, H319; Specific target organ toxicity (single exposure) – Category 3, H335; Specific target organ toxicity (single exposure) – Category 3, H336 | 10-<30% |

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

AU

(Contd. on page 3)

# Safety Data Sheet
## according to WHS Regulations

Date of issue: 17.07.2026 Version number 37 Revision: 17.07.2026

**Trade name:** GRF WDF-05 BO 125ML*10 NLFR

(Contd. of page 2)

## 4 First Aid Measures

· **General information:** No special measures required.
· **After inhalation:**
In case of unconsciousness place patient stably in side position for transportation.
· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
· **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
· **After swallowing:** If symptoms persist consult doctor.
· **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

## 5 Fire Fighting Measures

· **Suitable extinguishing agents:**
Water haze
Alcohol resistant foam
Fire-extinguishing powder
Carbon dioxide
· **For safety reasons unsuitable extinguishing agents:** Water with full jet
· **Special hazards arising from the substance or mixture**
No further relevant information available.
· **Protective equipment:** No special measures required.
· **Additional information**
Cool endangered receptacles with water spray.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

## 6 Accidental Release Measures

· **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
· **Methods and material for containment and cleaning up:**
Send for recovery or disposal in suitable receptacles.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
· **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

AU

(Contd. on page 4)

# Safety Data Sheet
## according to WHS Regulations

Date of issue: 17.07.2026 Version number 37 Revision: 17.07.2026

**Trade name:** GRF WDF-05 BO 125ML*10 NLFR

(Contd. of page 3)

## 7 Handling and Storage

· **Handling:**
· **Precautions for safe handling**
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
· **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
· **Storage:**
· **Requirements to be met by storerooms and receptacles:** Store in a cool location.
· **Information about storage in one common storage facility:** Not required
· **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
· **Storage class:** 3
· **Specific end use(s)** No further relevant information available.

## 8 Exposure controls and personal protection

· **Appropriate engineering controls** No further data; see section 7.

| · **Ingredients with limit values that require monitoring at the workplace:** | |
|---|---|
| **109-99-9 Tetrahydrofuran** | |
| WES | Long-term value: 295 mg/m³, 100 ppm<br>Sk |
| **78-93-3 Butanone** | |
| WES | Short-term value: 890 mg/m³, 300 ppm<br>Long-term value: 445 mg/m³, 150 ppm |

| · **DNELs** | | |
|---|---|---|
| **109-99-9 Tetrahydrofuran** | | |
| Oral | Consumer, oral, longterm exposition | 1.5 mg/kg bw/day |
| Dermal | Worker, dermal, longterm exposition | 12.6 mg/kg bw/day |
| | Consumer, dermal, longterm exposition | 1.5 mg/kg bw/day |
| Inhalative | Worker, inhalative, shortterm exposition | 96 mg/m³ |
| | Worker, inhalative, longterm exposition | 72.4 mg/m³ |
| | Consumer DNEL, acute inhalation | 52 mg/m³ |
| | Consumer, inhalative, longterm exposition | 13 mg/m³ |
| **78-93-3 Butanone** | | |
| Oral | Consumer, oral, longterm exposition | 31 mg/kg bw/day |
| Dermal | Worker, dermal, longterm exposition | 1161 mg/kg bw/day |
| | Consumer, dermal, longterm exposition | 412 mg/kg bw/day |
| Inhalative | Worker, inhalative, shortterm exposition | 900 mg/m³ |
| | Worker, inhalative, longterm exposition | 600 mg/m³ |

(Contd. on page 5)

# Safety Data Sheet
## according to WHS Regulations

Date of issue: 17.07.2026 Version number 37 Revision: 17.07.2026

**Trade name:** GRF WDF-05 BO 125ML*10 NLFR

(Contd. of page 4)

| | | |
|---|---|---|
| | Consumer DNEL, acute inhalation | 450 mg/m³ |
| | Consumer, inhalative, longterm exposition | 106 mg/m³ |

· **PNECs**

| | | |
|---|---|---|
| **109-99-9 Tetrahydrofuran** | | |
| Oral | Secondary Poisoning | 67 mg/kg |
| | Fresh water | 4.32 mg/l |
| | Fresh water sediment | 23.3 mg/kg dry weight |
| | Marine water | 0.432 mg/l |
| | Marine sediment | 2.33 mg/kg dry weight |
| | Soil | 2.13 mg/kg |
| | Sewage treatment plant | 4.6 mg/l |
| | Sporadic release | 21.6 mg/l |
| **78-93-3 Butanone** | | |
| Oral | Secondary Poisoning | 1000 mg/kg |
| | Fresh water | 55.8 mg/l |
| | Fresh water sediment | 284.7 mg/kg dry weight |
| | Marine water | 55.8 mg/l |
| | Marine sediment | 284.7 mg/kg dry weight |
| | Soil | 22.5 mg/kg |
| | Sewage treatment plant | 709 mg/l |
| | Sporadic release | 55.8 mg/l |

· **Additional information:** The lists valid during the making were used as basis.
· **Personal protective equipment:**
· **General protective and hygienic measures:**
The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.
· **Respiratory protection:**
Suitable respiratory protective device recommended.
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Use suitable respiratory protective device in case of insufficient ventilation.
· **Recommended filter device for short term use:** Filter A
· **Protection of hands:**
Solvent resistant gloves



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 6)

# Safety Data Sheet
## according to WHS Regulations

Date of issue: 17.07.2026 Version number 37 Revision: 17.07.2026

**Trade name:** GRF WDF-05 BO 125ML*10 NLFR

(Contd. of page 5)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**
Recommended thickness of the material: > 0,12 mm
Butyl rubber, BR
Nitrile rubber, NBR
Recommended thickness of the material: > 0,7 mm

· **Penetration time of glove material**
For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).
For the mixture of chemicals mentioned below the penetration time has to be at least 120 minutes (Permeation according to EN 374 Part 3: Level 4).

· **Eye protection:**



Tightly sealed goggles

Goggles recommended during refilling

· **Body protection:** Solvent resistant protective clothing

## 9 Physical and Chemical Properties

| | |
|---|---|
| · **General Information** | |
| · **Appearance:** | |
| · **Form:** | Fluid |
| · **Colour:** | According to product specification |
| · **Odour:** | Characteristic |
| · **Odour threshold:** | Not determined |
| · **pH-value:** | Not determined |
| · **Change in condition** | |
| · **Melting point/freezing point:** | Undetermined |
| · **Initial boiling point and boiling range:** | 65.5 °C |
| · **Flash point:** | -21 °C |
| · **Flammability** | Highly flammable. |
| · **Auto-ignition temperature:** | 230 °C |
| · **Decomposition temperature:** | Not determined |
| · **Ignition temperature:** | Product is not selfigniting. |
| · **Explosive properties:** | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| · **Explosion limits:** | |
| · **Lower:** | 1.5 Vol % |
| · **Upper:** | 12 Vol % |
| · **Vapour pressure at 20 °C:** | 200 hPa |
| · **Vapour pressure at 50 °C:** | 550 hPa |
| · **Density at 20 °C:** | 0.965-0.966 g/cm³ |
| · **Relative density** | Not determined |
| · **Vapour density** | Not determined |

(Contd. on page 7)

# Safety Data Sheet
## according to WHS Regulations

Date of issue: 17.07.2026 Version number 37 Revision: 17.07.2026

**Trade name:** GRF WDF-05 BO 125ML*10 NLFR

(Contd. of page 6)

| | |
|---|---|
| · **Evaporation rate** | Not determined |
| · **Solubility in / Miscibility with** | |
| · **water:** | Not miscible or difficult to mix. |
| · **Partition coefficient: n-octanol/water:** | Not determined |
| · **Viscosity:** | |
| · **Dynamic at 20 °C:** | 675 mPas |
| · **Kinematic:** | Not determined |
| · **Solvent content:** | |
| · **Organic solvents:** | 82.9 % |
| · **VOC (EC)** | 82.92 % |
| · **Solids content:** | 16.9 % |
| · **Other information** | All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture. |
| · **Particle characteristics** | Not applicable |
| · **Physical state** | Liquid |

## 10 Stability and Reactivity

· **Reactivity** No further relevant information available.
· **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
· **Possibility of hazardous reactions** No dangerous reactions known.
· **Conditions to avoid** No further relevant information available.
· **Incompatible materials:** No further relevant information available.
· **Hazardous decomposition products:** Danger of forming toxic pyrolysis products.

## 11 Toxicological Information

· **Information on toxicological effects**
· **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

| | | |
|---|---|---|
| **109-99-9 Tetrahydrofuran** | | |
| Oral | LD50 | 500 mg/kg (rat) |
| Dermal | LD50 | >2000 mg/kg (rat) |
| Inhalative | LC50/4 h | >5000 mg/l (rat) |
| **78-93-3 Butanone** | | |
| Oral | LD50 | >2193 mg/kg (rat) |
| Dermal | LD50 | >8050 mg/kg (rat) |

· **Primary irritant effect:**
· **Skin corrosion/irritation**
Causes skin irritation.
· **Serious eye damage/irritation**
Causes serious eye irritation.

(Contd. on page 8)

# Safety Data Sheet
## according to WHS Regulations

Date of issue: 17.07.2026 Version number 37 Revision: 17.07.2026

**Trade name:** GRF WDF-05 BO 125ML*10 NLFR

(Contd. of page 7)

· **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
· **Germ cell mutagenicity**
Not applicable
Based on available data, the classification criteria are not met.
· **Carcinogenicity** Based on available data, the classification criteria are not met.
· **Reproductive toxicity** Based on available data, the classification criteria are not met.
· **STOT-single exposure** May cause respiratory irritation. May cause drowsiness or dizziness.
· **STOT-repeated exposure** Based on available data, the classification criteria are not met.
· **Aspiration hazard** Based on available data, the classification criteria are not met.
· **Interactive effects**
· **Acute effects (acute toxicity, irritation and corrosivity)** Not applicable
· **Sensitisation** Not applicable
· **Repeated dose toxicity** Not applicable

## 12 Ecological Information

· **Toxicity**
· **Aquatic toxicity:** No further relevant information available.
· **Persistence and degradability** No further relevant information available.
· **Behaviour in environmental systems:**
· **Bioaccumulative potential** No further relevant information available.
· **Mobility in soil** No further relevant information available.
· **Additional ecological information:**
· **General notes:**
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable
· **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

· **Waste treatment methods**
· **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Disposal must be made according to official regulations.

· **Uncleaned packaging:**
· **Recommendation:**
Packagings that may not be cleansed are to be disposed of in the same manner as the product.

AU

(Contd. on page 9)

# Safety Data Sheet
## according to WHS Regulations

Date of issue: 17.07.2026 Version number 37 Revision: 17.07.2026

**Trade name:** GRF WDF-05 BO 125ML*10 NLFR

(Contd. of page 8)

## 14 Transport information

| | |
|---|---|
| · **UN-Number** | |
| · **ADG, IMDG, IATA** | UN1133 |
| · **UN proper shipping name** | |
| · **ADG** | 1133 ADHESIVES |
| · **IMDG, IATA** | ADHESIVES |
| · **Transport hazard class(es)** | |
| · **ADG** |  |
| · **Class** | 3 (F1) Flammable liquids. |
| · **Label** | 3 |
| · **IMDG, IATA** |  |
| · **Class** | 3 Flammable liquids. |
| · **Label** | 3 |
| · **Packing group** | |
| · **ADG, IMDG, IATA** | III |
| · **Environmental hazards:** | |
| · **Marine pollutant:** | No |
| · **Special precautions for user** | Warning: Flammable liquids. |
| · **Hazard identification number (Kemler code):** | - |
| · **EMS Number:** | F-E,S-D |
| · **Stowage Category** | A |
| · **Transport in bulk according to Annex II of Marpol and the IBC Code** | Not applicable |
| · **Transport/Additional information:** | |
| · **Quantity limitations** | On passenger aircraft/rail: 60 L<br>On cargo aircraft only: 220 L |
| · **ADG** | |
| · **Limited quantities (LQ)** | 5L |
| · **Excepted quantities (EQ)** | Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml |
| · **Transport category** | 3 |
| · **Tunnel restriction code** | E |

(Contd. on page 10)

# Safety Data Sheet
## according to WHS Regulations

Date of issue: 17.07.2026 Version number 37 Revision: 17.07.2026

**Trade name:** GRF WDF-05 BO 125ML*10 NLFR

(Contd. of page 9)

| | |
|---|---|
| · **IMDG** | |
| · **Limited quantities (LQ)** | 5L |
| · **Excepted quantities (EQ)** | Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml |
| · **Remarks:** | For substances with class 3 according to IMDG-Code chapter 2.3.2.2 packing group is classified in packing group III, as viscosity is in accordance with requirements (flow time t > 100s). |
| · **UN "Model Regulation":** | UN 1133 ADHESIVES, 3, III |

## 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Australian Inventory of Industrial Chemicals**

All ingredients are listed.

· **Standard for the Uniform Scheduling of Medicines and Poisons**

| | | |
|---|---|---|
| 78-93-3 | Butanone | S5 |

· **Australia: Priority Existing Chemicals**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Danger

· **Hazard statements**

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P261 Avoid breathing vapours.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

(Contd. on page 11)

# Safety Data Sheet
## according to WHS Regulations

Date of issue: 17.07.2026 Version number 37 Revision: 17.07.2026

**Trade name:** GRF WDF-05 BO 125ML*10 NLFR

(Contd. of page 10)

P501 Dispose of contents/container in accordance with national regulations.

· **Directive 2012/18/EU**
· **Named dangerous substances - ANNEX I** None of the ingredients is listed.
· **Seveso category** P5c FLAMMABLE LIQUIDS
· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5000 t
· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50000 t
· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**
H225 Highly flammable liquid and vapour.
H302 Harmful if swallowed.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

· **Department issuing SDS:** PSRA
· **Contact:** PSRA
· **Abbreviations and acronyms:**
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flammable liquids – Category 2: Flammable liquids – Category 2
Acute toxicity - oral – Category 4: Acute toxicity – Category 4
Skin corrosion/irritation – Category 2: Skin corrosion/irritation – Category 2
Eye damage/irritation – Category 2A: Serious eye damage/eye irritation – Category 2A
Specific target organ toxicity (single exposure) – Category 3: Specific target organ toxicity (single exposure) – Category 3
· *** Data compared to the previous version altered.**

AU