# Safety Data Sheet
## acc. to OSHA HCS

Printing date 07/15/2026 Reviewed on 07/15/2026

## 1 Identification

· **Product identifier**

· **Trade name:** GRF SILICONE S-200 TR CQ 300ML*12 L001
· **Application of the substance / the mixture** Sealant

· **Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**
Bison International
Dr.A.F.Philipsstraat 9
NL-4462 EW Goes
PO Box 160
NL-4460 AD Goes
tel. +31 88 3235700
fax. +31 88 3235800
e mail: sds@boltonadhesives.com

· **Information department:** PSRA
· **Emergency telephone number:**
Bison and Griffon products: +31 88 3235700. Operating hours mo-fr 08:00h-17:00h (CET)
UHU products: + 49 (0) 30/19240 (Notruf). Operating hours mo-fr 08:00h-17:00h (CET)

For detailed information contact the national Poison Centre @
https://poisoncentres.echa.europa.eu/appointed-bodies

* 
## 2 Hazard(s) identification

· **Classification of the substance or mixture**
Sensitization - Skin 1 H317 May cause an allergic skin reaction.
Carcinogenicity 2 H351 Suspected of causing cancer.

· **Label elements**
· **Hazard pictograms**



GHS07 GHS08

· **Signal word** Warning

· **Hazard-determining components of labeling:**
??????????????????????????????????????????

· **Hazard statements**
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
· **Precautionary statements**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 If on skin: Wash with plenty of water.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P321 Specific treatment (see on this label).

(Contd. on page 2)

# Safety Data Sheet
## acc. to OSHA HCS

Printing date 07/15/2026 Reviewed on 07/15/2026

**Trade name:** GRF SILICONE S-200 TR CQ 300ML*12 L001

(Contd. of page 1)

· **Classification system:**
· **NFPA ratings (scale 0 - 4)**




Health = 0
Fire = 0
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**




Health = 0
Fire = 0
Reactivity = 0

· **Other hazards**
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable

## 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**
· **Description:** Sealant

· **Dangerous components:**

| | | |
|---|---|---|
| 64742-46-7 | Distillates (petroleum), hydtrotreated middle | 2.5-10% |
| 128446-60-6 | 3-Aminopropyl(methyl) silsesquioxanes, ethoxy-terminated | ≥2.5-<10% |
| 919-30-2 | 3-aminopropyltriethoxysilane | ≥0.1-<1% |
| 13463-67-7 | Titanium dioxide | ≥0.1-<1% |
| 1760-24-3 | N-(3-(trimethoxysilyl)propyl)ethylenediamine | ≥0.1-<1% |

## 4 First-aid measures

· **Description of first aid measures**
· **General information:** No special measures required.
· **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
· **After eye contact:** Rinse opened eye for several minutes under running water.
· **After swallowing:** If symptoms persist consult doctor.
· **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

US

(Contd. on page 3)

# Safety Data Sheet
## acc. to OSHA HCS

Printing date 07/15/2026 Reviewed on 07/15/2026

**Trade name:** GRF SILICONE S-200 TR CQ 300ML*12 L001

(Contd. of page 2)

## 5 Fire-fighting measures

· **Extinguishing media**
· **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
· **Special hazards arising from the substance or mixture**
No further relevant information available.
· **Advice for firefighters**
· **Protective equipment:** No special measures required.

* 

## 6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures** Not required
· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
· **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
· **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
· **Protective Action Criteria for Chemicals**

| · **PAC-1:** | | |
|---|---|---|
| 63148-62-9 | Polydimethylsiloxane | 80 mg/m3 |
| 112945-52-5 | fumed silica | 18 mg/m3 |
| 919-30-2 | 3-aminopropyltriethoxysilane | 5.3 mg/m3 |
| 13463-67-7 | Titanium dioxide | 15 mg/m3 |
| 1760-24-3 | N-(3-(trimethoxysilyl)propyl)ethylenediamine | 1.6 mg/m3 |

| · **PAC-2:** | | |
|---|---|---|
| 63148-62-9 | Polydimethylsiloxane | 730 mg/m3 |
| 112945-52-5 | fumed silica | 100 mg/m3 |
| 919-30-2 | 3-aminopropyltriethoxysilane | 59 mg/m3 |
| 13463-67-7 | Titanium dioxide | 170 mg/m3 |
| 1760-24-3 | N-(3-(trimethoxysilyl)propyl)ethylenediamine | 18 mg/m3 |

| · **PAC-3:** | | |
|---|---|---|
| 63148-62-9 | Polydimethylsiloxane | 4400 mg/m3 |
| 112945-52-5 | fumed silica | 630 mg/m3 |
| 919-30-2 | 3-aminopropyltriethoxysilane | 350 mg/m3 |
| 13463-67-7 | Titanium dioxide | 990 mg/m3 |
| 1760-24-3 | N-(3-(trimethoxysilyl)propyl)ethylenediamine | 110 mg/m3 |

US

(Contd. on page 4)

# Safety Data Sheet
## acc. to OSHA HCS

Printing date 07/15/2026 Reviewed on 07/15/2026

**Trade name:** GRF SILICONE S-200 TR CQ 300ML*12 L001

(Contd. of page 3)

## 7 Handling and storage

· **Handling:**
· **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
· **Information about protection against explosions and fires:**
Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**
· **Storage:**
· **Requirements to be met by storerooms and receptacles:** No special requirements.
· **Information about storage in one common storage facility:** Not required
· **Further information about storage conditions:** Keep receptacle tightly sealed.
· **Storage class:** 11
· **Specific end use(s)** No further relevant information available.

* 
## 8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see section 7.

· **Control parameters**
· **Components with limit values that require monitoring at the workplace:**
The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

| **13463-67-7 Titanium dioxide** | |
|---|---|
| PEL | Long-term value: 15* mg/m³<br>*total dust |
| REL | See Pocket Guide App. A |
| TLV | Long-term value: 0.2* 2.5** mg/m³<br>resp. fraction, *nanoscale,**finescale, A3 |

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**
· **Personal protective equipment:**
· **General protective and hygienic measures:**
The usual precautionary measures for handling chemicals should be followed.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
· **Breathing equipment:** Not required
· **Protection of hands:**



Protective gloves

(Contd. on page 5)

# Safety Data Sheet
## acc. to OSHA HCS

Printing date 07/15/2026 Reviewed on 07/15/2026

**Trade name:** GRF SILICONE S-200 TR CQ 300ML*12 L001

(Contd. of page 4)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**
Recommended thickness of the material: > 0,12 mm
Nitrile rubber, NBR

· **Penetration time of glove material**
For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

· **Eye protection:** Not required

## 9 Physical and chemical properties

| | |
|---|---|
| · **Information on basic physical and chemical properties** | |
| · **General Information** | |
| · **Appearance:** | |
| **Form:** | Fluid |
| **Color:** | According to product specification |
| · **Odor:** | Characteristic |
| · **Odor threshold:** | Not determined |
| · **pH-value:** | Not applicable |
| · **Change in condition** | |
| **Melting point/Melting range:** | Undetermined |
| **Boiling point/Boiling range:** | 2230 °C (4046 °F) |
| · **Flash point:** | Not applicable |
| · **Flammability:** | Not determined |
| · **Auto igniting:** | >370 °C (>698 °F) |
| · **Decomposition temperature:** | Not determined |
| · **Ignition temperature:** | Product is not selfigniting. |
| · **Danger of explosion:** | Product does not present an explosion hazard. |
| · **Explosion limits:** | |
| **Lower:** | Not determined |
| **Upper:** | Not determined |
| · **Vapor pressure:** | Not applicable |
| · **Density:** | Not determined |
| · **Relative density** | Not determined |
| · **Vapor density** | Not applicable |
| · **Evaporation rate** | Not applicable. |
| · **Solubility in / Miscibility with** | |
| **Water:** | Insoluble. |

(Contd. on page 6)

# Safety Data Sheet
## acc. to OSHA HCS

Printing date 07/15/2026 Reviewed on 07/15/2026

**Trade name:** GRF SILICONE S-200 TR CQ 300ML*12 L001

(Contd. of page 5)

| | |
|---|---|
| · **Partition coefficient (n-octanol/water):** | Not determined |
| · **Viscosity:** | |
| **Dynamic:** | Not applicable |
| **Kinematic:** | Not applicable |
| · **Solvent content:** | |
| **VOC content:** | 0.00 % |
| **Solids content:** | 100.0 % |
| · **Other information** | All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture. |

* 
## 10 Stability and reactivity

· **Reactivity** No further relevant information available.
· **Chemical stability**
· **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
· **Possibility of hazardous reactions** No dangerous reactions known.
· **Conditions to avoid** No further relevant information available.
· **Incompatible materials:** No further relevant information available.
· **Hazardous decomposition products:** No dangerous decomposition products known.
· **Additional information:** During curing methanol (CAS 67-56-1) is produced.

## 11 Toxicological information

· **Information on toxicological effects**
· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

| | | |
|---|---|---|
| **919-30-2 3-aminopropyltriethoxysilane** | | |
| Oral | LD50 | 1780 mg/kg (rat) |
| Dermal | LD50 | 4000 mg/kg (rabbit) |
| **13463-67-7 Titanium dioxide** | | |
| Oral | LD50 | >5000 mg/kg (rat) |
| Dermal | LD50 | >2000 mg/kg (rat) |
| Inhalative | LC50/4 h | >6.82 mg/l (rat) |
| **1760-24-3 N-(3-(trimethoxysilyl)propyl)ethylenediamine** | | |
| Oral | LD50 | 2295 mg/kg (rat) |
| Dermal | LD50 | >2000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 1.49 mg/l (rat) |

· **Primary irritant effect:**
· **on the skin:** No irritant effect.
· **on the eye:** No irritating effect.

(Contd. on page 7)

# Safety Data Sheet
## acc. to OSHA HCS

Printing date 07/15/2026 Reviewed on 07/15/2026

**Trade name:** GRF SILICONE S-200 TR CQ 300ML*12 L001

(Contd. of page 6)

· **Sensitization:** Sensitization possible through skin contact.
· **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

· **Carcinogenic categories**

| · **IARC (International Agency for Research on Cancer)** | | |
|---|---|---|
| 13463-67-7 | Titanium dioxide | 2B |

| · **NTP (National Toxicology Program)** |
|---|
| None of the ingredients is listed. |

| · **OSHA-Ca (Occupational Safety & Health Administration)** |
|---|
| None of the ingredients is listed. |

· **Germ cell mutagenicity** Not applicable

## 12 Ecological information

· **Toxicity**
· **Aquatic toxicity:** No further relevant information available.
· **Persistence and degradability** No further relevant information available.
· **Behavior in environmental systems:**
· **Bioaccumulative potential** No further relevant information available.
· **Mobility in soil** No further relevant information available.
· **Additional ecological information:**
· **General notes:**
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable
· **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

· **Waste treatment methods**
· **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
Disposal must be made according to official regulations.

· **Uncleaned packagings:**
· **Recommendation:**
Packagings that cannot be cleansed are to be disposed of in the same manner as the product.

US

(Contd. on page 8)

# Safety Data Sheet
## acc. to OSHA HCS

Printing date 07/15/2026 Reviewed on 07/15/2026

**Trade name:** GRF SILICONE S-200 TR CQ 300ML*12 L001

(Contd. of page 7)

## 14 Transport information

| | |
|---|---|
| · **UN-Number** | |
| · **DOT, ADN** | not regulated |
| · **ADR/ADN, IMDG, IATA** | not regulated |
| | - |
| · **UN proper shipping name** | |
| · **DOT, ADR/ADN, ADN, IMDG, IATA** | not regulated |
| · **Transport hazard class(es)** | |
| · **DOT, ADR/ADN, ADN, IMDG, IATA** | |
| · **Class** | not regulated |
| · **Packing group** | |
| · **DOT, ADR/ADN, IMDG, IATA** | not regulated |
| · **Environmental hazards:** | |
| · **Marine pollutant:** | No |
| · **Special precautions for user** | Not applicable |
| · **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** | Not applicable |
| · **Transport/Additional information:** | Not dangerous according to the above specifications. |
| · **UN "Model Regulation":** | not regulated |

* 

## 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**

| | | |
|---|---|---|
| 63148-62-9 | Polydimethylsiloxane | ACTIVE |
| 112945-52-5 | fumed silica | ACTIVE |
| 64742-46-7 | Distillates (petroleum), hydtrotreated middle | ACTIVE |
| 128446-60-6 | 3-Aminopropyl(methyl) silsesquioxanes, ethoxy-terminated | ACTIVE |
| 919-30-2 | 3-aminopropyltriethoxysilane | ACTIVE |
| 3087-39-6 | titanium(4)-2-methylpropane-2-oleate | ACTIVE |
| 13463-67-7 | Titanium dioxide | ACTIVE |
| 1760-24-3 | N-(3-(trimethoxysilyl)propyl)ethylenediamine | ACTIVE |

(Contd. on page 9)

# Safety Data Sheet
## acc. to OSHA HCS

Printing date 07/15/2026 Reviewed on 07/15/2026

**Trade name:** GRF SILICONE S-200 TR CQ 300ML*12 L001

(Contd. of page 8)

· **Hazardous Air Pollutants**
None of the ingredients is listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

| | |
|---|---|
| 13463-67-7 | Titanium dioxide |

· **Chemicals known to cause reproductive toxicity for females:**
None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**
None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**
None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**
None of the ingredients is listed.

· **TLV (Threshold Limit Value)**

| | | |
|---|---|---|
| 13463-67-7 | Titanium dioxide | A4 |

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

| | |
|---|---|
| 13463-67-7 | Titanium dioxide |

· **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
· **Hazard pictograms**



GHS07 GHS08

· **Signal word** Warning

· **Hazard-determining components of labeling:**
??????????????????????????????????????????????

· **Hazard statements**
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
· **Precautionary statements**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 If on skin: Wash with plenty of water.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P321 Specific treatment (see on this label).
· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

US

(Contd. on page 10)

# Safety Data Sheet
## acc. to OSHA HCS

Printing date 07/15/2026 Reviewed on 07/15/2026

**Trade name:** GRF SILICONE S-200 TR CQ 300ML*12 L001

(Contd. of page 9)

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** PSRA
· **Contact:** PSRA
· **Date of preparation / last revision** 07/15/2026 / 23
· **Abbreviations and acronyms:**
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Sensitization - Skin 1: Skin sensitisation – Category 1
Carcinogenicity 2: Carcinogenicity – Category 2
· *** Data compared to the previous version altered.**

US