# ALU ZINCSPRAY

## ALUMINIUM COLOURED, FAST DRYING ZINC COATING.




### PRODUCT DESCRIPTION
Aluminium coloured, fast drying zinc coating.

### FIELD OF APPLICATION
For protecting (cold galvanizing) of metal against rust and corrosion, such as bodywork, welding seams, fences, gutter brackets and stairs. Also to repair damage to previously galvanised metal.

### PROPERTIES
· Rust and corrosion resistant
· Aluminium coloured
· Quick-drying
· Electrically conductive
· Resistant to temperatures between -30°C to +120°C
· Contains 98% pure zinc
· Paintable

### PREPARATION
**Preliminary Surface Treatment:**Make sure that the surface is clean, dry, and free of grease. Remove rust, mill scale and loose coatings.

### APPLICATION
**Directions for use:**
Shake well before use.
Spray surface evenly and thinly from a distance of approx. 30 cm. It is better to apply several thin coatings than one thick coating. Apply the next layer within 10 minutes or 24 hours after the previous layer. Regularly shake during use. After use, hold the can upside down and spray until only propellant gas is released.
**Stains/residue:** Remove wet stains with thinner. Remove dry stains with paint stripper.

### TECHNICAL SPECIFICATIONS

| | |
|---|---|
| Chemical base: | Zinc/Alu powder in solvent mixture |
| Colour: | Aluminium |
| Minimum temperature resistance: | -30 °C |
| Maximum temperature resistance: | 120 °C |

### STORAGE CONDITIONS
Shelf life: At least 36 months after production.
Stored in unopened packaging between +5°C and +25°C.
Close packaging properly after use and store in a dry, cool, and frost-free location.
Limited shelf life after opening.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.