# CLEANER

## CLEANER FOR (RIGID) PVC, PVC-C AND ABS




### PRODUCT DESCRIPTION
Cleaner for (rigid) PVC, PVC-C and ABS.

### FIELD OF APPLICATION
For cleaning and degreasing pipes, sockets and fittings of (rigid) PVC, PVC-C and ABS. Also suitable for removing uncured adhesive residue and for cleaning brushes and tools. Use in combination with Griffon Cleaner Cloth.
Not suitable for diluting PVC, PVC-C and ABS adhesive.

### PROPERTIES
· Universal
· Very powerful cleaning properties

### APPLICATION
**Coverage:** Indication of the number of joints per 1 L:

| Ø | 32 | 40 | 50 | 63 | 75 | 90 | 110 | 125 | 160 | 200 | 250 |
|---|---|---|---|---|---|---|---|---|---|---|---|
| # | 800 | 700 | 650 | 550 | 330 | 250 | 160 | 140 | 90 | 50 | 35 |

**Directions for use:**
1. Apply cleaner to a Griffon Cleaner Cloth. 2. Clean and degrease surfaces. 3. Remove any condensation with Griffon Cleaner Cloth and allow surfaces to dry properly. Close packaging immediately after use.

### TECHNICAL SPECIFICATIONS

| | |
|---|---|
| Chemical base: | Mixture of solvents |
| Colour: | Colourless |
| Density approx.: | 0.82 g/cm$^3$ |
| Viscosity: | Liquid |
| Viscosity approx.: | 1 mPa·s |

### STORAGE CONDITIONS
Shelf life: At least 36 months after production.
Stored in unopened packaging between +5°C and +25°C.
Close packaging properly after use and store in a dry, cool, and frost-free location.
Limited shelf life after opening.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.